



SN331M035ST Information

www.helsener.com

For Reference Only

Part Number SN331M035ST

Manufacturer Cornell Dubilier Electronics (CDE)

Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 330UF 20% 35V RADIAL

Package Radial, Car

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com





Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SN331M035ST	Specifications
-------------	-----------------------

Manufacturer Cornell Dubilier Electronics (CDE) Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can Series SN Capacitance 330µF Tolerance ±20% Voltage - Rated 35V ESR (Equivalent Series Resistance) 560 mOhm @ 120Hz Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Bi-Polar Applications General Purpose Ripple Current - Low Frequency 630mA @ 120Hz Ripple Current - High Frequency - Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 0.984" (25.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can		
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can Series SN Capacitance 330µF Tolerance ±20% Voltage - Rated 35V ESR (Equivalent Series Resistance) 560 mOhm @ 120Hz Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Bi-Polar Applications General Purpose Ripple Current - Low Frequency 630mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 0.984" (25.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Manufacturer Part Number	SN331M035ST
Aluminum Electrolytic Capacitors	Manufacturer	Cornell Dubilier Electronics (CDE)
Package Radial, Can Series SN Capacitance 330µF Tolerance ±20% Voltage - Rated 35V ESR (Equivalent Series Resistance) 560 mOhm @ 120Hz Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Bi-Polar Applications General Purpose Ripple Current - Low Frequency 630mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 0.984" (25.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Category	Capacitors
Series SN Capacitance 330μF Tolerance ±20% Voltage - Rated 35V ESR (Equivalent Series Resistance) 560 mOhm @ 120Hz Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Bi-Polar Applications General Purpose Ripple Current - Low Frequency 630mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 0.984" (25.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can		Aluminum Electrolytic Capacitors
Capacitance 330µF Tolerance ±20% Voltage - Rated 35V ESR (Equivalent Series Resistance) 560 mOhm @ 120Hz Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Bi-Polar Applications General Purpose Ripple Current - Low Frequency 630mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 0.984" (25.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Package	Radial, Can
Tolerance ±20% Voltage - Rated 35V ESR (Equivalent Series Resistance) 560 mOhm @ 120Hz Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Bi-Polar Applications General Purpose Ripple Current - Low Frequency 630mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 0.984" (25.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Series	SN
Voltage - Rated ESR (Equivalent Series Resistance) ESR (Equivalent Series Resistance) Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Bi-Polar Applications General Purpose Ripple Current - Low Frequency 630mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Capacitance	330μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 1000 Hrs @ 85°C -40°C ~ 85°C Polarization Bi-Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing 10.295" (7.50mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Rio Monting Type 1000 Hrs @ 85°C -40°C ~ 85°C	Tolerance	±20%
Lifetime @ Temp. Operating Temperature -40°C ~ 85°C Polarization Bi-Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case 1000 Hrs @ 85°C -40°C ~ 85°C Bi-Polar General Purpose 630mA @ 120Hz - 0.29T' (7.50mm) 0.295" (7.50mm) 0.630" Dia (16.00mm)	Voltage - Rated	35V
Operating Temperature -40°C ~ 85°C Polarization Bi-Polar Applications General Purpose 630mA @ 120Hz Ripple Current - Low Frequency Ripple Current - High Frequency - Impedance Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	ESR (Equivalent Series Resistance)	560 mOhm @ 120Hz
Polarization Bi-Polar Applications General Purpose Ripple Current - Low Frequency 630mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 0.984" (25.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Lifetime @ Temp.	1000 Hrs @ 85°C
Applications Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case Ripple Current - Hugh Frequency - 1. 1. 1. 1. 1. 1. 1.	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency Ripple Current - High Frequency	Polarization	Bi-Polar
Ripple Current - High Frequency -	Applications	General Purpose
Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 0.984" (25.00mm) Surface Mount Land Size -	Ripple Current - Low Frequency	630mA @ 120Hz
Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 0.984" (25.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Ripple Current - High Frequency	-
Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 0.984" (25.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Impedance	-
Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Lead Spacing	0.295" (7.50mm)
Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Size / Dimension	0.630" Dia (16.00mm)
Mounting Type Through Hole Package / Case Radial, Can	Height - Seated (Max)	0.984" (25.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

SN331M035ST Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SN331M035ST Payment Methods



















SN331M035ST Shipping Methods













If you have any question about SN331M035ST, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com