

SP00A-24-61P(301)

SP00A-24-61P(301) Information

Heisener.com	SP00A-24-61P(301) Amphenol Industrial Operations Connectors, Interconnects Circular Connectors CONN RCPT 61POS WALL MNT PIN - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



SP00A-24-61P(301) Specifications

Manufacturer Part Number SP00A-24-61P(301) Manufacturer Amphenol Industrial Operations Category Connectors, Interconnects Package - Package - Series MIL-DTL-26482 Series I, SP Connector Type Receptacle, Male Pins Number of Positions 61 Shell Size - Insert 24-61 Mounting Type Panel Mount, Flange Mounting Type Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection - Shell Material, Finish - Contact Finish - Yoltage - Rated 600VAC Yoltage - Rated 600VAC		
CategoryConnectors, Interconnects Circular ConnectorsPackage-SeriesMIL-DTL-26482 Series I, SPConnector TypeReceptacle, Male PinsNumber of Positions61Shell Size - Insert24-61Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeBayonet LockOrientationN(Normal)Ingress Protection-Shell Material, Finish-Contact Finish-Yoltage - Rated600VACCurrent Rating7.5A	Manufacturer Part Number	SP00A-24-61P(301)
Initial ConnectorsPackage-SeriesMIL-DTL-26482 Series I, SPConnector TypeReceptacle, Male PinsNumber of Positions61Shell Size - Insert24-61Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeBayonet LockOrientation-Shell Material, Finish-Shell Material, Finish-Features-Yoltage - Rated60VACCurrent Rating5.5A	Manufacturer	Amphenol Industrial Operations
Package.SeriesMIL-DTL-26482 Series I, SPConnector TypeReceptacle, Male PinsNumber of Positions61Shell Size - Insert24-61Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeBayonet LockOrientation.Ingress Protection-Shell Material, Finish-Contact Finish-Features-Voltage - Rated600VACCurrent Rating7.5A	Category	Connectors, Interconnects
SeriesMIL-DTL-26482 Series I, SPConnector TypeReceptacle, Male PinsNumber of Positions61Shell Size - Insert24-61Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeBayonet LockOrientation.Ingress Protection-Shell Material, Finish-Contact Finish-Features-Voltage - Rated600VACCurrent Rating7.5A		Circular Connectors
Connector TypeReceptacle, Male PinsNumber of Positions61Shell Size - Insert24-61Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, Finish-Contact Finish-Fastening-Yoltage - Rated600VACCurrent Rating7.5A	Package	-
Number of Positions61Number of Positions24-61Shell Size - Insert24-61Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, Finish-Features-Foatures-Voltage - Rated600VACCurrent Rating7.5A	Series	MIL-DTL-26482 Series I, SP
Shell Size - Insert24-61Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, Finish-Contact Finish-Features-Voltage - Rated600VACCurrent Rating7.5A	Connector Type	Receptacle, Male Pins
And and Shell Size, MIL- Hard Mount, FlangeMounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, Finish-Contact Finish-Features-Voltage - Rated600VACCurrent Rating7.5A	Number of Positions	61
Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeBayonet LockOrientationN(Normal)Ingress Protection-Shell Material, Finish-Contact Finish-Features-Voltage - Rated600VACKurent Rating-Stell Material Finish-Solder Cup-Stell Material Finish-Stell Material Finish-Ste	Shell Size - Insert	24-61
TerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, Finish-Contact Finish-Features-Voltage - Rated600VACCurrent Rating7.5A	Shell Size, MIL	-
Fastening TypeBayonet LockOrientationN(Normal)Ingress Protection-Shell Material, Finish-Contact Finish-Features-Voltage - Rated600VACCurrent Rating7.5A	Mounting Type	Panel Mount, Flange
OrientationN(Normal)Ingress Protection-Shell Material, Finish-Contact Finish-Features-Voltage - Rated600VACCurrent Rating7.5A	Termination	Solder Cup
Ingress Protection-Shell Material, Finish-Contact Finish-Features-Voltage - Rated600VACCurrent Rating7.5A	Fastening Type	Bayonet Lock
Shell Material, Finish-Contact Finish-Features-Voltage - Rated600VACCurrent Rating7.5A	Orientation	N (Normal)
Contact Finish-Features-Voltage - Rated600VACCurrent Rating7.5A	Ingress Protection	-
Features-Voltage - Rated600VACCurrent Rating7.5A	Shell Material, Finish	-
Voltage - Rated600VACCurrent Rating7.5A	Contact Finish	-
Current Rating 7.5A	Features	-
-	Voltage - Rated	600VAC
Report errors?	Current Rating	7.5A
		Report errors?

SP00A-24-61P(301) Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE ELARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

SP00A-24-61P(301) Payment Methods



SP00A-24-61P(301) Shipping Methods



If you have any question about SP00A-24-61P(301), please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com