

# SR381C474MAR

### SR381C474MAR Information

Heisener.com	 SR381C474MAR AVX Corporation Capacitors Ceramic Capacitors CAP CER 0.47UF 100V X7R RADIAL Radial For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## SR381C474MAR Specifications

ManufacturerAVX CorporationCapacitorsCaranic CapacitorsPackageRadialSeriesSkyCap? SRCapacitance0.47µFTolerance±20%Voltage - Rated100VTomperature Coefficient55°C ~ 125°CPeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.300° L x 0.150° W (7.62mm x 3.81mm)Height - Seated (Max)0.425° (10.80mm)Thickness (Max)0.375° (9.52mm)		
Capacitors       Ceramic Capacitors       Package     Radial       Series     SkyCap? SR       Capacitors     (atal)       Capacitance     0.47µF       Tolerance     ±20%       Voltage - Rated     100V       Temperature Coefficient     X7R       Operating Temperature     -55°C ~ 125°C       Features     -       Applications     General Purpose       Applications     General Purpose       Failure Rate     -       Mounting Type     Through Hole       Size / Dimension     0.300" L x 0.150" W (7.62mm x 3.81mm)       Height - Seated (Max)     0.425" (10.80mm)       Thickness (Max)     0.375" (9.52mm)	Manufacturer Part Number	SR381C474MAR
Ceranic CapacitorsPackageRadialSeriesSkyCap? SRCapacitance0.47μFTolerance±20%Voltage - Rated100VTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.425" (10.80mm)Height - Seated (Max)-Thickness (Max)-Lead SpacingGornel Leads	Manufacturer	AVX Corporation
PackageRadialSeriesSkyCap? SRCapacitance0.47μFTolerance±20%Voltage - Rated100VTomperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / Case.300" L x 0.150" W (7.62mm x 3.81mm)Bize / Dimension0.425" (10.80mm)Thickness (Max)-Lead SpacingFormed Leads	Category	Capacitors
Series     SkyCap? SR       Capacitance     0.47µF       Tolerance     ±20%       Voltage - Rated     100V       Temperature Coefficient     X7R       Operating Temperature     -55°C ~ 125°C       Features     -       Ratings     -       Applications     General Purpose       Failure Rate     -       Mounting Type     Through Hole       Size / Dimension     0.300° L x 0.150° W (7.62mm x 3.81mm)       Height - Seated (Max)     -       Thickness (Max)     -       Lead Spacing     0.375° (9.52mm)		Ceramic Capacitors
Capacitance     0.47μF       Tolerance     ±20%       Voltage - Rated     100V       Temperature Coefficient     X7R       Operating Temperature     -55°C ~ 125°C       Features     -       Ratings     -       Applications     General Purpose       Failure Rate     -       Mounting Type     Through Hole       Package / Case     Radial       Size / Dimension     0.425" (10.80mm)       Thickness (Max)     -       Lead Spacing     0.375" (9.52mm)	Package	Radial
Tolerance±20%Voltage - Rated100VTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.425" (10.80mm)Height - Seated (Max)0.425" (10.80mm)Thickness (Max)-Lead StyleFormed Leads	Series	SkyCap? SR
Voltage - Rated100VTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.300" L x 0.150" W (7.62mm x 3.81mm)Height - Seated (Max)-Thickness (Max)0.375" (9.52mm)Lead SpacingFormed LeadsLead StyleFormed Leads	Capacitance	0.47µF
Temperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.425" (10.80mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.375" (9.52mm)Lead StyleFormed Leads	Tolerance	±20%
Operating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.300" L x 0.150" W (7.62mm x 3.81mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.375" (9.52mm)Lead StyleFormed Leads	Voltage - Rated	100V
Features-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.300" L x 0.150" W (7.62mm x 3.81mm)Height - Seated (Max)0.425" (10.80mm)Thickness (Max)-Lead Spacing0.375" (9.52mm)Lead StyleFormed Leads	Temperature Coefficient	X7R
Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.300" L x 0.150" W (7.62mm x 3.81mm)Height - Seated (Max)0.425" (10.80mm)Thickness (Max)-Lead Spacing0.375" (9.52mm)Height - Seated StyleFormed Leads	Operating Temperature	-55°C ~ 125°C
ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.300" L x 0.150" W (7.62mm x 3.81mm)Height - Seated (Max)0.425" (10.80mm)Thickness (Max)-Lead Spacing0.375" (9.52mm)Lead StyleFormed Leads	Features	-
Failure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.300" L x 0.150" W (7.62mm x 3.81mm)Height - Seated (Max)0.425" (10.80mm)Thickness (Max)-Lead Spacing0.375" (9.52mm)Lead StyleFormed Leads	Ratings	-
Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.300" L x 0.150" W (7.62mm x 3.81mm)Height - Seated (Max)0.425" (10.80mm)Thickness (Max)-Lead Spacing0.375" (9.52mm)Lead StyleFormed Leads	Applications	General Purpose
Package / CaseRadialSize / Dimension0.300" L x 0.150" W (7.62mm x 3.81mm)Height - Seated (Max)0.425" (10.80mm)Thickness (Max)-Lead Spacing0.375" (9.52mm)Lead StyleFormed Leads	Failure Rate	-
Size / Dimension   0.300" L x 0.150" W (7.62mm x 3.81mm)     Height - Seated (Max)   0.425" (10.80mm)     Thickness (Max)   -     Lead Spacing   0.375" (9.52mm)     Lead Style   Formed Leads	Mounting Type	Through Hole
Height - Seated (Max)0.425" (10.80mm)Thickness (Max)-Lead Spacing0.375" (9.52mm)Lead StyleFormed Leads	Package / Case	Radial
Thickness (Max) -   Lead Spacing 0.375" (9.52mm)   Lead Style Formed Leads	Size / Dimension	0.300" L x 0.150" W (7.62mm x 3.81mm)
Lead Spacing0.375" (9.52mm)Lead StyleFormed Leads	Height - Seated (Max)	0.425" (10.80mm)
Lead Style Formed Leads	Thickness (Max)	-
•	Lead Spacing	0.375" (9.52mm)
Report errors?	Lead Style	Formed Leads
		Report errors?

#### SR381C474MAR Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### SR381C474MAR Payment Methods



### SR381C474MAR Shipping Methods



If you have any question about SR381C474MAR, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com