



## ST1-L2-DC5V Information

Heisener.com

Part Number ST1-L2-DC5V

Manufacturer Panasonic Electric Works

**Category** Relays

Power Relays, Over 2 Amps

**Description** RELAY GENERAL PURPOSE DPST 8A 5V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com





Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **ST1-L2-DC5V Specifications**

Manufacturer Part NumberST1-L2-DC5VManufacturerPanasonic Electric WorksCategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesSTRelay TypeGeneral PurposeCoil TypeLatching, Dual CoilCoil Current45.5mACoil Voltage5VDCContact FormDPST-NO/NC (1 Form A and B)Contact Rating (Current)8ASwitching Voltage380VAC, 250VDC - MaxTurn On Voltage (Max)4 VDCTurn Off Voltage (Min)-Operate Time10msRelease Time10ms		
CategoryRelays Power Relays, Over 2 AmpsPackage-SeriesSTRelay TypeGeneral PurposeCoil TypeLatching, Dual CoilCoil Current45.5mACoil Voltage5VDCContact FormDPST-NO/NC (1 Form A and B)Contact Rating (Current)8ASwitching Voltage380VAC, 250VDC - MaxTurn On Voltage (Max)4 VDCTurn Off Voltage (Min)-Operate Time10ms	Manufacturer Part Number	ST1-L2-DC5V
Package - Series ST Relay Type General Purpose Coil Type Latching, Dual Coil Coil Current 45.5mA Coil Voltage 5VDC Contact Form DPST-NO/NC (1 Form A and B) Contact Rating (Current) 8A Switching Voltage Max) 4 VDC Turn Off Voltage (Min) - Operate Time 10  Power Relays, Over 2 Amps  Package  387  ST  General Purpose  Beneral Purpose  10 Sept. Authorized  A VDC  10 Sept. Authorized  10 Sept. A	Manufacturer	Panasonic Electric Works
Package - Series ST Relay Type General Purpose Coil Type Latching, Dual Coil Coil Current 45.5mA Coil Voltage 5VDC Contact Form DPST-NO/NC (1 Form A and B) Contact Rating (Current) 8A Switching Voltage Max) 4 VDC Turn Off Voltage (Max) 4 VDC Turn Off Voltage (Min) - Operate Time 10ms	Category	Relays
Series ST Relay Type General Purpose Coil Type Latching, Dual Coil Coil Current 45.5mA Coil Voltage 5VDC Contact Form DPST-NO/NC (1 Form A and B) Contact Rating (Current) 8A Switching Voltage 380VAC, 250VDC - Max Turn On Voltage (Max) 4 VDC Turn Off Voltage (Min) - Operate Time 10ms		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Latching, Dual Coil Coil Current 45.5mA Coil Voltage 5VDC Contact Form DPST-NO/NC (1 Form A and B) Contact Rating (Current) 8A Switching Voltage 380VAC, 250VDC - Max Turn On Voltage (Max) 4 VDC Turn Off Voltage (Min) - Operate Time 10ms	Package	-
Coil Type Latching, Dual Coil Coil Current 45.5mA Coil Voltage 5VDC Contact Form DPST-NO/NC (1 Form A and B) Contact Rating (Current) 8A Switching Voltage 380VAC, 250VDC - Max Turn On Voltage (Max) 4 VDC Turn Off Voltage (Min) - Operate Time 10ms	Series	ST
Coil Current 45.5mA  Coil Voltage 5VDC  Contact Form DPST-NO/NC (1 Form A and B)  Contact Rating (Current) 8A  Switching Voltage 380VAC, 250VDC - Max  Turn On Voltage (Max) 4 VDC  Turn Off Voltage (Min) -  Operate Time 10ms	Relay Type	General Purpose
Coil Voltage 5VDC  Contact Form DPST-NO/NC (1 Form A and B)  Contact Rating (Current) 8A  Switching Voltage 380VAC, 250VDC - Max  Turn On Voltage (Max) 4 VDC  Turn Off Voltage (Min) -  Operate Time 10ms	Coil Type	Latching, Dual Coil
Contact Form DPST-NO/NC (1 Form A and B)  Contact Rating (Current) 8A  Switching Voltage 380VAC, 250VDC - Max  Turn On Voltage (Max) 4 VDC  Turn Off Voltage (Min) -  Operate Time 10ms	Coil Current	45.5mA
Contact Rating (Current)  Switching Voltage  380VAC, 250VDC - Max  Turn On Voltage (Max)  4 VDC  Turn Off Voltage (Min)  Operate Time  10ms	Coil Voltage	5VDC
Switching Voltage 380VAC, 250VDC - Max  Turn On Voltage (Max) 4 VDC  Turn Off Voltage (Min) -  Operate Time 10ms	Contact Form	DPST-NO/NC (1 Form A and B)
Turn On Voltage (Max) 4 VDC Turn Off Voltage (Min) - Operate Time 10ms	Contact Rating (Current)	8A
Turn Off Voltage (Min)  Operate Time  - 10ms	Switching Voltage	380VAC, 250VDC - Max
Operate Time 10ms	Turn On Voltage (Max)	4 VDC
	Turn Off Voltage (Min)	-
Release Time 10ms	Operate Time	10ms
	Release Time	10ms
Features Sealed - Fully	Features	Sealed - Fully
Mounting Type Through Hole	Mounting Type	Through Hole
Termination Style PC Pin	Termination Style	PC Pin
Report errors?		Report errors?

#### ST1-L2-DC5V Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# ST1-L2-DC5V Payment Methods





















## **ST1-L2-DC5V Shipping Methods**













If you have any question about ST1-L2-DC5V, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com