



## **TE60B10RJ Information**

Heisener.com

Part Number TE60B10RJ

Manufacturer TE Connectivity Passive Product

Category Resistors

**Chassis Mount Resistors** 

**Description** RES CHAS MNT 10 OHM 5% 60W

Package Radial, Tubular

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we









## **TE60B10RJ Specifications**

Manufacturer Part Number         TE60B10RJ           Manufacturer         TE Connectivity Passive Product           Category         Resistors           Package         Radial, Tubular           Series         TE, CGS           Resistance         10 Ohms           Tolerance         ±5%           Power (Watts)         60W           Composition         Wirewound           Temperature Coefficient         ±440ppm/°C           Operating Temperature         -25°C ~ 225°C           Features         Flame Proof, Safety           Coating, Housing Type         Silicone Coated           Mounting Feature         Brackets           Size / Dimension         1.102" Dia x 4.016" L (28.00mm x 102.00mm)           Height - Seated (Max)         -           Lead Style         Solder Lugs           Package / Case         Radial, Tubular           Failure Rate         -	1200D10N3 Specifications	
CategoryResistorsPackageRadial, TubularSeriesTE, CGSResistance10 OhmsTolerance±5%Power (Watts)60WCompositionWirewoundTemperature Coefficient±440ppm/°COperating Temperature-25°C ~ 225°CFeaturesFlame Proof, SafetyCoating, Housing TypeSilicone CoatedMounting FeatureBracketsSize / Dimension1.102" Dia x 4.016" L (28.00mm x 102.00mm)Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-	Manufacturer Part Number	TE60B10RJ
Chassis Mount Resistors  Package Radial, Tubular  TE, CGS  Resistance 10 Ohms  Tolerance ±5%  Power (Watts) 60W  Composition Wirewound  Temperature Coefficient ±440ppm/°C Operating Temperature -25°C ~ 225°C  Features Flame Proof, Safety  Coating, Housing Type Silicone Coated  Mounting Feature Brackets Size / Dimension 1.102" Dia x 4.016" L (28.00mm x 102.00mm)  Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular  Failure Rate	Manufacturer	TE Connectivity Passive Product
PackageRadial, TubularSeriesTE, CGSResistance10 OhmsTolerance±5%Power (Watts)60WCompositionWirewoundTemperature Coefficient±440ppm/°COperating Temperature-25°C ~ 225°CFeaturesFlame Proof, SafetyCoating, Housing TypeSilicone CoatedMounting FeatureBracketsSize / Dimension1.102" Dia x 4.016" L (28.00mm x 102.00mm)Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-	Category	Resistors
SeriesTE, CGSResistance10 OhmsTolerance±5%Power (Watts)60WCompositionWirewoundTemperature Coefficient±440ppm/°COperating Temperature-25°C ~ 225°CFeaturesFlame Proof, SafetyCoating, Housing TypeSilicone CoatedMounting FeatureBracketsSize / Dimension1.102" Dia x 4.016" L (28.00mm x 102.00mm)Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-		Chassis Mount Resistors
Resistance 10 Ohms Tolerance ±5% Power (Watts) 60W Composition Wirewound Temperature Coefficient ±440ppm/°C Operating Temperature -25°C ~ 225°C Features Flame Proof, Safety Coating, Housing Type Silicone Coated Mounting Feature Brackets Size / Dimension 1.102" Dia x 4.016" L (28.00mm x 102.00mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate -	Package	Radial, Tubular
Tolerance ±5%  Power (Watts) 60W  Composition Wirewound  Temperature Coefficient ±440ppm/°C  Operating Temperature -25°C ~ 225°C  Features Flame Proof, Safety  Coating, Housing Type Silicone Coated  Mounting Feature Brackets  Size / Dimension 1.102" Dia x 4.016" L (28.00mm x 102.00mm)  Height - Seated (Max) -  Lead Style Solder Lugs  Package / Case Radial, Tubular  Failure Rate -	Series	TE, CGS
Power (Watts) 60W  Composition Wirewound  Temperature Coefficient ±440ppm/°C  Operating Temperature -25°C ~ 225°C  Features Flame Proof, Safety  Coating, Housing Type Silicone Coated  Mounting Feature Brackets  Size / Dimension 1.102" Dia x 4.016" L (28.00mm x 102.00mm)  Height - Seated (Max) -  Lead Style Solder Lugs  Package / Case Radial, Tubular  Failure Rate -	Resistance	10 Ohms
Composition Wirewound  Temperature Coefficient ±440ppm/°C  Operating Temperature -25°C ~ 225°C  Features Flame Proof, Safety  Coating, Housing Type Silicone Coated  Mounting Feature Brackets  Size / Dimension 1.102" Dia x 4.016" L (28.00mm x 102.00mm)  Height - Seated (Max) -  Lead Style Solder Lugs  Package / Case Radial, Tubular  Failure Rate -	Tolerance	±5%
Temperature Coefficient ±440ppm/°C  Operating Temperature -25°C ~ 225°C  Features Flame Proof, Safety  Coating, Housing Type Silicone Coated  Mounting Feature Brackets  Size / Dimension 1.102" Dia x 4.016" L (28.00mm x 102.00mm)  Height - Seated (Max) -  Lead Style Solder Lugs  Package / Case Radial, Tubular  Failure Rate -	Power (Watts)	60W
Operating Temperature  -25°C ~ 225°C  Features  Flame Proof, Safety  Coating, Housing Type  Silicone Coated  Mounting Feature  Brackets  Size / Dimension  1.102" Dia x 4.016" L (28.00mm x 102.00mm)  Height - Seated (Max)  -  Lead Style  Solder Lugs  Package / Case  Radial, Tubular  Failure Rate  -  -25°C ~ 225°C  Flame Proof, Safety  Silicone Coated  Solder Lugs  Radial, Tubular  -	Composition	Wirewound
Features Flame Proof, Safety Coating, Housing Type Silicone Coated Mounting Feature Brackets Size / Dimension 1.102" Dia x 4.016" L (28.00mm x 102.00mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate -	Temperature Coefficient	±440ppm/°C
Coating, Housing Type  Silicone Coated  Mounting Feature  Brackets  1.102" Dia x 4.016" L (28.00mm x 102.00mm)  Height - Seated (Max)  Lead Style  Solder Lugs  Package / Case  Radial, Tubular  Failure Rate  Silicone Coated  Brackets  1.102" Dia x 4.016" L (28.00mm x 102.00mm)	Operating Temperature	-25°C ~ 225°C
Mounting Feature  Size / Dimension  1.102" Dia x 4.016" L (28.00mm x 102.00mm)  Height - Seated (Max)  Lead Style  Package / Case  Radial, Tubular  Failure Rate  Brackets  Solder Lugs  Radial, Tubular  -	Features	Flame Proof, Safety
Size / Dimension 1.102" Dia x 4.016" L (28.00mm x 102.00mm)  Height - Seated (Max) -  Lead Style Solder Lugs  Package / Case Radial, Tubular  Failure Rate -	Coating, Housing Type	Silicone Coated
Height - Seated (Max)  Lead Style  Package / Case  Radial, Tubular  Failure Rate  -	Mounting Feature	Brackets
Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-	Size / Dimension	1.102" Dia x 4.016" L (28.00mm x 102.00mm)
Package / Case Radial, Tubular Failure Rate -	Height - Seated (Max)	-
Failure Rate -	Lead Style	Solder Lugs
	Package / Case	Radial, Tubular
Report errors?	Failure Rate	-
		Report errors?

### **TE60B10RJ Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **TE60B10RJ Payment Methods**



















## **TE60B10RJ Shipping Methods**













If you have any question about TE60B10RJ, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com