



### **TJT25047RJ Information**

ww.helsener.com

Part Number TJT25047RJ

Manufacturer TE Connectivity Passive Product

Category Resistors

**Chassis Mount Resistors** 

**Description** RES CHAS MNT 47 OHM 5% 250W

Package Rectangular Case

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **TJT25047RJ Specifications**

Manufacturer Part Number         TJT25047RJ           Manufacturer         TE Connectivity Passive Product           Category         Resistors           Package         Rectangular Case           Series         TJT           Resistance         47 Ohms           Tolerance         ±5%           Power (Watts)         250W           Composition         Wirewound           Temperature Coefficient         ±260ppm/°C           Operating Temperature         -25°C ~ 250°C           Features         -           Coating, Housing Type         Aluminum           Mounting Feature         Screw Holes           Size / Dimension         7.087" L x 3.150" W (180.00mm x 80.00mm)           Height - Seated (Max)         0.394" (10.00mm)           Lead Style         Wire Leads           Package / Case         Rectangular Case           Failure Rate         -    Report errors?		
CategoryResistorsPackageRectangular CaseSeriesTJTResistance47 OhmsTolerance±5%Power (Watts)250WCompositionWirewoundTemperature Coefficient±260ppm/°COperating Temperature-25°C ~ 250°CFeatures-Coating, Housing TypeAluminumMounting FeatureScrew HolesSize / Dimension7.087" L x 3.150" W (180.00mm x 80.00mm)Height - Seated (Max)0.394" (10.00mm)Lead StyleWire LeadsPackage / CaseRectangular CaseFailure Rate-	Manufacturer Part Number	TJT25047RJ
Chassis Mount Resistors  Package Rectangular Case  Series TJT  Resistance 47 Ohms  Tolerance ±5%  Power (Watts) 250W  Composition Wirewound  Temperature Coefficient ±260ppm/°C  Operating Temperature -25°C ~ 250°C  Features -  Coating, Housing Type Aluminum  Mounting Feature Screw Holes  Size / Dimension 7.087" L x 3.150" W (180.00mm x 80.00mm)  Height - Seated (Max) 0.394" (10.00mm)  Lead Style Wire Leads  Package / Case Rectangular Case  Failure Rate	Manufacturer	TE Connectivity Passive Product
Package         Rectangular Case           Series         TJT           Resistance         47 Ohms           Tolerance         ±5%           Power (Watts)         250W           Composition         Wirewound           Temperature Coefficient         ±260ppm/°C           Operating Temperature         -25°C ~ 250°C           Features         -           Coating, Housing Type         Aluminum           Mounting Feature         Screw Holes           Size / Dimension         7.087" L x 3.150" W (180.00mm x 80.00mm)           Height - Seated (Max)         0.394" (10.00mm)           Lead Style         Wire Leads           Package / Case         Rectangular Case           Failure Rate         -	Category	Resistors
Series         TJT           Resistance         47 Ohms           Tolerance         ±5%           Power (Watts)         250W           Composition         Wirewound           Temperature Coefficient         ±260ppm/°C           Operating Temperature         -25°C ~ 250°C           Features         -           Coating, Housing Type         Aluminum           Mounting Feature         Screw Holes           Size / Dimension         7.087" L x 3.150" W (180.00mm x 80.00mm)           Height - Seated (Max)         0.394" (10.00mm)           Lead Style         Wire Leads           Package / Case         Rectangular Case           Failure Rate         -		Chassis Mount Resistors
Resistance 47 Ohms Tolerance ±5% Power (Watts) 250W Composition Wirewound Temperature Coefficient ±260ppm/°C Operating Temperature -25°C ~ 250°C Features - Coating, Housing Type Aluminum Mounting Feature Screw Holes Size / Dimension 7.087" L x 3.150" W (180.00mm x 80.00mm) Height - Seated (Max) 0.394" (10.00mm) Lead Style Wire Leads Package / Case Rectangular Case Failure Rate -	Package	Rectangular Case
Tolerance ±5%  Power (Watts) 250W  Composition Wirewound  Temperature Coefficient ±260ppm/°C  Operating Temperature -25°C ~ 250°C  Features -  Coating, Housing Type Aluminum  Mounting Feature Screw Holes  Size / Dimension 7.087" L x 3.150" W (180.00mm x 80.00mm)  Height - Seated (Max) 0.394" (10.00mm)  Lead Style Wire Leads  Package / Case Rectangular Case  Failure Rate -	Series	TJT
Power (Watts)  Composition  Wirewound  Temperature Coefficient  ±260ppm/°C  Operating Temperature  -25°C ~ 250°C  Features  - Coating, Housing Type  Aluminum  Mounting Feature  Screw Holes  Size / Dimension  7.087" L x 3.150" W (180.00mm x 80.00mm)  Height - Seated (Max)  Lead Style  Wire Leads  Package / Case  Failure Rate  -  250W  Aluminum  Aluminum  Mounting Feature  Screw Holes  7.087" L x 3.150" W (180.00mm x 80.00mm)  Reight - Seated (Max)  Aluminum  Aluminum  Reteads  Failure Rate  -  -  -  -  -  -  -  -  -  -  -  -  -	Resistance	47 Ohms
Composition Wirewound  Temperature Coefficient ±260ppm/°C  Operating Temperature -25°C ~ 250°C  Features - Coating, Housing Type Aluminum  Mounting Feature Screw Holes  Size / Dimension 7.087" L x 3.150" W (180.00mm x 80.00mm)  Height - Seated (Max) 0.394" (10.00mm)  Lead Style Wire Leads  Package / Case Rectangular Case  Failure Rate -	Tolerance	±5%
Temperature Coefficient ±260ppm/°C  Operating Temperature -25°C ~ 250°C  Features -  Coating, Housing Type Aluminum  Mounting Feature Screw Holes  Size / Dimension 7.087" L x 3.150" W (180.00mm x 80.00mm)  Height - Seated (Max) 0.394" (10.00mm)  Lead Style Wire Leads  Package / Case Rectangular Case  Failure Rate -	Power (Watts)	250W
Operating Temperature -25°C ~ 250°C  Features - Coating, Housing Type Aluminum  Mounting Feature Screw Holes Size / Dimension 7.087" L x 3.150" W (180.00mm x 80.00mm)  Height - Seated (Max) 0.394" (10.00mm)  Lead Style Wire Leads  Package / Case Rectangular Case  Failure Rate -	Composition	Wirewound
Features - Coating, Housing Type Aluminum  Mounting Feature Screw Holes Size / Dimension 7.087" L x 3.150" W (180.00mm x 80.00mm)  Height - Seated (Max) 0.394" (10.00mm)  Lead Style Wire Leads  Package / Case Rectangular Case  Failure Rate -	Temperature Coefficient	±260ppm/°C
Coating, Housing Type  Mounting Feature  Screw Holes Size / Dimension  7.087" L x 3.150" W (180.00mm x 80.00mm)  Height - Seated (Max)  Lead Style  Package / Case  Rectangular Case  Failure Rate  Aluminum  Screw Holes  7.087" L x 3.150" W (180.00mm x 80.00mm)  Wire Leads  Wire Leads  Rectangular Case	Operating Temperature	-25°C ~ 250°C
Mounting Feature  Size / Dimension  7.087" L x 3.150" W (180.00mm x 80.00mm)  Height - Seated (Max)  0.394" (10.00mm)  Lead Style  Package / Case  Rectangular Case  Failure Rate  -	Features	-
Size / Dimension 7.087" L x 3.150" W (180.00mm x 80.00mm)  Height - Seated (Max) 0.394" (10.00mm)  Lead Style Wire Leads  Package / Case Rectangular Case  Failure Rate -	Coating, Housing Type	Aluminum
Height - Seated (Max)  Lead Style  Package / Case  Failure Rate  0.394" (10.00mm)  Wire Leads  Rectangular Case  -	Mounting Feature	Screw Holes
Lead StyleWire LeadsPackage / CaseRectangular CaseFailure Rate-	Size / Dimension	7.087" L x 3.150" W (180.00mm x 80.00mm)
Package / Case Rectangular Case Failure Rate -	Height - Seated (Max)	0.394" (10.00mm)
Failure Rate -	Lead Style	Wire Leads
	Package / Case	Rectangular Case
Report errors?	Failure Rate	-
		Report errors?

#### **TJT25047RJ Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **TJT25047RJ Payment Methods**



















# **TJT25047RJ Shipping Methods**













If you have any question about TJT25047RJ, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com