

TL6100AF130QPSSDOME

TL6100AF130QPSSDOME Information



For Reference Only

Part Number TL6100AF130QPSSDOME

Manufacturer E-Switch

Category Switches
Tactile Switches

Description SWITCH TACTILE SPST-NO 0.05A 12V

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









TL6100AF130QPSSDOME Specifications

Manufacturer Part Number TL6100AF130QPSSDOME Manufacturer E-Switch Category Switches Package - Series TL6100 Circuit SPST-NO Switch Function Off-Mom Contact Rating @ Voltage 0.05A @ 12VDC Actuator Type Standard Mounting Type Through Hole Actuator Height off PCB, Vertical 4.70mm Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style PC Pin Outline 7.20mm x 7.20mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 130gf Ingress Protection - Features Pannet server?		
Category Switches Package - Series TL6100 Circuit SPST-NO Switch Function Off-Mom Contact Rating @ Voltage 0.05A @ 12VDC Actuator Type Standard Mounting Type Through Hole Actuator Height off PCB, Vertical 4.70mm Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style PC Pin Outline 7.20mm x 7.20mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 130gf Ingress Protection - Features Stainless Steel Contact Dome	Manufacturer Part Number	TL6100AF130QPSSDOME
Package - Series TL6100 Circuit SPST-NO Switch Function Off-Mom Contact Rating @ Voltage 0.05A @ 12VDC Actuator Type Standard Mounting Type Through Hole Actuator Height off PCB, Vertical 4.70mm Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style PC Pin Outline 7.20mm x 7.20mm Illumination Type, Color 1.10minated Illumination Type, Color 1.30gf Ingress Protection - Stainless Steel Contact Dome	Manufacturer	E-Switch
Package-SeriesTL6100CircuitSPST-NOSwitch FunctionOff-MomContact Rating @ Voltage0.05A @ 12VDCActuator TypeStandardMounting TypeThrough HoleActuator Height off PCB, Vertical4.70mmActuator Length, Right Angle-Actuator OrientationTop ActuatedTermination StylePC PinOutline7.20mm x 7.20mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Operating Force130gfIngress Protection-FeaturesStainless Steel Contact Dome	Category	Switches
Series TL6100 Circuit SPST-NO Switch Function Off-Mom Contact Rating @ Voltage 0.05A @ 12VDC Actuator Type Standard Mounting Type Through Hole Actuator Height off PCB, Vertical 4.70mm Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style PC Pin Outline 7.20mm x 7.20mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 130gf Ingress Protection - Features Stainless Steel Contact Dome		Tactile Switches
CircuitSPST-NOSwitch FunctionOff-MomContact Rating @ Voltage0.05A @ 12VDCActuator TypeStandardMounting TypeThrough HoleActuator Height off PCB, Vertical4.70mmActuator Length, Right Angle-Actuator OrientationTop ActuatedTermination StylePC PinOutline7.20mm x 7.20mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Operating Force130gfIngress Protection-FeaturesStainless Steel Contact Dome	Package	-
Switch Function Contact Rating @ Voltage Actuator Type Standard Mounting Type Through Hole Actuator Height off PCB, Vertical Actuator Length, Right Angle Actuator Orientation Top Actuated Termination Style Outline Outline T.20mm x 7.20mm Illumination Illumination Type, Color Illumination Voltage (Nominal) Operating Force Ingress Protection Features Stainless Steel Contact Dome	Series	TL6100
Contact Rating @ Voltage Actuator Type Standard Mounting Type Through Hole Actuator Height off PCB, Vertical Actuator Length, Right Angle Actuator Orientation Top Actuated Termination Style Outline Outline Transition Type, Color Illumination Type, Color Illumination Voltage (Nominal) Operating Force Ingress Protection Features 0.05A @ 12VDC Standard On.05A @ 12VDC Standard On.05A @ 12VDC Standard On.05A @ 12VDC Standard On.05A @ 12VDC Standard Ones Standard O	Circuit	SPST-NO
Actuator Type Standard Mounting Type Through Hole Actuator Height off PCB, Vertical 4.70mm Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style PC Pin Outline 7.20mm x 7.20mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 130gf Ingress Protection - Features Stainless Steel Contact Dome	Switch Function	Off-Mom
Mounting TypeThrough HoleActuator Height off PCB, Vertical4.70mmActuator Length, Right Angle-Actuator OrientationTop ActuatedTermination StylePC PinOutline7.20mm x 7.20mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Operating Force130gfIngress Protection-FeaturesStainless Steel Contact Dome	Contact Rating @ Voltage	0.05A @ 12VDC
Actuator Height off PCB, Vertical 4.70mm Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style PC Pin Outline 7.20mm x 7.20mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 130gf Ingress Protection - Features Stainless Steel Contact Dome	Actuator Type	Standard
Actuator Length, Right Angle Actuator Orientation Top Actuated PC Pin Outline 7.20mm x 7.20mm Illumination Illumination Type, Color Illumination Voltage (Nominal) Operating Force Ingress Protection Features Stainless Steel Contact Dome	Mounting Type	Through Hole
Actuator Orientation Top Actuated Termination Style PC Pin Outline 7.20mm x 7.20mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 130gf Ingress Protection - Features Stainless Steel Contact Dome	Actuator Height off PCB, Vertical	4.70mm
Termination Style PC Pin Outline 7.20mm x 7.20mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 130gf Ingress Protection - Features Stainless Steel Contact Dome	Actuator Length, Right Angle	-
Outline 7.20mm x 7.20mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 130gf Ingress Protection - Features Stainless Steel Contact Dome	Actuator Orientation	Top Actuated
IlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Operating Force130gfIngress Protection-FeaturesStainless Steel Contact Dome	Termination Style	PC Pin
Illumination Type, Color - Illumination Voltage (Nominal) - Coperating Force 130gf Ingress Protection - Stainless Steel Contact Dome	Outline	7.20mm x 7.20mm
Illumination Voltage (Nominal) - Operating Force 130gf Ingress Protection - Features Stainless Steel Contact Dome	Illumination	Non-Illuminated
Operating Force130gfIngress Protection-FeaturesStainless Steel Contact Dome	Illumination Type, Color	-
Ingress Protection - Features Stainless Steel Contact Dome	Illumination Voltage (Nominal)	-
Features Stainless Steel Contact Dome	Operating Force	130gf
	Ingress Protection	-
Poport arrays	Features	Stainless Steel Contact Dome
Report errors?		Report errors?

TL6100AF130QPSSDOME Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

TL6100AF130QPSSDOME Payment Methods





















TL6100AF130QPSSDOME Shipping Methods













If you have any question about TL6100AF130QPSSDOME, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com