



TL6700AF260QJ Information

Part Number TL6700AF260QJ

Manufacturer E-Switch
Category Switches

Tactile Switches

Description SWITCH TACTILE SPST-NO 0.05A 12V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









TL6700AF260QJ Specifications

Manufacturer Part Number TL6700AF260QJ Manufacturer E-Switch Category Switches Package - Series TL6700 Circuit SPST-NO Switch Function Off-Mom Cotact Rating @ Voltage 0.05A @ 12VDC Actuator Type Standard Mounting Type Surface Mount Actuator Height off PCB, Vertical 3.40mm Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style J Lead Outline 6.90mm x 6.20mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 260gf Ingress Protection - Features Process Sealed		
Category Switches Package - Series TL6700 Circuit SPST-NO Switch Function Off-Mom Contact Rating @ Voltage 0.05A @ 12VDC Actuator Type Standard Mounting Type Surface Mount Actuator Height off PCB, Vertical 3.40mm Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style J Lead Outline 6.90mm x 6.20mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 260gf Ingress Protection - Features Process Sealed	Manufacturer Part Number	TL6700AF260QJ
Package - TL6700 Series TL6700 Circuit SPST-NO Switch Function Off-Mom Contact Rating @ Voltage 0.05A @ 12VDC Actuator Type Standard Mounting Type Surface Mount Actuator Height off PCB, Vertical 3.40mm Actuator Length, Right Angle - Top Actuated Termination Style J Lead Outline 6.90mm x 6.20mm Illumination Type, Color Illumination Type, Color Illumination Voltage (Nominal) - Coperating Force 260gf Ingress Protection - Features Process Sealed	Manufacturer	E-Switch
Package - Series TL6700 Circuit SPST-NO Switch Function Off-Mom Contact Rating @ Voltage 0.05A @ 12VDC Actuator Type Standard Mounting Type Surface Mount Actuator Height off PCB, Vertical 3.40mm Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style J Lead Outline 6.90mm x 6.20mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 260gf Ingress Protection - Features Process Sealed	Category	Switches
Series TL6700 Circuit SPST-NO Switch Function Off-Mom Contact Rating @ Voltage 0.05A @ 12VDC Actuator Type Standard Mounting Type Surface Mount Actuator Height off PCB, Vertical 3.40mm Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style J Lead Outline 6.90mm x 6.20mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 260gf Ingress Protection - Features Process Sealed		Tactile Switches
CircuitSPST-NOSwitch FunctionOff-MomContact Rating @ Voltage0.05A @ 12VDCActuator TypeStandardMounting TypeSurface MountActuator Height off PCB, Vertical3.40mmActuator Length, Right Angle-Actuator OrientationTop ActuatedTermination StyleJ LeadOutline6.90mm x 6.20mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Operating Force260gfIngress Protection-FeaturesProcess Sealed	Package	-
Switch Function Off-Mom Contact Rating @ Voltage 0.05A @ 12VDC Actuator Type Standard Mounting Type Surface Mount Actuator Height off PCB, Vertical 3.40mm Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style J Lead Outline 6.90mm x 6.20mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 260gf Ingress Protection - Features Process Sealed	Series	TL6700
Contact Rating @ Voltage Actuator Type Standard Mounting Type Surface Mount Actuator Height off PCB, Vertical Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style J Lead Outline 6.90mm x 6.20mm Illumination Illumination Type, Color - Illumination Voltage (Nominal) Operating Force Ingress Protection Features Process Sealed	Circuit	SPST-NO
Actuator Type Surface Mount Actuator Height off PCB, Vertical 3.40mm Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style J Lead Outline 6.90mm x 6.20mm Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 260gf Ingress Protection - Features Process Sealed	Switch Function	Off-Mom
Mounting Type Actuator Height off PCB, Vertical Actuator Length, Right Angle Actuator Orientation Top Actuated Termination Style J Lead Outline 6.90mm x 6.20mm Illumination Illumination Type, Color Illumination Voltage (Nominal) Operating Force 1.260gf Ingress Protection Features Surface Mount 3.40mm Actuator Mount 1.340mm Actuator Orientation Top Actuated 1.340mm Actuator Orientation Top Actuated 1.340mm T	Contact Rating @ Voltage	0.05A @ 12VDC
Actuator Height off PCB, Vertical Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style Outline 6.90mm x 6.20mm Illumination Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) Operating Force 100prating Force 110prating Force 120prating Force 120p	Actuator Type	Standard
Actuator Length, Right Angle Actuator Orientation Top Actuated Termination Style J Lead Outline 6.90mm x 6.20mm Illumination Illumination Type, Color Illumination Voltage (Nominal) Operating Force Ingress Protection Features - Process Sealed	Mounting Type	Surface Mount
Actuator Orientation Top Actuated Termination Style J Lead Outline 6.90mm x 6.20mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 260gf Ingress Protection - Features Process Sealed	Actuator Height off PCB, Vertical	3.40mm
Termination Style J Lead Outline 6.90mm x 6.20mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 260gf Ingress Protection - Features Process Sealed	Actuator Length, Right Angle	-
Outline 6.90mm x 6.20mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 260gf Ingress Protection - Features Process Sealed	Actuator Orientation	Top Actuated
IlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Operating Force260gfIngress Protection-FeaturesProcess Sealed	Termination Style	J Lead
Illumination Type, Color-Illumination Voltage (Nominal)-Operating Force260gfIngress Protection-FeaturesProcess Sealed	Outline	6.90mm x 6.20mm
Illumination Voltage (Nominal)-Operating Force260gfIngress Protection-FeaturesProcess Sealed	Illumination	Non-Illuminated
Operating Force260gfIngress Protection-FeaturesProcess Sealed	Illumination Type, Color	-
Ingress Protection Features Process Sealed	Illumination Voltage (Nominal)	-
Features Process Sealed	Operating Force	260gf
	Ingress Protection	-
Report errors?	Features	Process Sealed
		Report errors?

TL6700AF260QJ Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

TL6700AF260QJ Payment Methods



















TL6700AF260QJ Shipping Methods













If you have any question about TL6700AF260QJ, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com