

# **TPS77533PWP**

#### **TPS77533PWP Information**

Personal Construction	 TPS77533PWP Texas Instruments Integrated Circuits (ICs) PMIC - Voltage Regulators - Linear IC REG LIN 3.3V 500MA 20HTSSOP 20-TSSOP (0.173", 4.40mm Width) Exposed Pad For the pricing/inventory/lead time, please contact	
For Reference Only	Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



### **TPS77533PWP Specifications**

Manufacturer Part Number TPS77533PWP   Manufacturer Texas Instruments   Category Integrated Circuits (ICs)   PMIC - Voltage Regulators - Linear PMIC - Voltage Regulators - Linear   Package 20-TSSOP (0.173", 4.40mm Width) Exposed Pad   Series -   Output Configuration Positive   Output Type Fixed   Number of Regulators 1   Voltage - Input (Max) 10V   Voltage - Output (Min/Fixed) 3.3V   Voltage - Output (Max) -   Voltage - Output (Max) 0.29V @ 500mA   Current - Output 500mA   Current - Output 500mA   Current - Output 500mA   Current - Output 500mA   Strase 60dB (100Hz)   Postedometer 500mA   Current - Output 500mA   Outrent - Output 60dB (100Hz)   Output Features 60dB (100Hz)   Postedometer 60dB (100Hz)   Operating Fenetures 60dB (100Hz)   Operating Fenetures 60dB (100Hz) <th></th> <th></th> <th></th>			
CategoryIntegrated Circuits (ICs)PackagePMIC - Voltage Regulators - LinearPackage20-TSSOP (0.173", 4.40mm Width) Exposed PadSeries-Output ConfigurationPositiveOutput TypeFixedNumber of Regulators1Voltage - Input (Max)10VVoltage - Output (Min/Fixed)3.3VVoltage - Output (Max)-Voltage Dopout (Max)0.29V @ 500mACurrent - Output500mACurrent - Output125µAPSRR60dB (100Hz)Control FeaturesDove Current, Over Temperature, Reverse PolarityOperating Temperature40°C ~ 125°CMounting TypeSurface MountPackage / Case20-TSSOP (0.173", 4.40mm Width) Exposed PadSupplier Device Package0-HTSSOP	Manufacturer Part Number	TPS77533PWP	
PMIC - Voltage Regulators - LinearPackage20-TSSOP (0.173", 4.40mm Width) Exposed PadSeries-Output ConfigurationPositiveOutput TypeFixedNumber of Regulators1Voltage - Input (Max)10VVoltage - Output (Min/Fixed)3.3VVoltage - Output (Max)-Voltage Dropout (Max)0.29V @ 500mACurrent - Output500mACurrent - Quiescent (Iq)-Current - Supply (Max)125µAPSRR60dB (100Hz)Control FeaturesOver Current, Over Temperature, Reverse PolarityOperating Temperature-40°C ~ 125°CMounting TypeSurface MountPackage / Case20-TTSSOP (0.173", 4.40mm Width) Exposed PadSupplier Device Package20-HTSSOP	Manufacturer	Texas Instruments	
Package20-TSSOP (0.173", 4.40mm Width) Exposed PadSeries-Output ConfigurationPositiveOutput TypeFixedNumber of Regulators1Voltage - Input (Max)10VVoltage - Output (Min/Fixed)3.3VVoltage - Output (Max)0.29V @ 500mACurrent - Output-Current - Output500mACurrent - Quiescent (q)-Current - Supply (Max)125µAPSRR60dB (10Hz)Control FeaturesNove Current, Over Temperature, Reverse PolarityProtection Features0.40°C ~ 125°CMounting TypeSurface MountPackage / Case0.4TSSOP (0.173", 4.40mm Width) Exposed PadSupplier Device Package0.4TSSOP	Category	Integrated Circuits (ICs)	
Series-Output ConfigurationPositiveOutput TypeFixedNumber of Regulators1Voltage Input (Max)10VVoltage Output (Min/Fixed)3.3VVoltage Output (Max)-Voltage Dropout (Max)0.29V @ 500mACurrent - Output500mACurrent - Output125µAPSRR60dB (100Hz)Protection FeaturesOver Current, Over Temperature, Reverse PolarityOperating Temperature-40°C ~ 125°CMounting TypeSurGNOUTS", 4.40mm Width) Exposed PadPuppler Device Package20+HTSSOP		PMIC - Voltage Regulators - Linear	
Output ConfigurationPositiveOutput TypeFixedNumber of Regulators1Voltage - Input (Max)10VVoltage - Output (Mar)3.3VVoltage - Output (Max)-Voltage Dropout (Max)0.29V @ 500mACurrent - Output500mACurrent - Output125µAPoster Supply (Max)60dB (100Hz)Control Features60dB (100Hz)Protection Features0ver Current, Over Temperature, Reverse PolarityOperating Temperature40°C ~ 125°CMounting TypeSurface MountPackage / Case20-TSSOP (0.173°, 4.40mm Width) Exposed PadSupplier Device Package0.40°CSOP	Package	20-TSSOP (0.173", 4.40mm Width) Exposed Pad	
Output TypeFixedNumber of Regulators1Voltage - Input (Max)10VVoltage - Output (Min/Fixed)3.3VVoltage - Output (Max)-Voltage Dropout (Max)0.29V @ 500mACurrent - Output500mACurrent - Quiescent (Iq)-Current - Supply (Max)125µAPSRR60dB (100Hz)Protection FeaturesNew Current, Over Temperature, Reverse PolarityOperating Temperature-Protection FeaturesSurface MountMounting TypeSurface MountPackage / Case0-TSSOP (0.173", 4.40mm Width) Exposed PadSupplier Device Package0-HTSSOP	Series	-	
Number of Regulators1Number of Regulators10VVoltage - Input (Max)10VVoltage - Output (Min/Fixed)3.3VVoltage - Output (Max)-Voltage Dropout (Max)0.29V @ 500mACurrent - Output500mACurrent - Output500mACurrent - Quiescent (Iq)-Current - Supply (Max)125µAPSRR60dB (100Hz)Control FeaturesFeable, ResetProtection FeaturesOver Current, Over Temperature, Reverse PolarityOperating Temperature40°C ~ 125°CMounting TypeSurface MountPackage / Case20-HTSSOP (0.173", 4.40mm Width) Exposed Pad	Output Configuration	Positive	
Voltage - Input (Max)IOVVoltage - Output (Min/Fixed)3.3VVoltage - Output (Max)-Voltage Dropout (Max)0.29V @ 500mACurrent - Output500mACurrent - Quiescent (Iq)-Current - Supply (Max)125µAPSRR60dB (100Hz)Control FeaturesNover Current, Over Temperature, Reverse PolarityProtection Features-40°C ~ 125°CMounting TypeSurface MountPackage / Case20-TTSSOP (0.173", 4.40mm Width) Exposed PadSupplier Device Package20-HTSSOP	Output Type	Fixed	
Voltage - Output (Min/Fixed)3.3VVoltage - Output (Max)-Voltage Dropout (Max)0.29V @ 500mACurrent - Output500mACurrent - Quiescent (Iq)-Current - Supply (Max)125µAPSRR60dB (100Hz)Control FeaturesEnable, ResetProtection Features-40°C ~ 125°CMounting TypeSurface MountPackage / Case20-TSSOP (0.173", 4.40mm Width) Exposed PadSupplier Device Package20-HTSSOP	Number of Regulators	1	
Voltage - Output (Max)-Voltage Dropout (Max)0.29V @ 500mACurrent - Output500mACurrent - Quiescent (Iq)-Current - Supply (Max)125μAPSRR60dB (100Hz)Control FeaturesEnable, ResetProtection FeaturesOver Current, Over Temperature, Reverse PolarityOperating Temperature-40°C ~ 125°CMounting TypeSurface MountPackage / Case20-TSSOP (0.173", 4.40mm Width) Exposed PadSupplier Device Package20-HTSSOP	Voltage - Input (Max)	10V	
Voltage Dropout (Max)0.29V @ 500mACurrent - Output500mACurrent - Quiescent (Iq)-Current - Supply (Max)125μAPSRR60dB (100Hz)Control FeaturesEnable, ResetProtection FeaturesOver Current, Over Temperature, Reverse PolarityOperating Temperature-40°C ~ 125°CMounting TypeSurface MountPackage / Case20-TSSOP (0.173", 4.40mm Width) Exposed PadSupplier Device Package20-HTSSOP	Voltage - Output (Min/Fixed)	3.3V	
Current - Output500mACurrent - Quiescent (Iq)-Current - Supply (Max)125μAPSRR60dB (100Hz)Control FeaturesEnable, ResetProtection FeaturesOver Current, Over Temperature, Reverse PolarityOperating Temperature-40°C ~ 125°CMounting TypeSurface MountPackage / Case20-TSSOP (0.173", 4.40mm Width) Exposed PadSupplier Device Package20-HTSSOP	Voltage - Output (Max)	-	
Current - Quiescent (Iq)-Current - Supply (Max)125μAPSRR60dB (100Hz)Control FeaturesEnable, ResetProtection FeaturesOver Current, Over Temperature, Reverse PolarityOperating Temperature-40°C ~ 125°CMounting TypeSurface MountPackage / Case20-TSSOP (0.173", 4.40mm Width) Exposed PadSupplier Device Package20-HTSSOP	Voltage Dropout (Max)	0.29V @ 500mA	
Current - Supply (Max) 125μA   PSRR 60dB (100Hz)   Control Features Enable, Reset   Protection Features Over Current, Over Temperature, Reverse Polarity   Operating Temperature -40°C ~ 125°C   Mounting Type Surface Mount   Package / Case 20-TSSOP (0.173", 4.40mm Width) Exposed Pad   Supplier Device Package 20-HTSSOP	Current - Output	500mA	
PSRR60dB (100Hz)Control FeaturesEnable, ResetProtection FeaturesOver Current, Over Temperature, Reverse PolarityOperating Temperature-40°C ~ 125°CMounting TypeSurface MountPackage / Case20-TSSOP (0.173", 4.40mm Width) Exposed PadSupplier Device Package20-HTSSOP	Current - Quiescent (Iq)	-	
Control FeaturesEnable, ResetProtection FeaturesOver Current, Over Temperature, Reverse PolarityOperating Temperature-40°C ~ 125°CMounting TypeSurface MountPackage / Case20-TSSOP (0.173", 4.40mm Width) Exposed PadSupplier Device Package20-HTSSOP	Current - Supply (Max)	125μΑ	
Protection FeaturesOver Current, Over Temperature, Reverse PolarityOperating Temperature-40°C ~ 125°CMounting TypeSurface MountPackage / Case20-TSSOP (0.173", 4.40mm Width) Exposed PadSupplier Device Package20-HTSSOP	PSRR	60dB (100Hz)	
Operating Temperature-40°C ~ 125°CMounting TypeSurface MountPackage / Case20-TSSOP (0.173", 4.40mm Width) Exposed PadSupplier Device Package20-HTSSOP	Control Features	Enable, Reset	
Mounting TypeSurface MountPackage / Case20-TSSOP (0.173", 4.40mm Width) Exposed PadSupplier Device Package20-HTSSOP	Protection Features	Over Current, Over Temperature, Reverse Polarity	
Package / Case20-TSSOP (0.173", 4.40mm Width) Exposed PadSupplier Device Package20-HTSSOP	Operating Temperature	$-40^{\circ}\mathrm{C} \sim 125^{\circ}\mathrm{C}$	
Supplier Device Package 20-HTSSOP	Mounting Type	Surface Mount	
	Package / Case	20-TSSOP (0.173", 4.40mm Width) Exposed Pad	
Depart emerge	Supplier Device Package	20-HTSSOP	
Report errors?			Report errors?

#### **TPS77533PWP Guarantees**



Quality Guarantees


We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

# **TPS77533PWP Payment Methods**



If you have any question about TPS77533PWP, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com