

# TR/0603FA250-R

#### TR/0603FA250-R Information

w	Part Number Manufacturer Category Description Package	TR/0603FA250-R Eaton Circuit Protection Fuses FUSE BOARD MNT 250MA 50VDC 0603 0603 (1608 Metric) For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



### TR/0603FA250-R Specifications

Manufacturer Part NumberTR/0603FA250-RManufacturerEatonCategoryCircuit ProtectionFusesFusesPackage0603 (1608 Metric)SeriesCHIP? 0603FAFuse TypeBoard Mount (Cartridge Style Excluded)Current Rating250mAVoltage Rating - DC50VResponse TimeFastPackage / Case0603 (1608 Metric)Nounting TypeSol (1608 Metric)Response TimeSol (1608 Metric)Response TimeSol (1608 Metric)Reaking Capacity @ Rated VoltageSol (1608 Metric)Reaking Capacity @ Rated VoltageSol (1608 Metric)Munting TypeSol (1608 Metric)ApprovalsCSA, ULApprovalsSol (250°C)			
CategoryCircuit ProtectionFusesPackage6003 (1608 Metric)SeriesCHIP? 0603 FAFuse TypeBoard Mount (Cartridge Style Excluded)Current Rating250mAVoltage Rating - AC50VResponse TimeFastPackage / Case0603 (1608 Metric)Mounting TypeSurface MountBreaking Capacity @ Rated Voltage50AMounting Type50AMething Lat50AApprovals603 (1608 Metric)Mounting TypeSurface MountBreaking Capacity @ Rated Voltage50AMething Lat6004ApprovalsCSA, UL	Manufacturer Part Number	TR/0603FA250-R	
FusePackage6603 (1608 Metric)SeriesCHIP? 0603FAFuse TypeBoard Mount (Cartridge Style Excluded)Current Rating250mAVoltage Rating - AC-Voltage Rating - DC50VResponse TimeFastPackage / Case6003 (1608 Metric)Mounting TypeSurface MountBreaking Capacity @ Rated Voltage50AMelting L2t0.0004ApprovalsCSA, UL	Manufacturer	Eaton	
Package6003 (1608 Metric)Package6003 (1608 Metric)SeriesCHIP? 0603FAFuse TypeBoard Mount (Cartridge Style Excluded)Current Rating250mAVoltage Rating - AC-Voltage Rating - DC50VResponse TimeFastPackage / Case0603 (1608 Metric)Mounting TypeSurface MountBreaking Capacity @ Rated Voltage50AMelting I2t0.0004ApprovalsCSA, UL	Category	Circuit Protection	
SeriesCHIP? 0603FAFuse TypeBoard Mount (Cartridge Style Excluded)Current Rating250mAVoltage Rating - AC-Voltage Rating - DC50VResponse TimeFastPackage / Case0603 (1608 Metric)Mounting TypeSurface MountBreaking Capacity @ Rated Voltage50AMelting I2t0.0004ApprovalsCSA, UL		Fuses	
Fuse TypeBoard Mount (Cartridge Style Excluded)Fuse TypeSoard Mount (Cartridge Style Excluded)Current Rating250mAVoltage Rating - AC-Voltage Rating - DC50VResponse TimeFastPackage / Case0603 (1608 Metric)Mounting TypeSurface MountBreaking Capacity @ Rated Voltage50AMelting I2t0.0004ApprovalsCSA, UL	Package	0603 (1608 Metric)	
Current Rating250mAVoltage Rating - AC-Voltage Rating - DC50VResponse TimeFastPackage / Case0603 (1608 Metric)Mounting TypeSurface MountBreaking Capacity @ Rated Voltage50AMelting I2t0.0004ApprovalsCSA, UL	Series	CHIP? 0603FA	
Notage Rating - AC-Voltage Rating - DC50VResponse TimeFastPackage / Case0603 (1608 Metric)Mounting TypeSurface MountBreaking Capacity @ Rated Voltage50AMelting I2t0.0004ApprovalsCSA, UL	Fuse Type	Board Mount (Cartridge Style Excluded)	
Voltage Rating - DC50VResponse TimeFastPackage / Case0603 (1608 Metric)Mounting TypeSurface MountBreaking Capacity @ Rated Voltage50AMelting I2t0.0004ApprovalsCSA, UL	Current Rating	250mA	
Response TimeFastPackage / Case0603 (1608 Metric)Mounting TypeSurface MountBreaking Capacity @ Rated Voltage50AMelting I2t0.0004ApprovalsCSA, UL	Voltage Rating - AC	-	
Package / Case0603 (1608 Metric)Mounting TypeSurface MountBreaking Capacity @ Rated Voltage50AMelting I2t0.0004ApprovalsCSA, UL	Voltage Rating - DC	50V	
Mounting TypeSurface MountBreaking Capacity @ Rated Voltage50AMelting I2t0.0004ApprovalsCSA, UL	Response Time	Fast	
Breaking Capacity @ Rated Voltage50AMelting I2t0.0004ApprovalsCSA, UL	Package / Case	0603 (1608 Metric)	
Melting I2t0.0004ApprovalsCSA, UL	Mounting Type	Surface Mount	
Approvals CSA, UL	Breaking Capacity @ Rated Voltage	50A	
	Melting I2t	0.0004	
Operating Temperature -55°C ~ 125°C	Approvals	CSA, UL	
	Operating Temperature	-55°C ~ 125°C	
Color -	Color	-	
Size / Dimension 0.063" L x 0.032" W x 0.019" H (1.60mm x 0.81mm x 0.48mm)	Size / Dimension	0.063" L x 0.032" W x 0.019" H (1.60mm x 0.81mm x 0.48mm)	
Report errors?			Report errors?

#### TR/0603FA250-R Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### TR/0603FA250-R Payment Methods





If you have any question about TR/0603FA250-R, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com