



UBY1H112MHL Information



For Reference Only

Part Number UBY1H112MHL

Manufacturer Nichicon
Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 1100UF 20% 50V RADIAL

Package Radial, Car

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









UBY1H112MHL Specifications

Manufacturer Part NumberUBY1H112MHLManufacturerNichiconCategoryCapacitorsPackageAluminum Electrolytic CapacitorsPackageRadial, CanSeriesUBYCapacitance1100µFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)37 mOhm @ 100kHzLifetime @ Temp.3000 Hrs @ 135°COperating Temperature-40°C ~ 135°CPolarizationPolarApplicationsAutomotiveRipple Current - Low Frequency1.512A @ 120HzRipple Current - High Frequency2.52A @ 100kHzImpedance-
CategoryCapacitorsPackageRadial, CanSeriesUBYCapacitance1100μFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)37 mOhm @ 100kHzLifetime @ Temp.3000 Hrs @ 135°COperating Temperature-40°C ~ 135°CPolarizationPolarApplicationsAutomotiveRipple Current - Low Frequency1.512A @ 120HzRipple Current - High Frequency2.52A @ 100kHzImpedance-
PackageAluminum Electrolytic CapacitorsPackageRadial, CanSeriesUBYCapacitance1100μFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)37 mOhm @ 100kHzLifetime @ Temp.3000 Hrs @ 135°COperating Temperature-40°C ~ 135°CPolarizationPolarApplicationsAutomotiveRipple Current - Low Frequency1.512A @ 120HzRipple Current - High Frequency2.52A @ 100kHzImpedance-
Package Radial, Can Series UBY Capacitance 1100µF Tolerance ±20% Voltage - Rated 50V ESR (Equivalent Series Resistance) 37 mOhm @ 100kHz Lifetime @ Temp. 3000 Hrs @ 135°C Operating Temperature -40°C ~ 135°C Polarization Polar Applications Automotive Ripple Current - Low Frequency 1.512A @ 120Hz Ripple Current - High Frequency 2.52A @ 100kHz Impedance -
SeriesUBYCapacitance1100μFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)37 mOhm @ 100kHzLifetime @ Temp.3000 Hrs @ 135°COperating Temperature-40°C ~ 135°CPolarizationPolarApplicationsAutomotiveRipple Current - Low Frequency1.512A @ 120HzRipple Current - High Frequency2.52A @ 100kHzImpedance-
Capacitance 1100µF Tolerance ±20% Voltage - Rated 50V ESR (Equivalent Series Resistance) 37 mOhm @ 100kHz Lifetime @ Temp. 3000 Hrs @ 135°C Operating Temperature -40°C ~ 135°C Polarization Polar Applications Automotive Ripple Current - Low Frequency 1.512A @ 120Hz Ripple Current - High Frequency 2.52A @ 100kHz Impedance -
Tolerance ±20% Voltage - Rated 50V ESR (Equivalent Series Resistance) 37 mOhm @ 100kHz Lifetime @ Temp. 3000 Hrs @ 135°C Operating Temperature -40°C ~ 135°C Polarization Polar Applications Automotive Ripple Current - Low Frequency 1.512A @ 120Hz Ripple Current - High Frequency 2.52A @ 100kHz Impedance -
Voltage - Rated ESR (Equivalent Series Resistance) Lifetime @ Temp. Operating Temperature Polarization Applications Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Sov 37 mOhm @ 100kHz 3000 Hrs @ 135°C -40°C ~ 135°C Polar Automotive 1.512A @ 120Hz 2.52A @ 100kHz
ESR (Equivalent Series Resistance) Lifetime @ Temp. 3000 Hrs @ 135°C Operating Temperature -40°C ~ 135°C Polarization Polar Applications Automotive Ripple Current - Low Frequency Ripple Current - High Frequency Impedance 37 mOhm @ 100kHz 3000 Hrs @ 135°C -40°C ~ 135°C Polar 2-1512A @ 120Hz 2-152A @ 120Hz
Lifetime @ Temp. 3000 Hrs @ 135°C Operating Temperature -40°C ~ 135°C Polarization Polar Applications Automotive Ripple Current - Low Frequency 1.512A @ 120Hz Ripple Current - High Frequency 2.52A @ 100kHz Impedance -
Operating Temperature -40°C ~ 135°C Polarization Polar Applications Automotive Ripple Current - Low Frequency Ripple Current - High Frequency 2.52A @ 100kHz Impedance -
Polarization Polar Applications Automotive Ripple Current - Low Frequency 1.512A @ 120Hz Ripple Current - High Frequency 2.52A @ 100kHz Impedance -
Applications Ripple Current - Low Frequency Ripple Current - High Frequency 2.52A @ 100kHz Impedance -
Ripple Current - Low Frequency Ripple Current - High Frequency Impedance 1.512A @ 120Hz 2.52A @ 100kHz
Ripple Current - High Frequency 2.52A @ 100kHz Impedance -
Impedance -
Lead Spacing 0.197" (5.00mm)
Size / Dimension 0.492" Dia (12.50mm)
Height - Seated (Max) 1.299" (33.00mm)
Surface Mount Land Size -
Mounting Type Through Hole
Package / Case Radial, Can
Report errors?

UBY1H112MHL Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

UBY1H112MHL Payment Methods



















UBY1H112MHL Shipping Methods













If you have any question about UBY1H112MHL, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com