



## **UEP0J682MHD Information**



For Reference Only

Part Number UEP0J682MHD

Manufacturer Nichicon Category Capacitors

Aluminum Electrolytic Capacitors

**Description** CAP ALUM 6800UF 20% 6.3V RADIAL

Package Radial, Car

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **UEP0J682MHD Specifications**

Category         Capacitors           Package         Radial, Can           Series         UEP           Capacitance         6800µF           Tolerance         ±20%           Voltage - Rated         6.3V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         1000 Hrs @ 105°C           Operating Temperature         -55°C ~ 105°C           Polarization         Bi-Polar           Applications         General Purpose           Ripple Current - Low Frequency         1.83A @ 120Hz           Ripple Current - High Frequency         2.1045A @ 10kHz           Impedance         -           Lead Spacing         0.295" (7.50mm)           Size / Dimension         0.709" Dia (18.00mm)           Height - Seated (Max)         1.476" (37.50mm)           Surface Mount Land Size         -           Mounting Type         Through Hole	-	
Category         Capacitors           Aluminum Electrolytic Capacitors           Package         Radial, Can           Series         UEP           Capacitance         6800µF           Tolerance         ±20%           Voltage - Rated         6.3V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         1000 Hrs @ 105°C           Operating Temperature         -55°C ~ 105°C           Polarization         Bi-Polar           Applications         General Purpose           Ripple Current - Low Frequency         1.83A @ 120Hz           Ripple Current - High Frequency         2.1045A @ 10kHz           Impedance         -           Lead Spacing         0.295" (7.50mm)           Size / Dimension         0.709" Dia (18.00mm)           Height - Seated (Max)         1.476" (37.50mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can	Manufacturer Part Number	UEP0J682MHD
Package         Radial, Can           Series         UEP           Capacitance         6800μF           Tolerance         ±20%           Voltage - Rated         6.3V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         1000 Hrs @ 105°C           Operating Temperature         -55°C ~ 105°C           Polarization         Bi-Polar           Applications         General Purpose           Ripple Current - Low Frequency         1.83A @ 120Hz           Ripple Current - High Frequency         2.1045A @ 10kHz           Impedance         -           Lead Spacing         0.295" (7.50mm)           Size / Dimension         0.709" Dia (18.00mm)           Height - Seated (Max)         1.476" (37.50mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can	Manufacturer	Nichicon
Package         Radial, Can           Series         UEP           Capacitance         6800µF           Tolerance         ±20%           Voltage - Rated         6.3V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         1000 Hrs @ 105°C           Operating Temperature         -55°C ~ 105°C           Polarization         Bi-Polar           Applications         General Purpose           Ripple Current - Low Frequency         1.83A @ 120Hz           Ripple Current - High Frequency         2.1045A @ 10kHz           Impedance         -           Lead Spacing         0.295" (7.50mm)           Size / Dimension         0.709" Dia (18.00mm)           Height - Seated (Max)         1.476" (37.50mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can	Category	Capacitors
Series         UEP           Capacitance         6800µF           Tolerance         ±20%           Voltage - Rated         6.3V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         1000 Hrs @ 105°C           Operating Temperature         -55°C ~ 105°C           Polarization         Bi-Polar           Applications         General Purpose           Ripple Current - Low Frequency         1.83A @ 120Hz           Ripple Current - High Frequency         2.1045A @ 10kHz           Impedance         -           Lead Spacing         0.295" (7.50mm)           Size / Dimension         0.709" Dia (18.00mm)           Height - Seated (Max)         1.476" (37.50mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can		Aluminum Electrolytic Capacitors
Capacitance       6800μF         Tolerance       ±20%         Voltage - Rated       6.3V         ESR (Equivalent Series Resistance)       -         Lifetime @ Temp.       1000 Hrs @ 105°C         Operating Temperature       -55°C ~ 105°C         Polarization       Bi-Polar         Applications       General Purpose         Ripple Current - Low Frequency       1.83A @ 120Hz         Ripple Current - High Frequency       2.1045A @ 10kHz         Impedance       -         Lead Spacing       0.295" (7.50mm)         Size / Dimension       0.709" Dia (18.00mm)         Height - Seated (Max)       1.476" (37.50mm)         Surface Mount Land Size       -         Mounting Type       Through Hole         Package / Case       Radial, Can	Package	Radial, Can
Tolerance       ±20%         Voltage - Rated       6.3V         ESR (Equivalent Series Resistance)       -         Lifetime @ Temp.       1000 Hrs @ 105°C         Operating Temperature       -55°C ~ 105°C         Polarization       Bi-Polar         Applications       General Purpose         Ripple Current - Low Frequency       1.83A @ 120Hz         Ripple Current - High Frequency       2.1045A @ 10kHz         Impedance       -         Lead Spacing       0.295" (7.50mm)         Size / Dimension       0.709" Dia (18.00mm)         Height - Seated (Max)       1.476" (37.50mm)         Surface Mount Land Size       -         Mounting Type       Through Hole         Package / Case       Radial, Can	Series	UEP
Voltage - Rated  ESR (Equivalent Series Resistance)  Lifetime @ Temp.  1000 Hrs @ 105°C  Operating Temperature  -55°C ~ 105°C  Polarization  Bi-Polar  Applications  General Purpose  Ripple Current - Low Frequency  1.83A @ 120Hz  Ripple Current - High Frequency  2.1045A @ 10kHz  Impedance  -  Lead Spacing  0.295" (7.50mm)  Size / Dimension  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can	Capacitance	6800μF
ESR (Equivalent Series Resistance)  Lifetime @ Temp.  1000 Hrs @ 105°C  Operating Temperature  -55°C ~ 105°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  1.83A @ 120Hz  Ripple Current - High Frequency  2.1045A @ 10kHz  Impedance  - Lead Spacing  0.295" (7.50mm)  Size / Dimension  0.709" Dia (18.00mm)  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can	Tolerance	±20%
Lifetime @ Temp.  Operating Temperature  -55°C ~ 105°C  Polarization  Bi-Polar  Applications  General Purpose  Ripple Current - Low Frequency  1.83A @ 120Hz  Ripple Current - High Frequency  2.1045A @ 10kHz  Impedance  - Lead Spacing  0.295" (7.50mm)  Size / Dimension  Height - Seated (Max)  1.476" (37.50mm)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can	Voltage - Rated	6.3V
Operating Temperature -55°C ~ 105°C Polarization Bi-Polar Applications General Purpose Ripple Current - Low Frequency 1.83A @ 120Hz Ripple Current - High Frequency 2.1045A @ 10kHz Impedance - Lead Spacing 0.295" (7.50mm) Size / Dimension 0.709" Dia (18.00mm) Height - Seated (Max) 1.476" (37.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	ESR (Equivalent Series Resistance)	-
Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Ripple Current - Low Frequency Ripple Cur	Lifetime @ Temp.	1000 Hrs @ 105°C
Applications General Purpose Ripple Current - Low Frequency 1.83A @ 120Hz Ripple Current - High Frequency 2.1045A @ 10kHz Impedance - Lead Spacing 0.295" (7.50mm) Size / Dimension 0.709" Dia (18.00mm) Height - Seated (Max) 1.476" (37.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Operating Temperature	-55°C ~ 105°C
Ripple Current - Low Frequency  Ripple Current - High Frequency  2.1045A @ 10kHz  Impedance  - Lead Spacing  0.295" (7.50mm)  Size / Dimension  0.709" Dia (18.00mm)  Height - Seated (Max)  1.476" (37.50mm)  Surface Mount Land Size  - Mounting Type  Through Hole  Package / Case  Radial, Can	Polarization	Bi-Polar
Ripple Current - High Frequency  2.1045A @ 10kHz  Impedance  - Lead Spacing  0.295" (7.50mm)  Size / Dimension  0.709" Dia (18.00mm)  Height - Seated (Max)  1.476" (37.50mm)  Surface Mount Land Size  - Mounting Type  Through Hole  Package / Case  Radial, Can	Applications	General Purpose
Impedance - Lead Spacing 0.295" (7.50mm) Size / Dimension 0.709" Dia (18.00mm) Height - Seated (Max) 1.476" (37.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Ripple Current - Low Frequency	1.83A @ 120Hz
Lead Spacing 0.295" (7.50mm) Size / Dimension 0.709" Dia (18.00mm) Height - Seated (Max) 1.476" (37.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Ripple Current - High Frequency	2.1045A @ 10kHz
Size / Dimension 0.709" Dia (18.00mm)  Height - Seated (Max) 1.476" (37.50mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can	Impedance	-
Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can	Lead Spacing	0.295" (7.50mm)
Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Size / Dimension	0.709" Dia (18.00mm)
Mounting Type Through Hole Package / Case Radial, Can	Height - Seated (Max)	1.476" (37.50mm)
Package / Case Radial, Can	Surface Mount Land Size	-
-	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

#### **UEP0J682MHD Guarantees**



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **UEP0J682MHD Payment Methods**



















### **UEP0J682MHD Shipping Methods**













If you have any question about UEP0J682MHD, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com