

UKW0J682MHD

Request a Quote

UKW0J682MHD Information

	Part Number	UKW0J682MHD	
www.heisoner.com	Manufacturer		Г
	Category	Capacitors Aluminum Electrolytic Capacitors	
	Description	CAP ALUM 6800UF 20% 6.3V RADIAL	
	Package	Radial, Can	
		For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com	L
For Reference Only		E-mail: salesdept@heisener.com	

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



UKW0J682MHD Specifications

CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesUKWCapacitance6800µFTolerance±20%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature900 Hrs @ 85°CPolarizationPolarApplicationsAudioRipple Current - Low Frequency1.6A @ 120HzRipple Current - High Frequency1.84A @ 10kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.949" Dia (12.50mm)Height - Seated (Max)0.944" (25.00mm)Surface Mount Land Size-Pounting TypeThrough HolePackage / CaseKadia, Can	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesUKWCapacitance6800µFTolerance±20%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature900 Hrs @ 85°CPolarizationPolarApplicationsAudioRipple Current - Low Frequency1.6A @ 120HzRipple Current - High Frequency1.84A @ 10kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.949" Dia (12.50mm)Height - Seated (Max)0.944" (25.00mm)Surface Mount Land Size-Pounting TypeThrough HolePackage / CaseKadia, Can	Manufacturer Part Number	UKW0J682MHD
IndextorAdminum Electrolytic CapacitorsPackageRadial, CanSeriesUKWCapacitance6800µFTolerance120%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Operating Temperature2000 Hrs @ 85°COperating Temperature640°C ~ 85°CPolarizationAudioApplications1.6A @ 120HzRipple Current - High Frequency1.84A @ 10kHzImpedance0.197° (.50mm)Siz / Dimension0.492° Dia (12.50mm)Siz / Dimension0.944° (25.00mm)Hight - Seated (Max)0.984° (.50.00mm)Surface Mount Land Size-Mounting TypeFacuacitationPackage / CaseKadial, Can	Manufacturer	Nichicon
PackageRadial, CanSeriesUKWCapacitance6800µFTolerance±20%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Operating Temperature2000 Hrs @ 85°COperating TemperaturePolarApplicationsAudioRipple Current - Low Frequency1.6A @ 120HzRipple Current - High Frequency0.197" (5.00mm)Siz / Dimension0.492" Dia (12.50mm)Siz / Dimension0.948" (25.00mm)Siz / Dimension0.948" (25.00mm)Surface Mount Land Size-Mounting TypeHolePackage / CaseKadial, Can	Category	Capacitors
SeriesUKWCapacitance6800µFTolerance±20%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsAudioRipple Current - Low Frequency1.6A @ 120HzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.944" (25.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKadia, Can		Aluminum Electrolytic Capacitors
Capacitance6800µFTolerance±20%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsAudioRipple Current - Low Frequency1.6A @ 120HzInpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.984" (25.00mm)Height - Seated (Max)0.984" (25.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKalia, Can	Package	Radial, Can
Tolerance±20%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsAudioRipple Current - Low Frequency1.6A @ 120HzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.984" (25.00mm)Height - Seated (Max)0.984" (25.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can	Series	UKW
Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarPolarApplicationsAudioApple Current - Low Frequency1.6A @ 120HzRipple Current - High Frequency0.197" (5.00mm)Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.948" (25.00mm)Height - Seated (Max)0.984" (25.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can	Capacitance	6800µF
ESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsAudioRipple Current - Low Frequency1.6A @ 120HzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.984" (25.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Tolerance	±20%
Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsAudioRipple Current - Low Frequency1.6A @ 120HzRipple Current - High Frequency1.84A @ 10kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.984" (25.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Voltage - Rated	6.3V
Operating Temperature -40°C ~ 85°C Polarization Polar Applications Audio Ripple Current - Low Frequency 1.6A @ 120Hz Ripple Current - High Frequency 1.84A @ 10kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 0.984" (25.00mm) Surface Mount Land Size - Mounting Type Finough Hole Package / Case Radial, Can	ESR (Equivalent Series Resistance)	-
PolarizationPolarPolarizationPolarApplicationsAudioRipple Current - Low Frequency1.6A @ 120HzRipple Current - High Frequency1.84A @ 10kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.984" (25.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	2000 Hrs @ 85°C
ApplicationsAudioApplicationsAudioRipple Current - Low Frequency1.6A @ 120HzRipple Current - High Frequency1.84A @ 10kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.984" (25.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Operating Temperature	-40°C ~ 85°C
IIIIIRipple Current - Low Frequency1.6A @ 120HzRipple Current - High Frequency1.84A @ 10kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.984" (25.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Polarization	Polar
Ripple Current - High Frequency1.84A @ 10kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.984" (25.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Applications	Audio
Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.984" (25.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	1.6A @ 120Hz
Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.984" (25.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	1.84A @ 10kHz
Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.984" (25.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	-
Height - Seated (Max)0.984" (25.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.197" (5.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.492" Dia (12.50mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	0.984" (25.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
• • • • • • • • • • • • • • • • • • •	Mounting Type	Through Hole
Benert errors?	Package / Case	Radial, Can
Report errors?		Report errors?

UKW0J682MHD Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

UKW0J682MHD Payment Methods



UKW0J682MHD Shipping Methods



If you have any question about UKW0J682MHD, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com