



UPT2W560MHD Information



For Reference Only

Part Number UPT2W560MHD

Manufacturer Nichicon
Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 56UF 20% 450V RADIAL

Package Radial, Car

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









UPT2W560MHD Specifications

Manufacturer Part Number UPT2W560MHD Manufacturer Nichicon Category Capacitors Package Radial, Can Series UPT Capacitance 56μF Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 5000 Hrs @ 105°C Operating Temperature -25°C ~ 105°C Polarization - Applications General Purpose Ripple Current - Low Frequency 440mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 1.457" (37.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can		
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can Series UPT Capacitance 56µF Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 5000 Hrs @ 105°C Operating Temperature -25°C ~ 105°C Polarization - Applications General Purpose Ripple Current - Low Frequency 440mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 1.457" (37.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Manufacturer Part Number	UPT2W560MHD
Package Radial, Can Series UPT Capacitance 56μF Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 5000 Hrs @ 105°C Operating Temperature -25°C ~ 105°C Polarization - Applications General Purpose Ripple Current - Low Frequency 440mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 1.457" (37.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Manufacturer	Nichicon
Package Radial, Can Series UPT Capacitance 56μF Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 5000 Hrs @ 105°C Operating Temperature -25°C ~ 105°C Polarization - Applications General Purpose Ripple Current - Low Frequency 440mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 1.457" (37.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Category	Capacitors
Series UPT Capacitance 56μF Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 5000 Hrs @ 105°C Operating Temperature -25°C ~ 105°C Polarization - Applications General Purpose Ripple Current - Low Frequency 440mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 1.457" (37.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can		Aluminum Electrolytic Capacitors
Capacitance 56µF Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 5000 Hrs @ 105°C Operating Temperature -25°C ~ 105°C Polarization - Applications General Purpose Ripple Current - Low Frequency 440mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 1.457" (37.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Package	Radial, Can
Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 5000 Hrs @ 105°C Operating Temperature -25°C ~ 105°C Polarization - Applications General Purpose Ripple Current - Low Frequency 440mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 1.457" (37.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Series	UPT
Voltage - Rated ESR (Equivalent Series Resistance) Lifetime @ Temp. 5000 Hrs @ 105°C Operating Temperature -25°C ~ 105°C Polarization Applications General Purpose Ripple Current - Low Frequency At 40mA @ 120Hz Ripple Current - High Frequency Impedance Lead Spacing 0.295" (7.50mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Raiol 105°C -25°C ~ 105°C -25°C	Capacitance	56μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 5000 Hrs @ 105°C Operating Temperature -25°C ~ 105°C Polarization Applications General Purpose Ripple Current - Low Frequency 440mA @ 120Hz Ripple Current - High Frequency Impedance - Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 1.457" (37.00mm) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Tolerance	±20%
Lifetime @ Temp. 5000 Hrs @ 105°C Operating Temperature -25°C ~ 105°C Polarization - Applications General Purpose Ripple Current - Low Frequency 440mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 1.457" (37.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Voltage - Rated	450V
Operating Temperature -25°C ~ 105°C Polarization - Applications General Purpose Ripple Current - Low Frequency 440mA @ 120Hz Ripple Current - High Frequency - Impedance Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 1.457" (37.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	ESR (Equivalent Series Resistance)	-
Polarization - General Purpose Ripple Current - Low Frequency 440mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 1.457" (37.00mm) Surface Mount Land Size - Through Hole Package / Case Radial, Can	Lifetime @ Temp.	5000 Hrs @ 105°C
Applications General Purpose Ripple Current - Low Frequency 440mA @ 120Hz Ripple Current - High Frequency Impedance - Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 1.457" (37.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Operating Temperature	-25°C ~ 105°C
Ripple Current - Low Frequency 440mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 1.457" (37.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Polarization	-
Ripple Current - High Frequency Impedance Lead Spacing O.295" (7.50mm) Size / Dimension O.630" Dia (16.00mm) Height - Seated (Max) I.457" (37.00mm) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Applications	General Purpose
Impedance - Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 1.457" (37.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Ripple Current - Low Frequency	440mA @ 120Hz
Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	-
Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 1.457" (37.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Impedance	-
Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Lead Spacing	0.295" (7.50mm)
Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Size / Dimension	0.630" Dia (16.00mm)
Mounting Type Through Hole Package / Case Radial, Can	Height - Seated (Max)	1.457" (37.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
-	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors

UPT2W560MHD Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

UPT2W560MHD Payment Methods



















UPT2W560MHD Shipping Methods













If you have any question about UPT2W560MHD, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com