



## **URZ0J682MHD Information**



For Reference Only

Part Number URZ0J682MHD

Manufacturer Nichicon Category Capacitors

**Aluminum Electrolytic Capacitors** 

**Description** CAP ALUM 6800UF 20% 6.3V RADIAL

Package Radial, Car

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **URZ0J682MHD Specifications**

Manufacturer Part NumberURZ0J682MHDManufacturerNichiconCategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesURZCapacitance6800µFTolerance±20%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.2A @ 120HzImpedance-Impedance-
CategoryCapacitorsPackageRadial, CanSeriesURZCapacitance6800μFTolerance±20%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.2A @ 120HzRipple Current - High Frequency1.38A @ 10kHzImpedance-
PackageAluminum Electrolytic CapacitorsPackageRadial, CanSeriesURZCapacitance6800μFTolerance±20%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.2A @ 120HzRipple Current - High Frequency1.38A @ 10kHzImpedance-
PackageRadial, CanSeriesURZCapacitance6800μFTolerance±20%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.2A @ 120HzRipple Current - High Frequency1.38A @ 10kHzImpedance-
SeriesURZCapacitance6800μFTolerance±20%Voltage - Rated6.3 VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.2A @ 120HzRipple Current - High Frequency1.38A @ 10kHzImpedance-
Capacitance6800μFTolerance±20%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.2A @ 120HzRipple Current - High Frequency1.38A @ 10kHzImpedance-
Tolerance ±20%  Voltage - Rated 6.3V  ESR (Equivalent Series Resistance) -  Lifetime @ Temp. 1000 Hrs @ 105°C  Operating Temperature -55°C ~ 105°C  Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 1.2A @ 120Hz  Ripple Current - High Frequency 1.38A @ 10kHz  Impedance -
Voltage - Rated  ESR (Equivalent Series Resistance)  Lifetime @ Temp.  1000 Hrs @ 105°C  Operating Temperature  -55°C ~ 105°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  Ripple Current - High Frequency  1.38A @ 10kHz  Impedance  -
ESR (Equivalent Series Resistance)  Lifetime @ Temp.  1000 Hrs @ 105°C  Operating Temperature  -55°C ~ 105°C  Polarization  Polar  Applications  General Purpose  Ripple Current - Low Frequency  1.2A @ 120Hz  Ripple Current - High Frequency  1.38A @ 10kHz  Impedance  -
Lifetime @ Temp. 1000 Hrs @ 105°C  Operating Temperature -55°C ~ 105°C  Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 1.2A @ 120Hz  Ripple Current - High Frequency 1.38A @ 10kHz  Impedance -
Operating Temperature  -55°C ~ 105°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  1.2A @ 120Hz  Ripple Current - High Frequency  1.38A @ 10kHz  Impedance  -
Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 1.2A @ 120Hz  Ripple Current - High Frequency 1.38A @ 10kHz  Impedance -
Applications General Purpose Ripple Current - Low Frequency 1.2A @ 120Hz Ripple Current - High Frequency 1.38A @ 10kHz Impedance -
Ripple Current - Low Frequency  Ripple Current - High Frequency  1.2A @ 120Hz  1.38A @ 10kHz  Impedance  -
Ripple Current - High Frequency 1.38A @ 10kHz Impedance -
Impedance -
2 10 1
Lead Spacing 0.295" (7.50mm)
Size / Dimension 0.709" Dia (18.00mm)
Height - Seated (Max) 0.650" (16.50mm)
Surface Mount Land Size -
Mounting Type Through Hole
Package / Case Radial, Can
Report errors?

#### **URZ0J682MHD Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **URZ0J682MHD Payment Methods**



















### **URZ0J682MHD Shipping Methods**













If you have any question about URZ0J682MHD, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com