



#### **V23061A1009A402 Information**



For Reference Only

Part Number V23061A1009A402

Manufacturer TE Connectivity Potter & Brumfield Relays

Category Relays

Power Relays, Over 2 Amps

**Description** RELAY GEN PURPOSE SPST 8A 48V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









### V23061A1009A402 Specifications

Manufacturer Part Number  Manufacturer  TE Connectivity Potter & Brumfield Relays  Relays  Power Relays, Over 2 Amps  Package  - Series  MSR, SCHRACK  Relay Type  General Purpose  Non Latching  Coil Current  5.5mA  Coil Voltage  48VDC  Contact Form  SPST-NO (1 Form A)  Contact Rating (Current)  8A  Switching Voltage  400VAC - Max  Turn On Voltage (Max)  Turn Off Voltage (Min)  4.8 VDC  Operate Time  10ms  Release Time  Features  Insulation - Class A, Sealed - Fully  Mounting Type  Through Hole  Termination Style  TE Connectivity Potter & Brumfield Relays  Report errors?		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesMSR, SCHRACKRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current5.5mACoil Voltage48VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)8ASwitching Voltage400VAC - MaxTurn On Voltage (Max)32.6 VDCTurn Off Voltage (Min)4.8 VDCOperate Time10msRelease Time5msFeaturesInsulation - Class A, Sealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	V23061A1009A402
Package-SeriesMSR, SCHRACKRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current5.5mACoil Voltage48VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)8ASwitching Voltage400VAC - MaxTurn On Voltage (Max)32.6 VDCTurn Off Voltage (Min)4.8 VDCOperate Time10msRelease Time5msFeaturesInsulation - Class A, Sealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Manufacturer	TE Connectivity Potter & Brumfield Relays
Package-SeriesMSR, SCHRACKRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current5.5mACoil Voltage48VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)8ASwitching Voltage400VAC - MaxTurn On Voltage (Max)32.6 VDCTurn Off Voltage (Min)4.8 VDCOperate Time10msRelease Time5msFeaturesInsulation - Class A, Sealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Category	Relays
SeriesMSR, SCHRACKRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current5.5mACoil Voltage48VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)8ASwitching Voltage400VAC - MaxTurn On Voltage (Max)32.6 VDCTurn Off Voltage (Min)4.8 VDCOperate Time10msRelease Time5msFeaturesInsulation - Class A, Sealed - FullyMounting TypeThrough HoleTermination StylePC Pin		Power Relays, Over 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current5.5mACoil Voltage48VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)8ASwitching Voltage400VAC - MaxTurn On Voltage (Max)32.6 VDCTurn Off Voltage (Min)4.8 VDCOperate Time10msRelease Time5msFeaturesInsulation - Class A, Sealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Package	-
Coil Type Non Latching Coil Current 5.5mA  Coil Voltage 48VDC Contact Form SPST-NO (1 Form A)  Contact Rating (Current) 8A Switching Voltage 400VAC - Max Turn On Voltage (Max) 32.6 VDC  Turn Off Voltage (Min) 4.8 VDC Operate Time 10ms Release Time 5ms Features Insulation - Class A, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Series	MSR, SCHRACK
Coil Current5.5mACoil Voltage48VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)8ASwitching Voltage400VAC - MaxTurn On Voltage (Max)32.6 VDCTurn Off Voltage (Min)4.8 VDCOperate Time10msRelease Time5msFeaturesInsulation - Class A, Sealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Relay Type	General Purpose
Coil Voltage 48VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 8A Switching Voltage 400VAC - Max Turn On Voltage (Max) 32.6 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 10ms Release Time 5ms Features Insulation - Class A, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Coil Type	Non Latching
Contact Form SPST-NO (1 Form A)  Contact Rating (Current) 8A  Switching Voltage 400VAC - Max  Turn On Voltage (Max) 32.6 VDC  Turn Off Voltage (Min) 4.8 VDC  Operate Time 10ms  Release Time 5ms  Features Insulation - Class A, Sealed - Fully  Mounting Type Through Hole  Termination Style PC Pin	Coil Current	5.5mA
Contact Rating (Current)  Switching Voltage  400VAC - Max  Turn On Voltage (Max)  32.6 VDC  Turn Off Voltage (Min)  4.8 VDC  Operate Time  10ms  Release Time  5ms  Features  Insulation - Class A, Sealed - Fully  Mounting Type  Through Hole  Termination Style  PC Pin	Coil Voltage	48VDC
Switching Voltage 400VAC - Max  Turn On Voltage (Max) 32.6 VDC  Turn Off Voltage (Min) 4.8 VDC  Operate Time 10ms  Release Time 5ms  Features Insulation - Class A, Sealed - Fully  Mounting Type Through Hole  Termination Style PC Pin	Contact Form	SPST-NO (1 Form A)
Turn On Voltage (Max)  Turn Off Voltage (Min)  4.8 VDC  Operate Time  10ms  Release Time  5ms  Features  Insulation - Class A, Sealed - Fully  Mounting Type  Through Hole  Termination Style  PC Pin	Contact Rating (Current)	8A
Turn Off Voltage (Min)  4.8 VDC  Operate Time  10ms  Release Time  5ms  Features  Insulation - Class A, Sealed - Fully  Mounting Type  Through Hole  Termination Style  PC Pin	Switching Voltage	400VAC - Max
Operate Time 10ms Release Time 5ms Features Insulation - Class A, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Turn On Voltage (Max)	32.6 VDC
Release Time 5ms Features Insulation - Class A, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	4.8 VDC
Features Insulation - Class A, Sealed - Fully  Mounting Type Through Hole  Termination Style PC Pin	Operate Time	10ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	5ms
Termination Style PC Pin	Features	Insulation - Class A, Sealed - Fully
•	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
		Report errors?

#### **V23061A1009A402 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# V23061A1009A402 Payment Methods



















### V23061A1009A402 Shipping Methods













If you have any question about V23061A1009A402, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com