



V60MLA1210H Information



For Reference Only

Part Number V60MLA1210H

Manufacturer Littelfuse Inc.

Category Circuit Protection
TVS - Varistors, MOVs

Description VARISTOR 75V 250A 1210

Package 1210 (3225 Metric)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









V60MLA1210H Specifications

Manufacturer Part Number V60MLA1210H Manufacturer Littelfuse Inc. Category Circuit Protection TVS - Varistors, MOVs Package 1210 (3225 Metric) Series MLA Varistor Voltage (Min) 67V Varistor Voltage (Typ) 75V Varistor Voltage (Max) 83V Current - Surge 250A Energy 1.5J Number of Circuits 1 Number of Circuits 1 Maximum AC Volts 50VAC Maximum DC Volts 60VDC Capacitance @ Frequency 440pF @ 1MHz Operating Temperature -55°C ~ 125°C (TA) Mounting Type Surface Mount, MLCV Package / Case 1210 (3225 Metric)	•	
Category Circuit Protection TVS - Varistors, MOVs Package 1210 (3225 Metric) Series MLA Varistor Voltage (Min) 67V Varistor Voltage (Typ) 75V Varistor Voltage (Max) 83V Current - Surge 250A Energy 1.5J Number of Circuits 1 Number of Circuits 1 Maximum AC Volts 50VAC Maximum DC Volts 60VDC Capacitance @ Frequency 440pF @ 1MHz Operating Temperature -55°C ~ 125°C (TA) Mounting Type Surface Mount, MLCV	Manufacturer Part Number	V60MLA1210H
TVS - Varistors, MOVs Package 1210 (3225 Metric) Series MLA Varistor Voltage (Min) 67V Varistor Voltage (Typ) 75V Varistor Voltage (Max) 83V Current - Surge 250A Energy 1.5J Number of Circuits 1 Number of Circuits 1 Maximum AC Volts 50VAC Maximum DC Volts 60VDC Capacitance @ Frequency 440pF @ 1MHz Operating Temperature -55°C ~ 125°C (TA) Mounting Type Surface Mount, MLCV	Manufacturer	Littelfuse Inc.
Package 1210 (3225 Metric) Series MLA Varistor Voltage (Min) 67V Varistor Voltage (Typ) 75V Varistor Voltage (Max) 83V Current - Surge 250A Energy 1.5J Number of Circuits 1 Number of Circuits 1 Maximum AC Volts 50VAC Maximum DC Volts 60VDC Capacitance @ Frequency 440pF @ 1MHz Operating Temperature -55°C ~ 125°C (TA) Mounting Type Surface Mount, MLCV	Category	Circuit Protection
SeriesMLAVaristor Voltage (Min)67 VVaristor Voltage (Typ)75 VVaristor Voltage (Max)83 VCurrent - Surge250 AEnergy1.5 JNumber of Circuits1Number of Circuits1Maximum AC Volts50 VACMaximum DC Volts60 VDCCapacitance @ Frequency440 pF @ 1 MHzOperating Temperature-55°C ~ 125°C (TA)Mounting TypeSurface Mount, MLCV		TVS - Varistors, MOVs
Varistor Voltage (Min) Varistor Voltage (Typ) 75V Varistor Voltage (Max) 83V Current - Surge 250A Energy 1.5J Number of Circuits 1 Number of Circuits 1 Maximum AC Volts Maximum DC Volts Capacitance @ Frequency 440pF @ 1MHz Operating Temperature Mounting Type 67V 75V 75V 75V 75V 83V 250A 1 1 1 1 1 1 1 1 1 1 1 1 1	Package	1210 (3225 Metric)
Varistor Voltage (Typ) Varistor Voltage (Max) Current - Surge 250A Energy 1.5J Number of Circuits 1 Number of Circuits 1 Maximum AC Volts Maximum DC Volts Capacitance @ Frequency Mounting Type 75V 75V 75V 75V 75V 75V 60V 60V 60V 75V 60V 75V 60V 75V 75V 60V 75V 75V 75V 75V 75V 75V 75V 7	Series	MLA
Varistor Voltage (Max) Current - Surge 250A Energy 1.5J Number of Circuits 1 Number of Circuits 1 Maximum AC Volts Maximum DC Volts 60VDC Capacitance @ Frequency Operating Temperature Mounting Type 83V 83V 83V 250A 80V 60V 1 1 83V 60V 60V 60V 60V 60V 60V 60V 6	Varistor Voltage (Min)	67V
Current - Surge250AEnergy1.5JNumber of Circuits1Number of Circuits1Maximum AC Volts50VACMaximum DC Volts60VDCCapacitance @ Frequency440pF @ 1MHzOperating Temperature-55°C ~ 125°C (TA)Mounting TypeSurface Mount, MLCV	Varistor Voltage (Typ)	75V
Energy 1.5J Number of Circuits 1 Number of Circuits 1 Maximum AC Volts 50VAC Maximum DC Volts 60VDC Capacitance @ Frequency 440pF @ 1MHz Operating Temperature -55°C ~ 125°C (TA) Mounting Type 1.5J Surface Mount, MLCV	Varistor Voltage (Max)	83V
Number of Circuits 1 Number of Circuits 1 Maximum AC Volts 50VAC Maximum DC Volts 60VDC Capacitance @ Frequency 440pF @ 1MHz Operating Temperature -55°C ~ 125°C (TA) Mounting Type Surface Mount, MLCV	Current - Surge	250A
Number of Circuits1Maximum AC Volts50VACMaximum DC Volts60VDCCapacitance @ Frequency440pF @ 1MHzOperating Temperature-55°C ~ 125°C (TA)Mounting TypeSurface Mount, MLCV	Energy	1.5J
Maximum AC Volts50VACMaximum DC Volts60VDCCapacitance @ Frequency440pF @ 1MHzOperating Temperature-55°C ~ 125°C (TA)Mounting TypeSurface Mount, MLCV	Number of Circuits	1
Maximum DC Volts60VDCCapacitance @ Frequency440pF @ 1MHzOperating Temperature-55°C ~ 125°C (TA)Mounting TypeSurface Mount, MLCV	Number of Circuits	1
Capacitance @ Frequency 440pF @ 1MHz Operating Temperature -55°C ~ 125°C (TA) Mounting Type Surface Mount, MLCV	Maximum AC Volts	50VAC
Operating Temperature -55°C ~ 125°C (TA) Mounting Type Surface Mount, MLCV	Maximum DC Volts	60VDC
Mounting Type Surface Mount, MLCV	Capacitance @ Frequency	440pF @ 1MHz
	Operating Temperature	-55°C ~ 125°C (TA)
Package / Case 1210 (3225 Metric)	Mounting Type	Surface Mount, MLCV
	Package / Case	1210 (3225 Metric)
Report errors?		Report errors?

V60MLA1210H Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

V60MLA1210H Payment Methods



















V60MLA1210H Shipping Methods













If you have any question about V60MLA1210H, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com