

VE-25B-CX-F4 Information

Heisener.com

Part Number VE-25B-CX-F4
Manufacturer Vicor Corporation

Category Power Supplies - Board Mount

DC DC Converters

Description CONVERTER MOD DC/DC 95V 75W

Package Full Brick

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









VE-25B-CX-F4 Specifications

Manufacturer Part Number Manufacturer Vicor Corporation Power Supplies - Board Mount DC DC Converters Package Full Brick Series VE-200 Type Isolated Module Number of Outputs Voltage - Input (Min) Voltage - Output 1 Voltage - Output 2 Voltage - Output 3 Voltage - Output 4 Current - Output (Max) Power (Watts) Voltage - Isolation Applications VE-25B-CX-F4 Vicor Corporation Vicor Corporation Power Supplies - Board Mount Vole Output Brick VE-200 Isolated Module Number of Outputs 1 Voltage - Input (Max) 200V Voltage - Output 1 95V Voltage - Output 2 - Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) 790mA Power (Watts) Voltage - Isolation JEF (Commercial)	
Category Power Supplies - Board Mount DC DC Converters Package Full Brick Series VE-200 Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 100V Voltage - Input (Max) 200V Voltage - Output 1 95V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 790mA Power (Watts) 75W Voltage - Isolation 3kV (3000V)	
DC DC Converters Package Full Brick Series VE-200 Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 100V Voltage - Input (Max) 200V Voltage - Output 1 95V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 790mA Power (Watts) 75W Voltage - Isolation 3kV (3000V)	
Package Full Brick Series VE-200 Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 100V Voltage - Input (Max) 200V Voltage - Output 1 95V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 790mA Power (Watts) 75W Voltage - Isolation 3kV (3000V)	
Series VE-200 Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 100V Voltage - Input (Max) 200V Voltage - Output 1 95V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 790mA Power (Watts) 75W Voltage - Isolation 3kV (3000V)	
Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 100V Voltage - Input (Max) 200V Voltage - Output 1 95V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 790mA Power (Watts) 75W Voltage - Isolation 3kV (3000V)	
Number of Outputs 1 Voltage - Input (Min) 100V Voltage - Input (Max) 200V Voltage - Output 1 95V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 790mA Power (Watts) 75W Voltage - Isolation 3kV (3000V)	
Voltage - Input (Min) 100V Voltage - Input (Max) 200V Voltage - Output 1 95V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 790mA Power (Watts) 75W Voltage - Isolation 3kV (3000V)	
Voltage - Input (Max) 200V Voltage - Output 1 95V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 790mA Power (Watts) 75W Voltage - Isolation 3kV (3000V)	
Voltage - Output 1 95V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 790mA Power (Watts) 75W Voltage - Isolation 3kV (3000V)	
Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 790mA Power (Watts) 75W Voltage - Isolation 3kV (3000V)	
Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 790mA Power (Watts) 75W Voltage - Isolation 3kV (3000V)	
Voltage - Output 4 - Current - Output (Max) 790mA Power (Watts) 75W Voltage - Isolation 3kV (3000V)	
Current - Output (Max) 790mA Power (Watts) 75W Voltage - Isolation 3kV (3000V)	
Power (Watts) 75W Voltage - Isolation 3kV (3000V)	
Voltage - Isolation 3kV (3000V)	
Applications ITE (Commercial)	
Features OCP, OTP, OVP, SCP	
Operating Temperature $-25^{\circ}\text{C} \sim 85^{\circ}\text{C}$	
Efficiency 90%	
Mounting Type Through Hole	
Package / Case Full Brick	
Size / Dimension 4.60" L x 1.86" W x 1.05" H (116.8mm x 47.2mm x 26.7mm)	

Supplier Device Package	-
Control Features	-
	Report errors?

VE-25B-CX-F4 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

VE-25B-CX-F4 Payment Methods





















VE-25B-CX-F4 Shipping Methods













If you have any question about VE-25B-CX-F4, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com