



#### **VE-2VM-CX Information**

Heisener.com

Part Number VE-2VM-CX
Manufacturer Vicor Corporation

**Category** Power Supplies - Board Mount

DC DC Converters

**Description** CONVERTER MOD DC/DC 10V 75W

Package Full Brick

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **VE-2VM-CX Specifications**

Manufacturer Part Number         VE-2VM-CX           Manufacturer         Vicor Corporation           Category         Power Supplies - Board Mount           DC DC Converters           Package         Full Brick           Series         VE-200           Type         Isolated Module           Number of Outputs         1           Voltage - Input (Min)         9V           Voltage - Input (Max)         36V           Voltage - Output 1         10V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         7.5A           Power (Watts)         75W           Voltage - Isolation         3kV (3000V)           Applications         ITE (Commercial)           Features         OCP, OTP, OVP, SCP           Operating Temperature         -25°C ~ 85°C		
Power Supplies - Board Mount	anufacturer Part Number	VE-2VM-CX
DC DC Converters	anufacturer	Vicor Corporation
Package         Full Brick           Series         VE-200           Type         Isolated Module           Number of Outputs         1           Voltage - Input (Min)         9V           Voltage - Input (Max)         36V           Voltage - Output 1         10V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         7.5A           Power (Watts)         75W           Voltage - Isolation         3kV (3000V)           Applications         ITE (Commercial)           Features         OCP, OTP, OVP, SCP	ategory	Power Supplies - Board Mount
Series         VE-200           Type         Isolated Module           Number of Outputs         1           Voltage - Input (Min)         9V           Voltage - Input (Max)         36V           Voltage - Output 1         10V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         7.5A           Power (Watts)         75W           Voltage - Isolation         3kV (3000V)           Applications         ITE (Commercial)           Features         OCP, OTP, OVP, SCP		DC DC Converters
Type Isolated Module  Number of Outputs 1  Voltage - Input (Min) 9V  Voltage - Input (Max) 36V  Voltage - Output 1 10V  Voltage - Output 2 -  Voltage - Output 3 -  Voltage - Output 4 -  Current - Output (Max) 7.5A  Power (Watts) 75W  Voltage - Isolation 3kV (3000V)  Applications ITE (Commercial)  Features OCP, OTP, OVP, SCP	ickage	Full Brick
Number of Outputs       1         Voltage - Input (Min)       9V         Voltage - Input (Max)       36V         Voltage - Output 1       10V         Voltage - Output 2       -         Voltage - Output 3       -         Voltage - Output 4       -         Current - Output (Max)       7.5A         Power (Watts)       75W         Voltage - Isolation       3kV (3000V)         Applications       ITE (Commercial)         Features       OCP, OTP, OVP, SCP	eries	VE-200
Voltage - Input (Min)         9V           Voltage - Input (Max)         36V           Voltage - Output 1         10V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         7.5A           Power (Watts)         75W           Voltage - Isolation         3kV (3000V)           Applications         ITE (Commercial)           Features         OCP, OTP, OVP, SCP	/pe	Isolated Module
Voltage - Input (Max)         36V           Voltage - Output 1         10V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         7.5A           Power (Watts)         75W           Voltage - Isolation         3kV (3000V)           Applications         ITE (Commercial)           Features         OCP, OTP, OVP, SCP	umber of Outputs	1
Voltage - Output 1  Voltage - Output 2  Voltage - Output 3  Voltage - Output 4  - Current - Output (Max)  Power (Watts)  Voltage - Isolation  Applications  ITE (Commercial)  Features  OCP, OTP, OVP, SCP	oltage - Input (Min)	9V
Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         7.5A           Power (Watts)         75W           Voltage - Isolation         3kV (3000V)           Applications         ITE (Commercial)           Features         OCP, OTP, OVP, SCP	oltage - Input (Max)	36V
Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         7.5A           Power (Watts)         75W           Voltage - Isolation         3kV (3000V)           Applications         ITE (Commercial)           Features         OCP, OTP, OVP, SCP	oltage - Output 1	10V
Voltage - Output 4  Current - Output (Max)  Power (Watts)  Voltage - Isolation  Applications  ITE (Commercial)  Features  OCP, OTP, OVP, SCP	oltage - Output 2	-
Current - Output (Max)  Power (Watts)  Voltage - Isolation  Applications  ITE (Commercial)  Features  OCP, OTP, OVP, SCP	oltage - Output 3	-
Power (Watts) 75W  Voltage - Isolation 3kV (3000V)  Applications ITE (Commercial)  Features OCP, OTP, OVP, SCP	oltage - Output 4	-
Voltage - Isolation 3kV (3000V)  Applications ITE (Commercial)  Features OCP, OTP, OVP, SCP	urrent - Output (Max)	7.5A
Applications ITE (Commercial) Features OCP, OTP, OVP, SCP	ower (Watts)	75W
Features OCP, OTP, OVP, SCP	oltage - Isolation	3kV (3000V)
	pplications	ITE (Commercial)
Operating Temperature $-25^{\circ}\text{C} \sim 85^{\circ}\text{C}$	eatures	OCP, OTP, OVP, SCP
	perating Temperature	-25°C ~ 85°C
Efficiency 90%	ficiency	90%
Mounting Type Through Hole	ounting Type	Through Hole
Package / Case Full Brick	ickage / Case	Full Brick
Size / Dimension 4.60" L x 2.40" W x 0.50" H (116.8mm x 61.0mm x 12.7mm)	ze / Dimension	4.60" L x 2.40" W x 0.50" H (116.8mm x 61.0mm x 12.7mm)

Supplier Device Package	-
Control Features	-
	Report errors?

#### **VE-2VM-CX Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# **VE-2VM-CX Payment Methods**



















## **VE-2VM-CX Shipping Methods**













If you have any question about VE-2VM-CX, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com