



VEP08US05 Information



For Reference Only

Part Number VEP08US05 **Manufacturer** XP Power

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

Description AC/DC WALL MOUNT ADAPTER 5V 8W

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









VEP08US05 Specifications

Manufacturer Part NumberVEP08US05ManufacturerXP PowerCategoryPower Supplies - External/Internal (Off-Board) AC DC Desktop, Wall AdaptersPackage-SeriesVEPRegion UtilizedInternationalFormWall MountInput TypeMulti-Blade (Sold Separately)Voltage - Input80 ~ 264 VACVoltage - Output5VCurrent - Output (Max)1.6APower (Watts)8WNo Load Power Consumption300mW (Max)PolarizationPositive CenterApplicationsITE (Commercial), MedicalEfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mmSize / Dimension2.83" L x 1.67" W x 1.06" H (72.0mm x 42.4mm x 26.8mm)		
Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series VEP Region Utilized International Form Wall Mount Input Type Multi-Blade (Sold Separately) Voltage - Input 80 ~ 264 VAC Voltage - Output (Max) 1.6A Power (Watts) 8W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications ITE (Commercial), Medical Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 2.83" L x 1.67" W x 1.06" H (72.0mm x 42.4mm x 26.8mm)	Manufacturer Part Number	VEP08US05
Package-SeriesVEPRegion UtilizedInternationalFormWall MountInput TypeMulti-Blade (Sold Separately)Voltage - Input80 ~ 264 VACVoltage - Output5VCurrent - Output (Max)1.6APower (Watts)8WNo Load Power Consumption300mW (Max)PolarizationPositive CenterApplicationsITE (Commercial), MedicalEfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mmSize / Dimension2.83" L x 1.67" W x 1.06" H (72.0mm x 42.4mm x 26.8mm)	Manufacturer	XP Power
Package - Series VEP Region Utilized International Form Wall Mount Input Type Multi-Blade (Sold Separately) Voltage - Input 80 ~ 264 VAC Voltage - Output 5V Current - Output (Max) 1.6A Power (Watts) 8W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications ITE (Commercial), Medical Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 2.83" L x 1.67" W x 1.06" H (72.0mm x 42.4mm x 26.8mm)	Category	Power Supplies - External/Internal (Off-Board)
SeriesVEPRegion UtilizedInternationalFormWall MountInput TypeMulti-Blade (Sold Separately)Voltage - Input80 ~ 264 VACVoltage - Output5VCurrent - Output (Max)1.6APower (Watts)8WNo Load Power Consumption300mW (Max)PolarizationPositive CenterApplicationsITE (Commercial), MedicalEfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mmSize / Dimension2.83" L x 1.67" W x 1.06" H (72.0mm x 42.4mm x 26.8mm)		AC DC Desktop, Wall Adapters
Region Utilized International Form Wall Mount Input Type Multi-Blade (Sold Separately) Voltage - Input 80 ~ 264 VAC Voltage - Output 5V Current - Output (Max) 1.6A Power (Watts) 8W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications ITE (Commercial), Medical Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 2.83" L x 1.67" W x 1.06" H (72.0mm x 42.4mm x 26.8mm)	Package	-
Form Wall Mount Input Type Multi-Blade (Sold Separately) Voltage - Input 80 ~ 264 VAC Voltage - Output 5V Current - Output (Max) 1.6A Power (Watts) 8W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications ITE (Commercial), Medical Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 2.83" L x 1.67" W x 1.06" H (72.0mm x 42.4mm x 26.8mm)	Series	VEP
Input TypeMulti-Blade (Sold Separately)Voltage - Input $80 \sim 264 \text{ VAC}$ Voltage - Output $5V$ Current - Output (Max) $1.6A$ Power (Watts) $8W$ No Load Power Consumption 300mW (Max)PolarizationPositive CenterApplicationsITE (Commercial), MedicalEfficiencyLevel VOperating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug, 2.5mm I.D. $x > 5.5\text{mm}$ O.D. $x > 11.0\text{mm}$ Size / Dimension 2.83° L $x > 1.67^{\circ}$ W $x > 1.06^{\circ}$ H (72.0mm $x > 42.4\text{mm}$ x 26.8mm)	Region Utilized	International
Voltage - Input $80 \sim 264 \text{ VAC}$ Voltage - Output $5V$ Current - Output (Max) $1.6A$ Power (Watts) $8W$ No Load Power Consumption 300mW (Max)PolarizationPositive CenterApplicationsITE (Commercial), MedicalEfficiencyLevel VOperating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug, 2.5mm I.D. $x > 5.5\text{mm}$ O.D. $x > 11.0\text{mm}$ Size / Dimension 2.83 " L $x > 1.67$ " W $x > 1.06$ " H (72.0mm $x > 42.4\text{mm}$ $x > 26.8\text{mm}$)	Form	Wall Mount
Voltage - Output (Max) 1.6A Power (Watts) 8W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications ITE (Commercial), Medical Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 2.83" L x 1.67" W x 1.06" H (72.0mm x 42.4mm x 26.8mm)	Input Type	Multi-Blade (Sold Separately)
Current - Output (Max) 1.6A Power (Watts) 8W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications ITE (Commercial), Medical Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 2.83" L x 1.67" W x 1.06" H (72.0mm x 42.4mm x 26.8mm)	Voltage - Input	80 ~ 264 VAC
Power (Watts) No Load Power Consumption 300mW (Max) Polarization Positive Center Applications ITE (Commercial), Medical Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 2.83" L x 1.67" W x 1.06" H (72.0mm x 42.4mm x 26.8mm)	Voltage - Output	5V
No Load Power Consumption 300mW (Max)PolarizationPositive CenterApplicationsITE (Commercial), MedicalEfficiencyLevel VOperating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mmSize / Dimension 2.83 " L x 1.67 " W x 1.06 " H (72.0 mm x 42.4 mm x 26.8 mm)	Current - Output (Max)	1.6A
PolarizationPositive CenterApplicationsITE (Commercial), MedicalEfficiencyLevel VOperating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mmSize / Dimension 2.83 " L x 1.67 " W x 1.06 " H (72.0 mm x 42.4 mm x 26.8 mm)	Power (Watts)	8W
Applications ITE (Commercial), Medical Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 2.83" L x 1.67" W x 1.06" H (72.0mm x 42.4mm x 26.8mm)	No Load Power Consumption	300mW (Max)
Efficiency Level V Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 2.83" L x 1.67" W x 1.06" H (72.0mm x 42.4mm x 26.8mm)	Polarization	Positive Center
Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension $2.83^{\circ}\text{L} \times 1.67^{\circ}\text{W} \times 1.06^{\circ}\text{H} (72.0\text{mm} \times 42.4\text{mm} \times 26.8\text{mm})$	Applications	ITE (Commercial), Medical
Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 2.83" L x 1.67" W x 1.06" H (72.0mm x 42.4mm x 26.8mm)	Efficiency	Level V
Size / Dimension 2.83" L x 1.67" W x 1.06" H (72.0mm x 42.4mm x 26.8mm)	Operating Temperature	0°C ~ 40°C
	Output Connector	Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mm
Report errors?	Size / Dimension	2.83" L x 1.67" W x 1.06" H (72.0mm x 42.4mm x 26.8mm)
1		Report errors?

VEP08US05 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

VEP08US05 Payment Methods



















VEP08US05 Shipping Methods













If you have any question about VEP08US05, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com