

VF30100C-E3/4W

VF30100C-E3/4W Information

	www.heisenen.com	 VF30100C-E3/4W Vishay Semiconductor Diodes Division Discrete Semiconductor Products Diodes - Rectifiers - Arrays DIODE ARRAY SCHOTTKY 100V ITO220 TO-220-3 Full Pack, Isolated Tab For the pricing/inventory/lead time, please contact us	
	For Reference Only	Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

E-mail: salesdept@heisener.com

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



VF30100C-E3/4W Specifications

ManufacturerVishay Semiconductor Diodes DivisionCategoryDiscrete Semiconductor ProductsDiodes - Rectifiers - ArraysPackageTO-220.3 Full Pack, Isolated TabSeriesTMBS?Diode Configuration1 Pair Common CathodeDiode TypeSchottkyVoltage - DC Reverse (Vr) (Max)100VCurrent - Average Rectified (Io) (per Diode)15AVoltage - Forward (Vf) (Max) @ If800mV @ 15ASpeedFast Recovery =< 500ms, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr500µA @ 100VOperating Temperature - Junction-40°C ~ 150°CMounting TypeThrough HolePackage / CaseTO-220.3 Full Pack, Isolated TabSupplier Device PackageTO-220.3 Full Pack, Isolated Tab		
CategoryDiscrete Semiconductor ProductsDiodes - Rectifiers - ArraysPackageTO-220-3 Full Pack, Isolated TabSeriesTMBS?Diode Configuration1 Pair Common CathodeDiode TypeSchottkyVoltage - DC Reverse (Vr) (Max)100VCurrent - Average Rectified (Io) (per Diode)15AVoltage - Forward (Vf) (Max) @ If800mV @ 15ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr500µA @ 100VOperating Temperature - Junction-40°C ~ 150°CMounting TypeThrough HolePackage / CaseTO-220AB Full Pack, Isolated Tab	Manufacturer Part Number	VF30100C-E3/4W
Diodes - Rectifiers - ArraysPackageTO-220-3 Full Pack, Isolated TabSeriesTMBS?Diode Configuration1 Pair Common CathodeDiode TypeSchottkyVoltage - DC Reverse (Vr) (Max)100VCurrent - Average Rectified (Io) (per Diode)15AVoltage - Forward (Vf) (Max) @ If800mV @ 15ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr500µA @ 100VOperating Temperature - Junction-40°C ~ 150°CMounting TypeThrough HolePackage / CaseTO-220.3 Full Pack, Isolated TabSupplier Device PackageITO-220AB	Manufacturer	Vishay Semiconductor Diodes Division
PackageTO-220-3 Full Pack, Isolated TabSeriesTMBS?Diode Configuration1 Pair Common CathodeDiode TypeSchottkyVoltage - DC Reverse (Vr) (Max)100VCurrent - Average Rectified (Io) (per Diode)15AVoltage - Forward (Vf) (Max) @ If800mV @ 15ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr500µA @ 100VOperating Temperature - Junction-40°C ~ 150°CMounting TypeThrough HolePackage / CaseTO-220.3 Full Pack, Isolated TabSupplier Device PackageITO-220AB	Category	Discrete Semiconductor Products
SeriesTMBS?Diode Configuration1 Pair Common CathodeDiode TypeSchottkyVoltage - DC Reverse (Vr) (Max)100VCurrent - Average Rectified (Io) (per Diode)15AVoltage - Forward (Vf) (Max) @ If800mV @ 15ASpeedFast Recovery = < 500ms, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr500µA @ 100VOperating Temperature - Junction-40°C ~ 150°CMounting TypeThrough HolePackage / CaseTO-220ABSupplier Device PackageITO-220AB		Diodes - Rectifiers - Arrays
Diode Configuration1 Pair Common CathodeDiode TypeSchottkyVoltage - DC Reverse (Vr) (Max)100VCurrent - Average Rectified (Io) (per Diode)15AVoltage - Forward (Vf) (Max) @ If800mV @ 15ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr500µA @ 100VOperating Temperature - Junction-40°C ~ 150°CMounting TypeThrough HolePackage / CaseTO-220-3 Full Pack, Isolated TabSupplier Device PackageITO-220AB	Package	TO-220-3 Full Pack, Isolated Tab
Diode TypeSchottkyVoltage - DC Reverse (Vr) (Max)100VCurrent - Average Rectified (Io) (per Diode)15AVoltage - Forward (Vf) (Max) @ If800mV @ 15ASpeedFast Recovery =< 500ns, > 200mA (Io)Speed-Current - Reverse Leakage @ Vr500µA @ 100VOperating Temperature - Junction-40°C ~ 150°CMounting TypeThrough HolePackage / CaseTO-220.3 Full Pack, Isolated TabSupplier Device PackageITO-220AB	Series	TMBS?
Voltage - DC Reverse (Vr) (Max)100VCurrent - Average Rectified (Io) (per Diode)15AVoltage - Forward (Vf) (Max) @ If800mV @ 15ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr500µA @ 100VOperating Temperature - Junction-40°C ~ 150°CMounting TypeThrough HolePackage / CaseTO-220-3 Full Pack, Isolated TabSupplier Device PackageITO-220AB	Diode Configuration	1 Pair Common Cathode
Current - Average Rectified (Io) (per Diode)15AVoltage - Forward (Vf) (Max) @ If800mV @ 15ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr500µA @ 100VOperating Temperature - Junction-40°C ~ 150°CMounting TypeThrough HolePackage / CaseTO-220-3 Full Pack, Isolated TabSupplier Device PackageITO-220AB	Diode Type	Schottky
Voltage - Forward (Vf) (Max) @ If800mV @ 15ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr500µA @ 100VOperating Temperature - Junction-40°C ~ 150°CMounting TypeThrough HolePackage / CaseTO-220-3 Full Pack, Isolated TabSupplier Device PackageITO-220AB	Voltage - DC Reverse (Vr) (Max)	100V
SpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr500µA @ 100VOperating Temperature - Junction-40°C ~ 150°CMounting TypeThrough HolePackage / CaseTO-220-3 Full Pack, Isolated TabSupplier Device PackageITO-220AB	Current - Average Rectified (Io) (per Diode)	15A
Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr500μA @ 100VOperating Temperature - Junction-40°C ~ 150°CMounting TypeThrough HolePackage / CaseTO-220-3 Full Pack, Isolated TabSupplier Device PackageITO-220AB	Voltage - Forward (Vf) (Max) @ If	800mV @ 15A
Current - Reverse Leakage @ Vr500µA @ 100VOperating Temperature - Junction-40°C ~ 150°CMounting TypeThrough HolePackage / CaseTO-220-3 Full Pack, Isolated TabSupplier Device PackageITO-220AB	Speed	Fast Recovery =< 500ns, > 200mA (Io)
Operating Temperature - Junction-40°C ~ 150°CMounting TypeThrough HolePackage / CaseTO-220-3 Full Pack, Isolated TabSupplier Device PackageITO-220AB	Reverse Recovery Time (trr)	-
Mounting TypeThrough HolePackage / CaseTO-220-3 Full Pack, Isolated TabSupplier Device PackageITO-220AB	Current - Reverse Leakage @ Vr	500µA @ 100V
Package / CaseTO-220-3 Full Pack, Isolated TabSupplier Device PackageITO-220AB	Operating Temperature - Junction	$-40^{\circ}\text{C} \sim 150^{\circ}\text{C}$
Supplier Device Package ITO-220AB	Mounting Type	Through Hole
	Package / Case	TO-220-3 Full Pack, Isolated Tab
Report errors?	Supplier Device Package	ITO-220AB
		Report errors?

VF30100C-E3/4W Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

VF30100C-E3/4W Payment Methods





If you have any question about VF30100C-E3/4W, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com