

# VI-2W2-IV-F3 Information



For Reference Only

Part Number VI-2W2-IV-F3
Manufacturer Vicor Corporation

**Category** Power Supplies - Board Mount

DC DC Converters

**Description** CONVERTER MOD DC/DC 15V 150W

Package Full Brick

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# VI-2W2-IV-F3 Specifications

Manufacturer         VI-2W2-IV-F3           Manufacturer         Vicor Corporation           Category         Power Supplies - Board Mount           DC DC Converters           Package         Full Brick           Series         VI-200           Type         Isolated Module           Number of Outputs         1           Voltage - Input (Min)         18V           Voltage - Input (Max)         36V           Voltage - Output 1         15V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         10A           Power (Watts)         150W           Voltage - Isolation         3kV (3000V)           Applications         ITE (Commercial)           Features         OCP, OTP, OVP, SCP           Operating Temperature         -40°C ~ 85°C	
Power Supplies - Board Mount	
Package         Full Brick           Series         VI-200           Type         Isolated Module           Number of Outputs         1           Voltage - Input (Min)         18V           Voltage - Input (Max)         36V           Voltage - Output 1         15V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         10A           Power (Watts)         150W           Voltage - Isolation         3kV (3000V)           Applications         ITE (Commercial)           Features         OCP, OTP, OVP, SCP	
Package         Full Brick           Series         VI-200           Type         Isolated Module           Number of Outputs         1           Voltage - Input (Min)         18V           Voltage - Input (Max)         36V           Voltage - Output 1         15V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         10A           Power (Watts)         150W           Voltage - Isolation         3kV (3000V)           Applications         ITE (Commercial)           Features         OCP, OTP, OVP, SCP	
Series         VI-200           Type         Isolated Module           Number of Outputs         1           Voltage - Input (Min)         18V           Voltage - Input (Max)         36V           Voltage - Output 1         15V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         10A           Power (Watts)         150W           Voltage - Isolation         3kV (3000V)           Applications         ITE (Commercial)           Features         OCP, OTP, OVP, SCP	
Type         Isolated Module           Number of Outputs         1           Voltage - Input (Min)         18V           Voltage - Input (Max)         36V           Voltage - Output 1         15V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         10A           Power (Watts)         150W           Voltage - Isolation         3kV (3000V)           Applications         ITE (Commercial)           Features         OCP, OTP, OVP, SCP	
Number of Outputs       1         Voltage - Input (Min)       18V         Voltage - Input (Max)       36V         Voltage - Output 1       15V         Voltage - Output 2       -         Voltage - Output 3       -         Voltage - Output 4       -         Current - Output (Max)       10A         Power (Watts)       150W         Voltage - Isolation       3kV (3000V)         Applications       ITE (Commercial)         Features       OCP, OTP, OVP, SCP	
Voltage - Input (Min)       18V         Voltage - Input (Max)       36V         Voltage - Output 1       15V         Voltage - Output 2       -         Voltage - Output 3       -         Voltage - Output 4       -         Current - Output (Max)       10A         Power (Watts)       150W         Voltage - Isolation       3kV (3000V)         Applications       ITE (Commercial)         Features       OCP, OTP, OVP, SCP	
Voltage - Input (Max)         36V           Voltage - Output 1         15V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         10A           Power (Watts)         150W           Voltage - Isolation         3kV (3000V)           Applications         ITE (Commercial)           Features         OCP, OTP, OVP, SCP	
Voltage - Output 1       15V         Voltage - Output 2       -         Voltage - Output 3       -         Voltage - Output 4       -         Current - Output (Max)       10A         Power (Watts)       150W         Voltage - Isolation       3kV (3000V)         Applications       ITE (Commercial)         Features       OCP, OTP, OVP, SCP	
Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         10A           Power (Watts)         150W           Voltage - Isolation         3kV (3000V)           Applications         ITE (Commercial)           Features         OCP, OTP, OVP, SCP	
Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         10A           Power (Watts)         150W           Voltage - Isolation         3kV (3000V)           Applications         ITE (Commercial)           Features         OCP, OTP, OVP, SCP	
Voltage - Output 4  Current - Output (Max)  Power (Watts)  Voltage - Isolation  Applications  ITE (Commercial)  Features  OCP, OTP, OVP, SCP	
Current - Output (Max) 10A  Power (Watts) 150W  Voltage - Isolation 3kV (3000V)  Applications ITE (Commercial)  Features OCP, OTP, OVP, SCP	
Power (Watts)  Voltage - Isolation  Applications  ITE (Commercial)  Features  OCP, OTP, OVP, SCP	
Voltage - Isolation 3kV (3000V)  Applications ITE (Commercial)  Features OCP, OTP, OVP, SCP	
Applications ITE (Commercial) Features OCP, OTP, OVP, SCP	
Features OCP, OTP, OVP, SCP	
Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$	
Operating Temperature	
Efficiency 90%	
Mounting Type Through Hole	
Package / Case Full Brick	
Size / Dimension 4.60" L x 1.86" W x 0.79" H (116.8mm x 47.2mm x 20.1mm)	

Supplier Device Package	-
Control Features	-
	Report errors?

#### VI-2W2-IV-F3 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# VI-2W2-IV-F3 Payment Methods


































If you have any question about VI-2W2-IV-F3, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com