

## VJ1210A471KBEAT4X

## **VJ1210A471KBEAT4X Information**



For Reference Only

Part Number VJ1210A471KBEAT4X

Manufacturer Vishay Vitramon

**Category** Capacitors

Ceramic Capacitors

**Description** CAP CER 470PF 500V NP0 1210

**Package** 1210 (3225 Metric)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **VJ1210A471KBEAT4X Specifications**

Manufacturer  Category  Capacitors  Ceramic Capacitors  Package  1210 (3225 Metric)  Series  VJ OMD  Capacitance  470pF  Tolerance  ±10%  Voltage - Rated  500V  Temperature Coefficient  COG, NPO  Operating Temperature  -55°C ~ 125°C  Features  Soft Termination, High Voltage  Ratings  -  Applications  Nishay Vitramon  Capacitors  Vishay Vitramon  Coramic Capacitors  Volage - Netric  ±10 (3225 Metric)  VJ OMD  470pF  500V  500V  500V  500V  Temperature Coefficient  COG, NPO  Operating Temperature  -55°C ~ 125°C  Features  Boardflex Sensitive		
Category         Capacitors           Package         1210 (3225 Metric)           Series         VJ OMD           Capacitance         470pF           Tolerance         ±10%           Voltage - Rated         500V           Temperature Coefficient         C0G, NPO           Operating Temperature         -55°C ~ 125°C           Features         Soft Termination, High Voltage           Ratings         -           Applications         Boardflex Sensitive           Failure Rate         -	Manufacturer Part Number	VJ1210A471KBEAT4X
Ceramic Capacitors  Package 1210 (3225 Metric)  Series VJ OMD  Capacitance 470pF  Tolerance ±10%  Voltage - Rated 500V  Temperature Coefficient COG, NP0  Operating Temperature -55°C ~ 125°C  Features Soft Termination, High Voltage  Ratings -  Applications Boardflex Sensitive  Failure Rate -	Manufacturer	Vishay Vitramon
Package 1210 (3225 Metric)  Series VJ OMD  Capacitance 470pF  Tolerance ±10%  Voltage - Rated 500V  Temperature Coefficient COG, NP0  Operating Temperature -55°C ~ 125°C  Features Soft Termination, High Voltage  Ratings -  Applications Boardflex Sensitive  Failure Rate -	Category	Capacitors
Series VJ OMD  Capacitance 470pF  Tolerance ±10%  Voltage - Rated 500V  Temperature Coefficient COG, NPO  Operating Temperature -55°C ~ 125°C  Features Soft Termination, High Voltage  Ratings -  Applications Boardflex Sensitive  Failure Rate -		Ceramic Capacitors
Capacitance 470pF  Tolerance ±10%  Voltage - Rated 500V  Temperature Coefficient C0G, NP0  Operating Temperature -55°C ~ 125°C  Features Soft Termination, High Voltage  Ratings -  Applications Boardflex Sensitive  Failure Rate -	Package	1210 (3225 Metric)
Tolerance $\pm 10\%$ Voltage - Rated $500V$ Temperature Coefficient $C0G$ , NP0  Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$ Features $Soft$ Termination, High Voltage  Ratings $-$ Applications $Boardflex$ Sensitive  Failure Rate $-$	Series	VJ OMD
Voltage - Rated 500V  Temperature Coefficient C0G, NP0  Operating Temperature -55°C ~ 125°C  Features Soft Termination, High Voltage  Ratings -  Applications Boardflex Sensitive  Failure Rate -	Capacitance	470pF
Temperature Coefficient  COG, NPO  Operating Temperature  -55°C ~ 125°C  Features  Soft Termination, High Voltage  Ratings  -  Applications  Boardflex Sensitive  Failure Rate  -	Tolerance	±10%
Operating Temperature -55°C ~ 125°C  Features Soft Termination, High Voltage  Ratings -  Applications Boardflex Sensitive  Failure Rate -	Voltage - Rated	500V
Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate -	Temperature Coefficient	COG, NPO
Ratings - Applications Boardflex Sensitive Failure Rate -	Operating Temperature	-55°C ~ 125°C
Applications Boardflex Sensitive Failure Rate -	Features	Soft Termination, High Voltage
Failure Rate -	Ratings	-
	Applications	Boardflex Sensitive
Mounting Type Surface Mount, MLCC	Failure Rate	-
	Mounting Type	Surface Mount, MLCC
Package / Case 1210 (3225 Metric)	Package / Case	1210 (3225 Metric)
Size / Dimension 0.132" L x 0.098" W (3.35mm x 2.50mm)	Size / Dimension	0.132" L x 0.098" W (3.35mm x 2.50mm)
Height - Seated (Max)	Height - Seated (Max)	-
Thickness (Max) 0.073" (1.85mm)	Thickness (Max)	0.073" (1.85mm)
Lead Spacing -	Lead Spacing	-
Lead Style -	Lead Style	-
Report errors		Report errors?

#### VJ1210A471KBEAT4X Guarantees



#### **Ouality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **VJ1210A471KBEAT4X Payment Methods**



















### VJ1210A471KBEAT4X Shipping Methods













If you have any question about VJ1210A471KBEAT4X, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com