

# **VJ1812A331JBGAT4X**

## VJ1812A331JBGAT4X Information



For Reference Only

Part Number VJ1812A331JBGAT4X

Manufacturer Vishay Vitramon

**Category** Capacitors

**Ceramic Capacitors** 

**Description** CAP CER 330PF 1KV NP0 1812

Package 1812 (4532 Metric)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **VJ1812A331JBGAT4X Specifications**

Manufacturer Part Number         VJ1812A331JBGAT4X           Manufacturer         Vishay Vitramon           Category         Capacitors           Package         1812 (4532 Metric)           Series         VJ OMD           Capacitance         330pF           Tolerance         ±5%           Voltage - Rated         1000V (1kV)           Temperature Coefficient         C0G, NPO           Operating Temperature         -55°C ~ 125°C           Features         Soft Termination, High Voltage           Ratings         -           Applications         Boardflex Sensitive           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         1812 (4532 Metric)           Size / Dimension         0.183" L x 0.126" W (4.65mm x 3.20mm)           Height - Seated (Max)         -           Thickness (Max)         0.086" (2.18mm)           Lead Spacing         -           Lead Spacing         -           Lead Style         -		
Category         Capacitors           Package         1812 (4532 Metric)           Series         VJ OMD           Capacitance         330pF           Tolerance         ±5%           Voltage - Rated         1000V (1kV)           Temperature Coefficient         COG, NPO           Operating Temperature         -55°C ~ 125°C           Features         Soft Termination, High Voltage           Ratings         -           Applications         Boardflex Sensitive           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         1812 (4532 Metric)           Size / Dimension         0.183" L x 0.126" W (4.65mm x 3.20mm)           Height - Seated (Max)         -           Thickness (Max)         0.086" (2.18mm)           Lead Spacing         -           Lead Style         -	Manufacturer Part Number	VJ1812A331JBGAT4X
Package         1812 (4532 Metric)           Series         VJ OMD           Capacitance         330pF           Tolerance         ±5%           Voltage - Rated         1000V (1kV)           Temperature Coefficient         COG, NPO           Operating Temperature         -55°C ~ 125°C           Features         Soft Termination, High Voltage           Ratings         -           Applications         Boardflex Sensitive           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         1812 (4532 Metric)           Size / Dimension         0.183" L x 0.126" W (4.65mm x 3.20mm)           Height - Seated (Max)         -           Thickness (Max)         0.086" (2.18mm)           Lead Spacing         -           Lead Style         -	Manufacturer	Vishay Vitramon
Package         1812 (4532 Metric)           Series         VJ OMD           Capacitance         330pF           Tolerance         ±5%           Voltage - Rated         1000V (1kV)           Temperature Coefficient         C0G, NP0           Operating Temperature         -55°C ~ 125°C           Features         Soft Termination, High Voltage           Ratings         -           Applications         Boardflex Sensitive           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         1812 (4532 Metric)           Size / Dimension         0.183" L x 0.126" W (4.65mm x 3.20mm)           Height - Seated (Max)         -           Thickness (Max)         0.086" (2.18mm)           Lead Spacing         -           Lead Style         -	Category	Capacitors
Series         VJ OMD           Capacitance         330pF           Tolerance         ±5%           Voltage - Rated         1000V (1kV)           Temperature Coefficient         C0G, NP0           Operating Temperature         -55°C ~ 125°C           Features         Soft Termination, High Voltage           Ratings         -           Applications         Boardflex Sensitive           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         1812 (4532 Metric)           Size / Dimension         0.183" L x 0.126" W (4.65mm x 3.20mm)           Height - Seated (Max)         -           Thickness (Max)         0.086" (2.18mm)           Lead Spacing         -           Lead Style         -		Ceramic Capacitors
Capacitance         330pF           Tolerance         ±5%           Voltage - Rated         1000V (1kV)           Temperature Coefficient         COG, NPO           Operating Temperature         -55°C ~ 125°C           Features         Soft Termination, High Voltage           Ratings         -           Applications         Boardflex Sensitive           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         1812 (4532 Metric)           Size / Dimension         0.183" L x 0.126" W (4.65mm x 3.20mm)           Height - Seated (Max)         -           Thickness (Max)         0.086" (2.18mm)           Lead Spacing         -           Lead Style         -	Package	1812 (4532 Metric)
Tolerance ±5%  Voltage - Rated 1000V (1kV)  Temperature Coefficient COG, NP0  Operating Temperature -55°C ~ 125°C  Features Soft Termination, High Voltage  Ratings Applications Boardflex Sensitive  Failure Rate Mounting Type Surface Mount, MLCC  Package / Case 1812 (4532 Metric)  Size / Dimension 0.183" L x 0.126" W (4.65mm x 3.20mm)  Height - Seated (Max)  Thickness (Max) 0.086" (2.18mm)  Lead Spacing  Lead Style	Series	VJ OMD
Voltage - Rated1000V (1kV)Temperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesSoft Termination, High VoltageRatings-ApplicationsBoardflex SensitiveFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1812 (4532 Metric)Size / Dimension0.183" L x 0.126" W (4.65mm x 3.20mm)Height - Seated (Max)-Thickness (Max)0.086" (2.18mm)Lead Spacing-Lead Style-	Capacitance	330pF
Temperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CFeaturesSoft Termination, High VoltageRatings-ApplicationsBoardflex SensitiveFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1812 (4532 Metric)Size / Dimension0.183" L x 0.126" W (4.65mm x 3.20mm)Height - Seated (Max)-Thickness (Max)0.086" (2.18mm)Lead Spacing-Lead Style-	Tolerance	±5%
Operating Temperature-55°C ~ 125°CFeaturesSoft Termination, High VoltageRatings-ApplicationsBoardflex SensitiveFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1812 (4532 Metric)Size / Dimension0.183" L x 0.126" W (4.65mm x 3.20mm)Height - Seated (Max)-Thickness (Max)0.086" (2.18mm)Lead Spacing-Lead Style-	Voltage - Rated	1000V (1kV)
Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1812 (4532 Metric) Size / Dimension 0.183" L x 0.126" W (4.65mm x 3.20mm) Height - Seated (Max) - Thickness (Max) 0.086" (2.18mm) Lead Spacing - Lead Style -	Temperature Coefficient	C0G, NP0
Ratings - Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1812 (4532 Metric) Size / Dimension 0.183" L x 0.126" W (4.65mm x 3.20mm) Height - Seated (Max) - Thickness (Max) 0.086" (2.18mm) Lead Spacing - Lead Style -	Operating Temperature	-55°C ~ 125°C
Applications Boardflex Sensitive  Failure Rate -  Mounting Type Surface Mount, MLCC  Package / Case 1812 (4532 Metric)  Size / Dimension 0.183" L x 0.126" W (4.65mm x 3.20mm)  Height - Seated (Max) -  Thickness (Max) 0.086" (2.18mm)  Lead Spacing -  Lead Style -	Features	Soft Termination, High Voltage
Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1812 (4532 Metric) Size / Dimension 0.183" L x 0.126" W (4.65mm x 3.20mm) Height - Seated (Max) - Thickness (Max) 0.086" (2.18mm) Lead Spacing - Lead Style -	Ratings	-
Mounting Type Surface Mount, MLCC Package / Case 1812 (4532 Metric) Size / Dimension 0.183" L x 0.126" W (4.65mm x 3.20mm) Height - Seated (Max) - Thickness (Max) 0.086" (2.18mm) Lead Spacing - Lead Style -	Applications	Boardflex Sensitive
Package / Case 1812 (4532 Metric) Size / Dimension 0.183" L x 0.126" W (4.65mm x 3.20mm) Height - Seated (Max) - Thickness (Max) 0.086" (2.18mm) Lead Spacing - Lead Style -	Failure Rate	-
Size / Dimension       0.183" L x 0.126" W (4.65mm x 3.20mm)         Height - Seated (Max)       -         Thickness (Max)       0.086" (2.18mm)         Lead Spacing       -         Lead Style       -	Mounting Type	Surface Mount, MLCC
Height - Seated (Max)  Thickness (Max)  Lead Spacing  Lead Style  -  -  -  -  -  -  -  -  -  -  -  -  -	Package / Case	1812 (4532 Metric)
Thickness (Max) 0.086" (2.18mm)  Lead Spacing -  Lead Style -	Size / Dimension	0.183" L x 0.126" W (4.65mm x 3.20mm)
Lead Spacing - Lead Style -	Height - Seated (Max)	-
Lead Style -	Thickness (Max)	0.086" (2.18mm)
	Lead Spacing	-
Report errors?	Lead Style	-
1		Report errors?

## VJ1812A331JBGAT4X Guarantees



#### **Ouality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **VJ1812A331JBGAT4X Payment Methods**



















# VJ1812A331JBGAT4X Shipping Methods













If you have any question about VJ1812A331JBGAT4X, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com