

# VJ2220A222KBGAT4X

### VJ2220A222KBGAT4X Information



For Reference Only

Part Number VJ2220A222KBGAT4X

Manufacturer Vishay Vitramon

**Category** Capacitors

Ceramic Capacitors

**Description** CAP CER 2200PF 1KV NP0 2220

**Package** 2220 (5750 Metric)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# VJ2220A222KBGAT4X Specifications

Manufacturer Part Number  Manufacturer  Vishay Vitramon  Category  Capacitors  Ceramic Capacitors  Package  2220 (5750 Metric)  Series  VJ OMD  Capacitance  2200pF  Tolerance  ±10%  Voltage - Rated  1000V (1kV)  Temperature Coefficient  Cog, NP0  Operating Temperature  -55°C ~ 125°C  Features  Ratings  -Applications  Boardflex Sensitive  Failure Rate  Mounting Type  Surface Mount, MLCC
Category         Capacitors           Package         2220 (5750 Metric)           Series         VJ OMD           Capacitance         2200pF           Tolerance         ±10%           Voltage - Rated         1000V (1kV)           Temperature Coefficient         C0G, NPO           Operating Temperature         -55°C ~ 125°C           Features         Soft Termination, High Voltage           Ratings         -           Applications         Boardflex Sensitive           Failure Rate         -           Mounting Type         Surface Mount, MLCC
Ceramic Capacitors  Package 2220 (5750 Metric)  Series VJ OMD  Capacitance 2200pF  Tolerance ±10%  Voltage - Rated 1000V (1kV)  Temperature Coefficient COG, NPO  Operating Temperature -55°C ~ 125°C  Features Soft Termination, High Voltage  Ratings -  Applications Boardflex Sensitive  Failure Rate  Mounting Type Surface Mount, MLCC
Package 2220 (5750 Metric)  Series VJ OMD  Capacitance 2200pF  Tolerance ±10%  Voltage - Rated 1000V (1kV)  Temperature Coefficient COG, NP0  Operating Temperature -55°C ~ 125°C  Features Soft Termination, High Voltage  Ratings -  Applications Boardflex Sensitive  Failure Rate  Mounting Type Surface Mount, MLCC
Series VJ OMD  Capacitance 2200pF  Tolerance ±10%  Voltage - Rated 1000V (1kV)  Temperature Coefficient COG, NP0  Operating Temperature -55°C ~ 125°C  Features Soft Termination, High Voltage  Ratings -  Applications Boardflex Sensitive  Failure Rate -  Mounting Type Surface Mount, MLCC
Capacitance 2200pF Tolerance ±10%  Voltage - Rated 1000V (1kV) Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC
Tolerance ±10%  Voltage - Rated 1000V (1kV)  Temperature Coefficient C0G, NP0  Operating Temperature -55°C ~ 125°C  Features Soft Termination, High Voltage  Ratings -  Applications Boardflex Sensitive  Failure Rate -  Mounting Type Surface Mount, MLCC
Voltage - Rated  1000V (1kV)  Temperature Coefficient  COG, NP0  Operating Temperature  -55°C ~ 125°C  Features  Soft Termination, High Voltage  Ratings  - Applications  Boardflex Sensitive  Failure Rate  Mounting Type  Surface Mount, MLCC
Temperature Coefficient  COG, NPO  Operating Temperature  -55°C ~ 125°C  Features  Soft Termination, High Voltage  Ratings  -  Applications  Boardflex Sensitive  Failure Rate  Mounting Type  COG, NPO  Soft Termination, High Voltage  Soft Termination, High Voltage
Operating Temperature  -55°C ~ 125°C  Soft Termination, High Voltage  Ratings  - Applications  Boardflex Sensitive  Failure Rate  Mounting Type  Surface Mount, MLCC
Features Soft Termination, High Voltage  Ratings - Applications Boardflex Sensitive  Failure Rate - Mounting Type Surface Mount, MLCC
Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC
Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC
Failure Rate - Mounting Type Surface Mount, MLCC
Mounting Type Surface Mount, MLCC
D 1 /C
Package / Case 2220 (5750 Metric)
Size / Dimension 0.226" L x 0.200" W (5.74mm x 5.08mm)
Height - Seated (Max)
Thickness (Max) 0.086" (2.18mm)
Lead Spacing -
Lead Style -
Report errors

### VJ2220A222KBGAT4X Guarantees



### **Ouality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### VJ2220A222KBGAT4X Payment Methods

































If you have any question about VJ2220A222KBGAT4X, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com