

VPP12-2400

VPP12-2400 Information



Number	VPP12-2400
ufacturer	Triad Magnetics
gory	Transformers Power Transformers
ription	XFRMR LAMINATED 30VA THRU HOLE
age	-
	For the pricing/inventory/lead time, please contact
	us
	Website: https://www.heisener.com
	E-mail: salesdept@heisener.com



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



VPP12-2400 Specifications

ManufacturerTriad MagneticsCategoryTransformersPackage-Package-SeriesPC Mount: World Series?TypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 6.3V, Series 12.6VCurrent - Output (Max)DualSecondary Winding(s)DualSecondary Winding(s)DualPower - Max30 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension66.68mm L x 55.55mm WHeight - Seated (Max)39.67mmVoltage - Isolation4000Vrms		
CategoryTransformersPower TransformersPackagePackageSeriesPC Mount: World Series?TypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 6.3V, Series 12.6VCurrent - Output (Max)Parallel 4.8A, Series 2.4APrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max30 VAMounting TypeThrough HoleSize / Dimension66.68mm L x 55.55mm WHeight - Seated (Max)39.67mmVoltage - Isolation4000VrmsWeight1.2 lbs (544.3g)	Manufacturer Part Number	VPP12-2400
InterfactPower TransformersPackage-SeriesPC Mount: World Series?TypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 6.3V, Series 12.6VCurrent - Output (Max)Parallel 4.8A, Series 2.4APrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max30 VAMounting TypeThrough HoleSize / Dimension66.68mm L x 55.55mm WSize / Dimension39.67mmVoltage - Isolation4000VrmsWeight1.2 lbs (544.3g)	Manufacturer	Triad Magnetics
Package-SeriesPC Mourt: World Series?TypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 6.3V, Series 12.6VCurrent - Output (Max)Parallel 4.8A, Series 2.4APrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max30 VAMounting TypeCroing HoleStez / Dimension66.8mm L x 55.55mm WStez / Dimension39.67mmVoltage - Isolation30.0VWeightSuccondersionWeightSecondersionStez / DimensionSecondersionStez / DimensionSecondersionStez / DimensionSecondersionSter / DimensionSecondersionStez / DimensionSecondersion	Category	Transformers
SeriesPC Mount: World Series?TypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 6.3V, Series 12.6VCurrent - Output (Max)Parallel 4.8A, Series 2.4APrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max30 VAMounting TypeThrough HoleTermination Style66.68mm L x 55.55mm WSize / Dimension39.67mmVoltage - Isolation4000VrmsWeight1.2 lbs (544.3g)		Power Transformers
TypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 6.3V, Series 12.6VCurrent - Output (Max)Parallel 4.8A, Series 2.4APrimary Winding(s)DualSecondary Winding(s)DualPower - MaxNoPower - MaxSol VAMounting TypePrinauge HoleTermination Style66.68mm L x 55.55mm WSize / Dimension39.67mmVoltage - Isolation4000VrmsWeight1.2 lbs (544.3g)	Package	-
Voltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 6.3V, Series 12.6VCurrent - Output (Max)Parallel 4.8A, Series 2.4APrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max30 VAMounting TypeThrough HoleTermination Style66.68mm L x 55.55mm WSize / Dimension39.67mmHeight - Seated (Max)4000VrmsWeight1.2 lbs (544.3g)	Series	PC Mount: World Series?
Voltage - Secondary (Full Load)Parallel 6.3V, Series 12.6VCurrent - Output (Max)Parallel 4.8A, Series 2.4APrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max30 VAMounting TypeThrough HoleTermination Style9C PinSize / Dimension66.68mm L x 55.55mm WHeight - Seated (Max)39.67mmVoltage - Isolation4000VrmsWeight1.2 lbs (544.3g)	Туре	Laminated Core
Current - Output (Max)Parallel 4.8A, Series 2.4APrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max30 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension66.68mm L x 55.55mm WHeight - Seated (Max)39.67mmVoltage - Isolation4000VrmsWeight1.2 lbs (544.3g)	Voltage - Primary	115V, 230V
Primary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max30 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension66.68mm L x 55.55mm WHeight - Seated (Max)39.67mmVoltage - Isolation4000VrmsWeight1.2 lbs (544.3g)	Voltage - Secondary (Full Load)	Parallel 6.3V, Series 12.6V
Secondary Winding(s)DualCenter TapNoPower - Max30 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension66.68mm L x 55.55mm WHeight - Seated (Max)39.67mmVoltage - Isolation4000VrmsWeight1.2 lbs (544.3g)	Current - Output (Max)	Parallel 4.8A, Series 2.4A
Center TapNoPower - Max30 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension66.68mm L x 55.55mm WHeight - Seated (Max)39.67mmVoltage - Isolation4000VrmsWeight1.2 lbs (544.3g)	Primary Winding(s)	Dual
Power - Max30 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension66.68mm L x 55.55mm WHeight - Seated (Max)39.67mmVoltage - Isolation4000VrmsWeight1.2 lbs (544.3g)	Secondary Winding(s)	Dual
Nounting TypeThrough HoleTermination StylePC PinSize / Dimension66.68mm L x 55.55mm WHeight - Seated (Max)39.67mmVoltage - Isolation4000VrmsWeight1.2 lbs (544.3g)	Center Tap	No
Termination StylePC PinSize / Dimension66.68mm L x 55.55mm WHeight - Seated (Max)39.67mmVoltage - Isolation4000VrmsWeight1.2 lbs (544.3g)	Power - Max	30 VA
Size / Dimension 66.68mm L x 55.55mm W Height - Seated (Max) 39.67mm Voltage - Isolation 4000Vrms Weight 1.2 lbs (544.3g)	Mounting Type	Through Hole
Height - Seated (Max)39.67mmVoltage - Isolation4000VrmsWeight1.2 lbs (544.3g)	Termination Style	PC Pin
Voltage - Isolation4000VrmsWeight1.2 lbs (544.3g)	Size / Dimension	66.68mm L x 55.55mm W
Weight 1.2 lbs (544.3g)	Height - Seated (Max)	39.67mm
	Voltage - Isolation	4000Vrms
Report errors?	Weight	1.2 lbs (544.3g)
		Report errors?

VPP12-2400 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about VPP12-2400, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com