

VPP20-1000 Information



For Reference Only

Part Number VPP20-1000

Manufacturer Triad Magnetics

Category Transformers
Power Transformers

Description XFRMR LAMINATED 20VA THRU HOLE

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









VPP20-1000 Specifications

Manufacturer Part Number VPP20-1000 Manufacturer Triad Magnetics Category Transformers Package - Series PC Mount: World Series? Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 10V, Series 20V Current - Output (Max) Parallel 2A, Series 1A Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 20 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 57.15mm L x 47.63mm W Height - Seated (Max) 41.28mm Voltage - Isolation 4000Vrms Weight 0.9 lb (408.23g)		
Category Transformers Package - Series PC Mount: World Series? Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 10V, Series 20V Current - Output (Max) Parallel 2A, Series 1A Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 20 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 57.15mm L x 47.63mm W Height - Seated (Max) 41.28mm Voltage - Isolation 4000Vrms Weight 0.9 lb (408.23g)	Manufacturer Part Number	VPP20-1000
Package Power Transformers Package PC Mount: World Series? Type Laminated Core Voltage - Primary I15V, 230V Voltage - Secondary (Full Load) Parallel 10V, Series 20V Current - Output (Max) Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 20 VA Mounting Type Through Hole Termination Style Size / Dimension Fixed Max) Voltage - Isolation Voltage - Isolation Power Transformers PC Mount: World Series? PC Mount: World Series? PC Mount: World Series? PC Mount: World Series? Parallel 10V, Series 20V Parallel 10V, Series 20V Parallel 2A, Series 1A Pual Poual Poua	Manufacturer	Triad Magnetics
Package-SeriesPC Mount: World Series?TypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 10V, Series 20VCurrent - Output (Max)Parallel 2A, Series 1APrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max20 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension57.15mm L x 47.63mm WHeight - Seated (Max)41.28mmVoltage - Isolation4000VrmsWeight0.9 lb (408.23g)	Category	Transformers
SeriesPC Mount: World Series?TypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 10V, Series 20VCurrent - Output (Max)Parallel 2A, Series 1APrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max20 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension57.15mm L x 47.63mm WHeight - Seated (Max)41.28mmVoltage - Isolation4000VrmsWeight0.9 lb (408.23g)		Power Transformers
Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 10V, Series 20V Current - Output (Max) Parallel 2A, Series 1A Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 20 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 57.15mm L x 47.63mm W Height - Seated (Max) 41.28mm Voltage - Isolation 4000Vrms Weight 0.9 lb (408.23g)	Package	-
Voltage - Primary Voltage - Secondary (Full Load) Parallel 10V, Series 20V Current - Output (Max) Parallel 2A, Series 1A Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 20 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 57.15mm L x 47.63mm W Height - Seated (Max) Voltage - Isolation Weight 4000Vrms Weight	Series	PC Mount: World Series?
Voltage - Secondary (Full Load) Current - Output (Max) Parallel 2A, Series 1A Primary Winding(s) Dual Secondary Winding(s) Center Tap No Power - Max 20 VA Mounting Type Through Hole Termination Style Size / Dimension For Easted (Max) Voltage - Isolation Weight Parallel 10V, Series 20V Parallel 10V, Series 1A Dual Secondary Winding(s) A	Туре	Laminated Core
Current - Output (Max) Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 20 VA Mounting Type Through Hole Termination Style Size / Dimension Size / Dimension Voltage - Isolation Weight Parallel 2A, Series 1A Parallel 2A, Series 1A Parallel 2A, Series 1A Pual Pual Pual Pual Poual	Voltage - Primary	115V, 230V
Primary Winding(s) Secondary Winding(s) Dual Center Tap No Power - Max 20 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 57.15mm L x 47.63mm W Height - Seated (Max) Voltage - Isolation Weight Dual No 104 104 105 105 105 105 105 105	Voltage - Secondary (Full Load)	Parallel 10V, Series 20V
Secondary Winding(s)DualCenter TapNoPower - Max20 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension57.15mm L x 47.63mm WHeight - Seated (Max)41.28mmVoltage - Isolation4000VrmsWeight0.9 lb (408.23g)	Current - Output (Max)	Parallel 2A, Series 1A
Center Tap No Power - Max 20 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 57.15mm L x 47.63mm W Height - Seated (Max) 41.28mm Voltage - Isolation 4000Vrms Weight 0.9 lb (408.23g)	Primary Winding(s)	Dual
Power - Max Mounting Type Through Hole Termination Style PC Pin Size / Dimension 57.15mm L x 47.63mm W Height - Seated (Max) Voltage - Isolation Weight 20 VA PC Pin 40.00 Pin 40.00 Vims 40.00 Vims 0.9 lb (408.23g)	Secondary Winding(s)	Dual
Mounting Type Through Hole Termination Style PC Pin Size / Dimension 57.15mm L x 47.63mm W Height - Seated (Max) 41.28mm Voltage - Isolation 4000Vrms Weight 0.9 lb (408.23g)	Center Tap	No
Termination Style PC Pin Size / Dimension 57.15mm L x 47.63mm W Height - Seated (Max) 41.28mm Voltage - Isolation 4000Vrms Weight 0.9 lb (408.23g)	Power - Max	20 VA
Size / Dimension 57.15mm L x 47.63mm W Height - Seated (Max) 41.28mm Voltage - Isolation 4000Vrms Weight 0.9 lb (408.23g)	Mounting Type	Through Hole
Height - Seated (Max) Voltage - Isolation Weight 41.28mm 4000Vrms 0.9 lb (408.23g)	Termination Style	PC Pin
Voltage - Isolation 4000Vrms Weight 0.9 lb (408.23g)	Size / Dimension	57.15mm L x 47.63mm W
Weight 0.9 lb (408.23g)	Height - Seated (Max)	41.28mm
	Voltage - Isolation	4000Vrms
Report errors?	Weight	0.9 lb (408.23g)
		Report errors?

VPP20-1000 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

VPP20-1000 Payment Methods



















VPP20-1000 Shipping Methods













If you have any question about VPP20-1000, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com