



VSBU-120-T312B Information



For Reference Only

Part Number VSBU-120-T312B

Manufacturer CUI Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Converters

Description AC/DC CNVRTR 3.3V 12V 12V 120W

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









VSBU-120-T312B Specifications

Manufacturer Part Number VSBU-120-T312B Manufacturer CUI Inc. Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series VSBU-120-T Type Open Frame Number of Outputs 3 Voltage - Input 90 ~ 260 VAC Voltage - Output 1 3.3V Voltage - Output 2 12V Voltage - Output 3 12V Voltage - Output 4 - Current - Output (Max) 15A, 6A, 800mA Power (Watts) 120W Applications ITE (Commercial) Voltage - Isolation 4.242kV (4242V) Efficiency 80% Operating Temperature 0°C ~ 70°C Features PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.28" H (127.0mm x 76.2mm x 32.5mm)			
Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series VSBU-120-T Type Open Frame Number of Outputs 3 Voltage - Input 90 ~ 260 VAC Voltage - Output 1 3.3V Voltage - Output 2 12V Voltage - Output 3 12V Voltage - Output (Max) 15A, 6A, 800mA Power (Watts) 120W Applications ITE (Commercial) Voltage - Isolation 4.242kV (4242V) Efficiency 80% Operating Temperature 0°C ~ 70°C Features PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.28" H (127.0mm x 76.2mm x 32.5mm)	Manufacturer Part Number	VSBU-120-T312B	
Package - Series VSBU-120-T Type Open Frame Number of Outputs 3 Voltage - Input 90 ~ 260 VAC Voltage - Output 1 3.3V Voltage - Output 2 12V Voltage - Output 3 12V Voltage - Output 4 - Current - Output (Max) 15A, 6A, 800mA Power (Watts) 120W Applications ITE (Commercial) Voltage - Isolation 4.242kV (4242V) Efficiency 80% Operating Temperature 0°C ~ 70°C Features PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.28" H (127.0mm x 76.2mm x 32.5mm)	Manufacturer	CUI Inc.	
Package - Series VSBU-120-T Type Open Frame Number of Outputs 3 Voltage - Input 90 ~ 260 VAC Voltage - Output 1 3.3V Voltage - Output 2 12V Voltage - Output 3 12V Voltage - Output 4 - Current - Output (Max) 15A, 6A, 800mA Power (Watts) 120W Applications ITE (Commercial) Voltage - Isolation 4.242kV (4242V) Efficiency 80% Operating Temperature 0°C ~ 70°C Features PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.28" H (127.0mm x 76.2mm x 32.5mm)	Category	Power Supplies - External/Internal (Off-Board)	
Series VSBU-120-T Type Open Frame Number of Outputs 3 Voltage - Input 90 ~ 260 VAC Voltage - Output 1 3.3V Voltage - Output 2 12V Voltage - Output 3 12V Voltage - Output 4 - Current - Output (Max) 15A, 6A, 800mA Power (Watts) 120W Applications ITE (Commercial) Voltage - Isolation 4.242kV (4242V) Efficiency 80% Operating Temperature 0°C ~ 70°C Features PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.28" H (127.0mm x 76.2mm x 32.5mm)		AC DC Converters	
Type Open Frame Number of Outputs 3 Voltage - Input 90 ~ 260 VAC Voltage - Output 1 3.3V Voltage - Output 2 12V Voltage - Output 3 12V Voltage - Output 4 - Current - Output (Max) 15A, 6A, 800mA Power (Watts) 120W Applications ITE (Commercial) Voltage - Isolation 4.242kV (4242V) Efficiency 80% Operating Temperature 0°C ~ 70°C Features PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.28" H (127.0mm x 76.2mm x 32.5mm)	Package	-	
Number of Outputs 3 Voltage - Input 90 ~ 260 VAC Voltage - Output 1 3.3V Voltage - Output 2 12V Voltage - Output 3 12V Voltage - Output 4 - Current - Output (Max) 15A, 6A, 800mA Power (Watts) 120W Applications ITE (Commercial) Voltage - Isolation 4.242kV (4242V) Efficiency 80% Operating Temperature 0°C ~ 70°C Features PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.28" H (127.0mm x 76.2mm x 32.5mm)	Series	VSBU-120-T	
Voltage - Input 90 ~ 260 VAC Voltage - Output 1 3.3V Voltage - Output 2 12V Voltage - Output 3 12V Voltage - Output 4 - Current - Output (Max) 15A, 6A, 800mA Power (Watts) 120W Applications ITE (Commercial) Voltage - Isolation 4.242kV (4242V) Efficiency 80% Operating Temperature 0°C ~ 70°C Features PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.28" H (127.0mm x 76.2mm x 32.5mm)	Туре	Open Frame	
Voltage - Output 1 3.3V Voltage - Output 2 12V Voltage - Output 3 12V Voltage - Output 4 - Current - Output (Max) 15A, 6A, 800mA Power (Watts) 120W Applications ITE (Commercial) Voltage - Isolation 4.242kV (4242V) Efficiency 80% Operating Temperature 0°C ~ 70°C Features PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.28" H (127.0mm x 76.2mm x 32.5mm)	Number of Outputs	3	
Voltage - Output 2 Voltage - Output 3 12V Voltage - Output 4 - Current - Output (Max) Power (Watts) 120W Applications ITE (Commercial) Voltage - Isolation 4.242kV (4242V) Efficiency 80% Operating Temperature PFC, Universal Input Mounting Type Size / Dimension 12V 12V	Voltage - Input	90 ~ 260 VAC	
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation 4.242kV (4242V) Efficiency Operating Temperature O°C ~ 70°C Features PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 12V	Voltage - Output 1	3.3V	
Voltage - Output 4 Current - Output (Max) 15A, 6A, 800mA Power (Watts) 120W Applications ITE (Commercial) Voltage - Isolation 4.242kV (4242V) Efficiency 80% Operating Temperature 0°C ~ 70°C Features PFC, Universal Input Mounting Type Chassis Mount Size / Dimension	Voltage - Output 2	12V	
Current - Output (Max) Power (Watts) 120W Applications ITE (Commercial) Voltage - Isolation 4.242kV (4242V) Efficiency 80% Operating Temperature 0°C ~ 70°C Features PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 15A, 6A, 800mA 120W A. 800m A. 90m A. 90m	Voltage - Output 3	12V	
Power (Watts) Applications ITE (Commercial) Voltage - Isolation 4.242kV (4242V) Efficiency 80% Operating Temperature 0°C ~ 70°C Features PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 120W 4.242kV (4242V) 80% 5.00" L x 3.00" W x 1.28" H (127.0mm x 76.2mm x 32.5mm)	Voltage - Output 4	-	
Applications ITE (Commercial) Voltage - Isolation 4.242kV (4242V) Efficiency 80% Operating Temperature 0°C ~ 70°C Features PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.28" H (127.0mm x 76.2mm x 32.5mm)	Current - Output (Max)	15A, 6A, 800mA	
Voltage - Isolation $4.242kV$ ($4242V$)Efficiency 80% Operating Temperature $0^{\circ}C \sim 70^{\circ}C$ FeaturesPFC, Universal InputMounting TypeChassis MountSize / Dimension 5.00 " L x 3.00 " W x 1.28 " H (127.0 mm x 76.2 mm x 32.5 mm)	Power (Watts)	120W	
Efficiency 80% Operating Temperature $0^{\circ}\text{C} \sim 70^{\circ}\text{C}$ Features PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.28" H (127.0mm x 76.2mm x 32.5mm)	Applications	ITE (Commercial)	
Operating Temperature 0°C ~ 70°C Features PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.28" H (127.0mm x 76.2mm x 32.5mm)	Voltage - Isolation	4.242kV (4242V)	
Features PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.28" H (127.0mm x 76.2mm x 32.5mm)	Efficiency	80%	
Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.28" H (127.0mm x 76.2mm x 32.5mm)	Operating Temperature	0°C ~ 70°C	
Size / Dimension 5.00" L x 3.00" W x 1.28" H (127.0mm x 76.2mm x 32.5mm)	Features	PFC, Universal Input	
	Mounting Type	Chassis Mount	
Report errors?	Size / Dimension	5.00" L x 3.00" W x 1.28" H (127.0mm x 76.2mm x 32.5mm)	
			Report errors?

VSBU-120-T312B Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

VSBU-120-T312B Payment Methods





















VSBU-120-T312B Shipping Methods













If you have any question about VSBU-120-T312B, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com