

**VX1810310000G Information**


For Reference Only

**Part Number** [VX1810310000G](#)  
**Manufacturer** Amphenol Anytek  
**Category** Connectors, Interconnects  
[Terminal Blocks - Headers, Plugs and Sockets](#)  
**Description** TERM BLOCK HDR 18POS 90DEG 3.5MM  
**Package** -  
 For the pricing/inventory/lead time, please contact us  
 Website: <https://www.heisener.com>  
 E-mail: [salesdept@heisener.com](mailto:salesdept@heisener.com)



[Request a Quote](#)

**Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.


**VX1810310000G Specifications**

|                                       |   |
|---------------------------------------|---|
| Manufacturer Part Number              | <a href="#">VX1810310000G</a>   |
| Manufacturer                          | Amphenol Anytek   |
| Category                              | Connectors, Interconnects<br><a href="#">Terminal Blocks - Headers, Plugs and Sockets</a> |
| Package                               | -   |
| Series                                | VX  |
| Type                                  | Header, Male Pins, Shrouded (2 Side)  |
| Number of Positions                   | 18  |
| Positions Per Level                   | 9   |
| Number of Levels                      | 2   |
| Pitch                                 | 0.138" (3.50mm)   |
| Header Orientation                    | 90°, Right Angle  |
| Plug Wire Entry                       | -   |
| Termination Style                     | Solder  |
| Mounting Type                         | Through Hole  |
| Current - IEC                         | -   |
| Voltage - IEC                         | -   |
| Current - UL                          | 7A  |
| Voltage - UL                          | 150V  |
| Wire Gauge or Range - AWG             | -   |
| Wire Gauge or Range - mm <sup>2</sup> | -   |
| Color                                 | Orange  |
| Operating Temperature                 | -40°C ~ 115°C   |
| Contact Mating Finish                 | Tin   |

