

## **WAU16-500 Information**



For Reference Only

Part Number WAU16-500 Manufacturer Triad Magnetics

Category Power Supplies - External/Internal (Off-Board)

AC AC Wall Adapters

**Description** AC/AC WALL MNT ADAPTER 16V 500MA

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **WAU16-500 Specifications**

Manufacturer Part Number         WAU16-500           Manufacturer         Triad Magnetics           Category         Power Supplies - External/Internal (Off-Board)           AC AC Wall Adapters           Package         -           Series         WAU16           Region Utilized         North America           Form         Wall Mount (Class II)           Input Type         Fixed Blade           Voltage - Input         120VAC           Voltage - Output         16VAC           Current - Output (Max)         500mA           Power (Watts)         8W           No Load Power Consumption         -           Applications         ITE (Commercial)           Efficiency         -           Operating Temperature         -10°C ~ 40°C           Output Connector         Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm           Size / Dimension         1.89" L x 2.36" W x 3.15" H (48.0mm x 60.0mm x 80.0mm)           Approvals         cUL, UL			
Category         Power Supplies - External/Internal (Off-Board)           AC AC Wall Adapters           Package         -           Series         WAU16           Region Utilized         North America           Form         Wall Mount (Class II)           Input Type         Fixed Blade           Voltage - Input         120VAC           Voltage - Output         16VAC           Current - Output (Max)         500mA           Power (Watts)         8W           No Load Power Consumption         -           Applications         ITE (Commercial)           Efficiency         -           Operating Temperature         -10°C ~ 40°C           Output Connector         Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm           Size / Dimension         1.89" L x 2.36" W x 3.15" H (48.0mm x 60.0mm x 80.0mm)           Approvals         cUL, UL	Manufacturer Part Number	WAU16-500	
Package         -           Series         WAU16           Region Utilized         North America           Form         Wall Mount (Class II)           Input Type         Fixed Blade           Voltage - Input         120VAC           Voltage - Output         16VAC           Current - Output (Max)         500mA           Power (Watts)         8W           No Load Power Consumption         -           Applications         ITE (Commercial)           Efficiency         -           Operating Temperature         -10°C ~ 40°C           Output Connector         Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm           Size / Dimension         1.89" L x 2.36" W x 3.15" H (48.0mm x 60.0mm x 80.0mm)           Approvals         cUL, UL	Manufacturer	Triad Magnetics	
Package         -           Series         WAU16           Region Utilized         North America           Form         Wall Mount (Class II)           Input Type         Fixed Blade           Voltage - Input         120VAC           Voltage - Output         16VAC           Current - Output (Max)         500mA           Power (Watts)         8W           No Load Power Consumption         -           Applications         ITE (Commercial)           Efficiency         -           Operating Temperature         -10°C ~ 40°C           Output Connector         Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm           Size / Dimension         1.89" L x 2.36" W x 3.15" H (48.0mm x 60.0mm x 80.0mm)           Approvals         cUL, UL	Category	Power Supplies - External/Internal (Off-Board)	
SeriesWAU16Region UtilizedNorth AmericaFormWall Mount (Class II)Input TypeFixed BladeVoltage - Input120 V ACVoltage - Output16 V ACCurrent - Output (Max)500mAPower (Watts)8WNo Load Power Consumption-ApplicationsITE (Commercial)Efficiency-Operating Temperature-10°C ~ 40°COutput ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mmSize / Dimension1.89" L x 2.36" W x 3.15" H (48.0mm x 60.0mm x 80.0mm)ApprovalscUL, UL		AC AC Wall Adapters	
Region Utilized North America Form Wall Mount (Class II) Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 16VAC Current - Output (Max) 500mA Power (Watts) 8W No Load Power Consumption - Applications ITE (Commercial) Efficiency - Operating Temperature -10°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 1.89" L x 2.36" W x 3.15" H (48.0mm x 60.0mm x 80.0mm) Approvals cUL, UL	Package	-	
Form Wall Mount (Class II)  Input Type Fixed Blade  Voltage - Input 120 VAC  Voltage - Output 16 VAC  Current - Output (Max) 500mA  Power (Watts) 8W  No Load Power Consumption -  Applications ITE (Commercial)  Efficiency -  Operating Temperature -10°C ~ 40°C  Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm  Size / Dimension 1.89" L x 2.36" W x 3.15" H (48.0mm x 60.0mm x 80.0mm)  Approvals cUL, UL	Series	WAU16	
Input Type Fixed Blade  Voltage - Input 120VAC  Voltage - Output 16VAC  Current - Output (Max) 500mA  Power (Watts) 8W  No Load Power Consumption -  Applications ITE (Commercial)  Efficiency - Operating Temperature -10°C ~ 40°C  Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm  Size / Dimension 1.89" L x 2.36" W x 3.15" H (48.0mm x 60.0mm x 80.0mm)  Approvals cUL, UL	Region Utilized	North America	
Voltage - Input  120VAC  Voltage - Output  16VAC  Current - Output (Max)  500mA  Power (Watts)  No Load Power Consumption  - Applications  ITE (Commercial)  Efficiency  Operating Temperature  Output Connector  Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm  Size / Dimension  1.89" L x 2.36" W x 3.15" H (48.0mm x 60.0mm x 80.0mm)  Approvals  cUL, UL	Form	Wall Mount (Class II)	
Voltage - Output  Current - Output (Max)  500mA  Power (Watts)  No Load Power Consumption  Applications  ITE (Commercial)  Efficiency  Operating Temperature  -10°C ~ 40°C  Output Connector  Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm  Size / Dimension  1.89" L x 2.36" W x 3.15" H (48.0mm x 60.0mm x 80.0mm)  cUL, UL	Input Type	Fixed Blade	
Current - Output (Max)  Fower (Watts)  No Load Power Consumption  Applications  ITE (Commercial)  Efficiency  Operating Temperature  -10°C ~ 40°C  Output Connector  Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm  Size / Dimension  1.89" L x 2.36" W x 3.15" H (48.0mm x 60.0mm x 80.0mm)  Approvals  cUL, UL	Voltage - Input	120VAC	
Power (Watts)  No Load Power Consumption  Applications  ITE (Commercial)  Efficiency  Operating Temperature  -10°C ~ 40°C  Output Connector  Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm  Size / Dimension  1.89" L x 2.36" W x 3.15" H (48.0mm x 60.0mm x 80.0mm)  Approvals  cUL, UL	Voltage - Output	16VAC	
No Load Power Consumption  Applications  ITE (Commercial)  Efficiency  Operating Temperature  -10°C ~ 40°C  Output Connector  Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm  Size / Dimension  1.89" L x 2.36" W x 3.15" H (48.0mm x 60.0mm x 80.0mm)  Approvals  cUL, UL	Current - Output (Max)	500mA	
Applications ITE (Commercial)  Efficiency - Operating Temperature -10°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 1.89" L x 2.36" W x 3.15" H (48.0mm x 60.0mm x 80.0mm) Approvals cUL, UL	Power (Watts)	8W	
Efficiency -	No Load Power Consumption	-	
Operating Temperature $-10^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 1.89" L x 2.36" W x 3.15" H (48.0mm x 60.0mm x 80.0mm) Approvals cUL, UL	Applications	ITE (Commercial)	
Output Connector  Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm  Size / Dimension  1.89" L x 2.36" W x 3.15" H (48.0mm x 60.0mm x 80.0mm)  cUL, UL	Efficiency	-	
Size / Dimension       1.89" L x 2.36" W x 3.15" H (48.0mm x 60.0mm x 80.0mm)         Approvals       cUL, UL	Operating Temperature	-10°C ~ 40°C	
Approvals cUL, UL	Output Connector	Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 11.0mm	
	Size / Dimension	1.89" L x 2.36" W x 3.15" H (48.0mm x 60.0mm x 80.0mm)	
Report errors?	Approvals	cUL, UL	
			Report errors?

#### **WAU16-500 Guarantees**



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **WAU16-500 Payment Methods**





















## **WAU16-500 Shipping Methods**













If you have any question about WAU16-500, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com