



WFH230L75RJE Information

www.heisener.com

For Reference Only

Part Number WFH230L75RJE

Manufacturer Ohmite
Category Resistors

Chassis Mount Resistors

Description RES CHAS MNT 75 OHM 5% 230W

Package Radial, Rectangular Case

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









WFH230L75RJE Specifications

Manufacturer Part Number WFH230L75RJE Manufacturer Ohmite Category Resistors Package Radial, Rectangular Case Series WFH Resistance 75 Ohms Tolerance ±5% Power (Watts) 230W Composition Wirewound Temperature Coefficient - Operating Temperature -40°C ~ 220°C Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 8.268" L x 2.008" W (210.00mm x 51.00mm) Height - Seated (Max) 0.496" (12.60mm) Lead Style Solder Lugs Package / Case Radial, Rectangular Case Failure Rate -		
Category Resistors Package Radial, Rectangular Case Series WFH Resistance 75 Ohms Tolerance ±5% Power (Watts) 230W Composition Wirewound Temperature Coefficient - Operating Temperature -40°C ~ 220°C Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 8.268" L x 2.008" W (210.00mm x 51.00mm) Height - Seated (Max) 0.496" (12.60mm) Lead Style Solder Lugs Package / Case Radial, Rectangular Case Failure Rate -	Manufacturer Part Number	WFH230L75RJE
Chassis Mount Resistors Package Radial, Rectangular Case WFH Resistance 75 Ohms Tolerance ±5% Power (Watts) 230W Composition Wirewound Temperature Coefficient - Operating Temperature -40°C ~ 220°C Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 8.268" L x 2.008" W (210.00mm x 51.00mm) Height - Seated (Max) Lead Style Package / Case Radial, Rectangular Case Failure Rate Chassis Mount Resistors WFH Audit Case Radial, Rectangular Case Failure Rate Coating, Housing Type Aluminum 8.268" L x 2.008" W (210.00mm x 51.00mm) Coating, Housing Type Radial, Rectangular Case Failure Rate	Manufacturer	Ohmite
Package Radial, Rectangular Case Series WFH Resistance 75 Ohms Tolerance ±5% Power (Watts) 230W Composition Wirewound Temperature Coefficient - Operating Temperature -40°C ~ 220°C Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 8.268" L x 2.008" W (210.00mm x 51.00mm) Height - Seated (Max) 0.496" (12.60mm) Lead Style Solder Lugs Package / Case Radial, Rectangular Case Failure Rate -	Category	Resistors
Series WFH Resistance 75 Ohms Tolerance ±5% Power (Watts) 230W Composition Wirewound Temperature Coefficient - Operating Temperature -40°C ~ 220°C Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 8.268" L x 2.008" W (210.00mm x 51.00mm) Height - Seated (Max) 0.496" (12.60mm) Lead Style Solder Lugs Package / Case Radial, Rectangular Case Failure Rate -		Chassis Mount Resistors
Resistance 75 Ohms Tolerance ±5% Power (Watts) 230W Composition Wirewound Temperature Coefficient - Operating Temperature -40°C ~ 220°C Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 8.268" L x 2.008" W (210.00mm x 51.00mm) Height - Seated (Max) 0.496" (12.60mm) Lead Style Solder Lugs Package / Case Radial, Rectangular Case Failure Rate -	Package	Radial, Rectangular Case
Tolerance ±5% Power (Watts) 230W Composition Wirewound Temperature Coefficient - Operating Temperature -40°C ~ 220°C Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 8.268" L x 2.008" W (210.00mm x 51.00mm) Height - Seated (Max) 0.496" (12.60mm) Lead Style Solder Lugs Package / Case Radial, Rectangular Case Failure Rate -	Series	WFH
Power (Watts) Composition Wirewound Temperature Coefficient Operating Temperature -40°C ~ 220°C Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 8.268" L x 2.008" W (210.00mm x 51.00mm) Height - Seated (Max) Lead Style Package / Case Radial, Rectangular Case Failure Rate -	Resistance	75 Ohms
Composition Wirewound Temperature Coefficient - Operating Temperature -40°C ~ 220°C Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 8.268" L x 2.008" W (210.00mm x 51.00mm) Height - Seated (Max) 0.496" (12.60mm) Lead Style Solder Lugs Package / Case Radial, Rectangular Case Failure Rate -	Tolerance	±5%
Temperature Coefficient Operating Temperature -40°C ~ 220°C Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 8.268" L x 2.008" W (210.00mm x 51.00mm) Height - Seated (Max) 0.496" (12.60mm) Lead Style Solder Lugs Package / Case Radial, Rectangular Case Failure Rate -	Power (Watts)	230W
Operating Temperature -40°C ~ 220°C Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 8.268" L x 2.008" W (210.00mm x 51.00mm) Height - Seated (Max) 0.496" (12.60mm) Lead Style Solder Lugs Package / Case Radial, Rectangular Case Failure Rate -	Composition	Wirewound
Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 8.268" L x 2.008" W (210.00mm x 51.00mm) Height - Seated (Max) 0.496" (12.60mm) Lead Style Solder Lugs Package / Case Radial, Rectangular Case Failure Rate -	Temperature Coefficient	-
Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 8.268" L x 2.008" W (210.00mm x 51.00mm) Height - Seated (Max) 0.496" (12.60mm) Lead Style Solder Lugs Package / Case Radial, Rectangular Case Failure Rate -	Operating Temperature	-40°C ~ 220°C
Mounting Feature Size / Dimension 8.268" L x 2.008" W (210.00mm x 51.00mm) Height - Seated (Max) 0.496" (12.60mm) Lead Style Solder Lugs Package / Case Radial, Rectangular Case Failure Rate -	Features	-
Size / Dimension 8.268" L x 2.008" W (210.00mm x 51.00mm) Height - Seated (Max) 0.496" (12.60mm) Lead Style Solder Lugs Package / Case Radial, Rectangular Case Failure Rate -	Coating, Housing Type	Aluminum
Height - Seated (Max) Lead Style Package / Case Failure Rate 0.496" (12.60mm) Solder Lugs Radial, Rectangular Case -	Mounting Feature	Flanges
Lead StyleSolder LugsPackage / CaseRadial, Rectangular CaseFailure Rate-	Size / Dimension	8.268" L x 2.008" W (210.00mm x 51.00mm)
Package / Case Radial, Rectangular Case Failure Rate -	Height - Seated (Max)	0.496" (12.60mm)
Failure Rate -	Lead Style	Solder Lugs
	Package / Case	Radial, Rectangular Case
Report errors?	Failure Rate	-
		Report errors?

WFH230L75RJE Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

WFH230L75RJE Payment Methods



















WFH230L75RJE Shipping Methods













If you have any question about WFH230L75RJE, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com