

WM8953ECS/RV

quest a Quote

WM8953ECS/RV Information

For Reference Only	Part Number	WM8953ECS/RV
	Manufacturer	Cirrus Logic Inc.
	Category	Integrated Circuits (ICs) Data Acquisition - ADCs/DACs - Special Purpose
	Description	IC ADC MONO MIC-INPUT 42WCSP
	Package	42-WFBGA, WLCSP
		For the pricing/inventory/lead time, please contact us
		Website: https://www.heisener.com E-mail: salesdept@heisener.com

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



WM8953ECS/RV Specifications

Manufacturer Part NumberWM8953ECS/RVManufacturerCirrus Logic Inc.CategoryIntegrated Circuits (ICS) Data Acquisition - ADCs/DACs - Special PurposePackage42-WFBGA, WLCSPSeries-TypeADC, AudioNumber of Channels-Sendution (Bits)24 bSampling Rate (Per Second)48kVoltage Supply SourceAnalog and DigitalVoltage Supply Source40°C ~ 85°CMounting TypeSurface MountPackage / Case24-WFBGA, WLCSP			
CategoryIntegrated Circuits (ICs)Data Acquisition - ADCs/DACs - Special PurposePackage42-WFBGA, WLCSPSeries-TypeADC, AudioNumber of Channels-Resolution (Bits)24 bSampling Rate (Per Second)48kData InterfaceDSP, I2SVoltage Supply Source.4nolog and DigitalVoltage - Supply.40°C ~ 85°CMounting TypeSurface MountPackage / Case42-WERGA, WLCSPSupplier Device Package42-WERGA, WLCSP	Manufacturer Part Number	WM8953ECS/RV	
NateData Acquisition - ADCs/DACs - Special PurposePackage42-WFBGA, WLCSPSeries-TypeADC, AudioNumber of Channels-Resolution (Bits)24 bSampling Rate (Per Second)48kData InterfaceDSP, I2SVoltage Supply SourceAnalog and DigitalVoltage - Supply1.71 V ~ 3.6 VOperating Temperature40°C ~ 85°CMounting TypeSurface MountPackage / Case42-WFBGA, WLCSPSupplier Device Package42-WLCSP	Manufacturer	Cirrus Logic Inc.	
Package42-WFBGA, WLCSPSeries-TypeADC, AudioNumber of Channels-Resolution (Bits)24 bSampling Rate (Per Second)48kData InterfaceDSP, I2SVoltage Supply SourceAnalog and DigitalVoltage - Supply1.71 V ~ 3.6 VOperating TemperatureSurface MountPackage / Case42-WFBGA, WLCSPSupplier Device Package42-WLCSP	Category	Integrated Circuits (ICs)	
Series-Series-TypeADC, AudioNumber of Channels-Resolution (Bits)24 bSampling Rate (Per Second)48kData InterfaceDSP, I2SVoltage Supply SourceAnalog and DigitalVoltage - Supply1.71 V ~ 3.6 VOperating TemperatureSurface MountPackage / CaseSurface MountPackage / Case42-WFBGA, WLCSP		Data Acquisition - ADCs/DACs - Special Purpose	
TypeADC, AudioNumber of Channels-Resolution (Bits)24 bSampling Rate (Per Second)48kData InterfaceDSP, I2SVoltage Supply SourceAnalog and DigitalVoltage - Supply1.71 V ~ 3.6 VOperating Temperature40°C ~ 85°CMounting TypeSurface MountPackage / Case42-WFBGA, WLCSP	Package	42-WFBGA, WLCSP	
Number of Channels-Resolution (Bits)24 bSampling Rate (Per Second)48kData InterfaceDSP, I2SVoltage Supply SourceAnalog and DigitalVoltage - Supply1.71 V ~ 3.6 VOperating Temperature-40°C ~ 85°CMounting TypeSurface MountPackage / Case42-WFBGA, WLCSPSupplier Device Package42-WLCSP	Series	-	
Resolution (Bits)24 bSampling Rate (Per Second)48kData InterfaceDSP, I2SVoltage Supply SourceAnalog and DigitalVoltage - Supply1.71 V ~ 3.6 VOperating Temperature-40°C ~ 85°CMounting TypeSurface MountPackage / Case42-WFBGA, WLCSPSupplier Device Package42-WLCSP	Туре	ADC, Audio	
Sampling Rate (Per Second)48kData InterfaceDSP, I2SVoltage Supply SourceAnalog and DigitalVoltage - Supply1.71 V ~ 3.6 VOperating Temperature-40°C ~ 85°CMounting TypeSurface MountPackage / Case42·WFBGA, WLCSPSupplier Device Package42·WLCSP	Number of Channels	-	
Data InterfaceDSP, I2SVoltage Supply SourceAnalog and DigitalVoltage - Supply1.71 V ~ 3.6 VOperating Temperature-40°C ~ 85°CMounting TypeSurface MountPackage / Case42-WFBGA, WLCSPSupplier Device Package42-WLCSP	Resolution (Bits)	24 b	
Voltage Supply SourceAnalog and DigitalVoltage - Supply1.71 V ~ 3.6 VOperating Temperature-40°C ~ 85°CMounting TypeSurface MountPackage / Case42-WFBGA, WLCSPSupplier Device Package42-WLCSP	Sampling Rate (Per Second)	48k	
Voltage - Supply1.71 V ~ 3.6 VOperating Temperature-40°C ~ 85°CMounting TypeSurface MountPackage / Case42-WFBGA, WLCSPSupplier Device Package42-WLCSP	Data Interface	DSP, I2S	
Operating Temperature-40°C ~ 85°CMounting TypeSurface MountPackage / Case42-WFBGA, WLCSPSupplier Device Package42-WLCSP	Voltage Supply Source	Analog and Digital	
Mounting TypeSurface MountPackage / Case42-WFBGA, WLCSPSupplier Device Package42-WLCSP	Voltage - Supply	1.71 V ~ 3.6 V	
Package / Case42-WFBGA, WLCSPSupplier Device Package42-WLCSP	Operating Temperature	-40°C ~ 85°C	
Supplier Device Package 42-WLCSP	Mounting Type	Surface Mount	
	Package / Case	42-WFBGA, WLCSP	
Depart among	Supplier Device Package	42-WLCSP	
Report errors?		Report errors?	

WM8953ECS/RV Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

WM8953ECS/RV Payment Methods





If you have any question about WM8953ECS/RV, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com