

www.lemo.com

FVG.0W.302.CLAC35

SUMMARY

Wires

 Low
 2

 High
 0

 Coax
 0

 Triax
 0

Quad 0
Fiber 0
Fluidic 0

Series 0W

Termination type Male solder

IP rating 68

Cable Ø 3.10 - 3.50 mm

Matching parts EVG.0W.302.CLL

Status active

Alternative part



Image is for illustrative purpose only

Download

Request a quote

Catalog

TECHNICAL DETAILS

Mechanics

Shell Style/Model FV*: Straight plug, cable collet

Keying 1 key (alpha=0; Plug: male contacts; Receptacle: female contacts)

Housing Material Brass (chrome plated) shell and collet nut, nickel plated brass latch sleeve and mid pieces

Cable Fixing C35: 3.1 - 3.5 mm

Variant

Weight 19.07 g

Performance

Configuration

Insulator

Rated Current #10 Amps

Specifications

Contact Type: Solder Max. Matings: 5000

Contact Dia.: 0.9 mm (0.035in)

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

Bucket Dia.: 0.8 mm (0.031in)

Max. Solid Conductor: 0.34 mm² (AWG 22) Max. Stranded Conductor: 0.34 mm² (AWG 22)

R (max): 4.8 mOhm


Vtest (contact-contact): 1300 V (AC) 1800 V (DC) Vtest (contact-shell): 1050 V (AC) 1500 V (DC)

Others

Pressure: 30 bars IP Rating: 68

DRAWINGS

Draws





Dimensions

	А	В	L	М	N	S1	S 3
mm.	17.2	8.9	35.5	30.8	13.5	16	8
in.	0,68	0,35	1,40	1,21	0,53	0,63	0,31

RECOMMENDED BY LEMO

Tools

None

Cables

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

002 080	PVC	Grey	
020 240	PTFE	White	=======================================

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.