

Dual N-Channel 30-V (D-S) MOSFET with Schottky Diode

PRODUCT SUMMARY

PRODUCT SUMMARY			
	V _{DS} (V)	R _{DS(on)} (Ω)	I _D (A)
Channel-1	30	0.011 at V _{GS} = 10 V	10
		0.016 at V _{GS} = 4.5 V	8.2
Channel-2		0.0085 at V _{GS} = 10 V	14
		0.0095 at V _{GS} = 4.5 V	13

SCHOTTKY PRODUCT SUMMARY

V_{DS} (V)	V_{SD} (V) Diode Forward Voltage	I_F (A)
30	0.53 V at 3 A	2

FEATURES


- Halogen-free According to IEC 61249-2-21 Definition
- TrenchFET® Power MOSFET
- 100 % R_g Tested
- Compliant to RoHS Directive 2002/95/EC




RoHS
COMPLIANT
HALOGEN
FREE
Available

APPLICATIONS

- DC/DC Converters
 - Game Stations
 - Video Equipment



Ordering Information: Si4310BDY-T1-E3 (Lead (Pb)-free)
Si4310BDY-T1-GE3 (Lead (Pb)-free and Halogen-free)



ABSOLUTE MAXIMUM RATINGS $T_A = 25$ °C, unless otherwise noted

Parameter	Symbol	Channel-1		Channel-2		Unit
		10 s	Steady State	10 s	Steady State	
Drain-Source Voltage	V_{DS}	30				V
Gate-Source Voltage	V_{GS}	± 20		± 20		V
Continuous Drain Current ($T_J = 150$ °C) ^a	I_D	10	7.5	14	9.8	A
		8	6	11	7.8	
Pulsed Drain Current	I_{DM}	40		50		A
Continuous Source Current (Diode Conduction) ^a	I_S	1.8	1.04	2.73	1.33	A
Maximum Power Dissipation ^a	P_D	2	1.14	3.0	1.47	W
		1.28	0.73	1.9	0.94	
Operating Junction and Storage Temperature Range	T_J, T_{stg}	- 55 to 150				°C

THERMAL RESISTANCE RATINGS

Parameter	Symbol	Channel-1		Channel-2		Schottky		Unit
		Typ.	Max.	Typ.	Max.	Typ.	Max.	
Maximum Junction-to-Ambient ^a	R_{thJA}	53	62.5	34	35	40	48	°C/W
		92	110	70	72	76	93	
Maximum Junction-to-Foot (Drain)	R_{thJF}	35	42	17	24	21	26	°C/W

Notes:

a. Surface Mounted on 1" x 1" FR4 board.

MOSFET SPECIFICATIONS T _J = 25 °C, unless otherwise noted								
Parameter	Symbol	Test Conditions		Min.	Typ. ^a	Max.	Unit	
Static								
Gate Threshold Voltage	V _{GS(th)}	V _{DS} = V _{GS} , I _D = 250 μA	Ch-1	1.0		3.0	V	
			Ch-2	1.0		3.0		
Gate-Body Leakage	I _{GSS}	V _{DS} = 0 V, V _{GS} = ± 20 V	Ch-1			100	nA	
			Ch-2			100		
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} = 30 V, V _{GS} = 0 V	Ch-1			1	μA	
			Ch-2			100		
		V _{DS} = 30 V, V _{GS} = 0 V, T _J = 85 °C	Ch-1			15		
			Ch-2			4000		
On-State Drain Current ^b	I _{D(on)}	V _{DS} = 5 V, V _{GS} = 10 V	Ch-1	20			A	
			Ch-2	30				
Drain-Source On-State Resistance ^b	R _{DS(on)}	V _{GS} = 10 V, I _D = 10 A	Ch-1		0.009	0.011	Ω	
		V _{GS} = 10 V, I _D = 14 A	Ch-2		0.0065	0.0085		
		V _{GS} = 4.5 V, I _D = 8.2 A	Ch-1		0.013	0.016		
		V _{GS} = 4.5 V, I _D = 13 A	Ch-2		0.0075	0.0095		
Forward Transconductance ^b	g _{fs}	V _{DS} = 15 V, I _D = 10 A	Ch-1		30		S	
		V _{DS} = 15 V, I _D = 14 A	Ch-2		60			
Diode Forward Voltage ^b	V _{SD}	I _S = 1.8 V, V _{GS} = 0 V	Ch-1		0.76	1.1	V	
		I _S = 2.73 V, V _{GS} = 0 V	Ch-2		0.485	0.53		
Dynamic ^a								
Input Capacitance	C _{iss}	V _{DS} = 15 V, V _{GS} = 0 V, f = 1 MHz	Ch-1	790	1580	2370	pF	
			Ch-2	1530	3060	4590		
Output Capacitance	C _{oss}		Ch-1	145	290	435		
			Ch-2	300	600	900		
Reverse Transfer Capacitance	C _{rss}		Ch-1	70	140	210		
			Ch-2	115	225	340		
Total Gate Charge	Q _g	Channel-1	Ch-1		12	18	nC	
		V _{DS} = 15 V, V _{GS} = 4.5 V, I _D = 10 A	Ch-2		19	30		
Gate-Source Charge	Q _{gs}		Channel-1	Ch-1		5.3		
		Channel-2	Ch-2		10			
Gate-Drain Charge	Q _{gd}	V _{DS} = 15 V, V _{GS} = 4.5 V, I _D = 14 A	Ch-1		4.3			
			Ch-2		5			
Gate Resistance	R _g	f = 1 MHz	Ch-1	0.90	1.8	2.7	Ω	
			Ch-2	0.3	0.95	1.4		
Turn-On Delay Time	t _{d(on)}	Channel-1 V _{DD} = 15 V, R _L = 15 Ω I _D ≅ 1 A, V _{GEN} = 10 V, R _g = 6 Ω	Ch-1		13	20	ns	
			Ch-2		17	26		
Rise Time	t _r		Ch-1		10	15		
			Ch-2		12	20		
Turn-Off Delay Time	t _{d(off)}		Channel-2 V _{DD} = 15 V, R _L = 15 Ω I _D ≅ 1 A, V _{GEN} = 10 V, R _g = 6 Ω	Ch-1		33		50
			Ch-2		53	80		
Fall Time	t _f	Ch-1		10	15			
		Ch-2		17	26			
Source-Drain Reverse Recovery Time	t _{rr}	I _F = 1.8 A, dI/dt = 100 A/μs	Ch-1		25	40		
		I _F = 2.73 V, dI/dt = 100 A/μs	Ch-2		31	50		

Notes:

a. Guaranteed by design, not subject to production testing.


b. Pulse test; pulse width $\leq 300\ \mu\text{s}$, duty cycle $\leq 2\ \%$.




SCHOTTKY SPECIFICATIONS $T_J = 25\text{ }^{\circ}\text{C}$, unless otherwise noted						
Parameter	Symbol	Test Conditions	Min.	Typ.	Max.	Unit
Forward voltage Drop	V_F	$I_F = 3\text{ A}$		0.485	0.53	V
		$I_F = 3\text{ A}$, $T_J = 125\text{ }^{\circ}\text{C}$		0.42	0.42	
Maximum Reverse Leakage Current	I_{rm}	$V_R = 30\text{ V}$		0.008	0.100	mA
		$V_R = 30\text{ V}$, $T_J = 75\text{ }^{\circ}\text{C}$		0.4	5	
		$V_R = 30\text{ V}$, $T_J = 125\text{ }^{\circ}\text{C}$		0.5	20	
Junction Capacitance	C_T	$V_R = 15\text{ V}$		102		pF

Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.


CHANNEL-1 TYPICAL CHARACTERISTICS $25\text{ }^{\circ}\text{C}$, unless otherwise noted




Output Characteristics









Transfer Characteristics






On-Resistance vs. Drain Current









Capacitance


CHANNEL-1 TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted

CHANNEL-1 TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted




CHANNEL-2 TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted**Output Characteristics****Transfer Characteristics****On-Resistance vs. Drain Current****Capacitance****Gate Charge****On-Resistance vs. Junction Temperature**


CHANNEL-2 TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted




Source-Drain Diode Forward Voltage




On-Resistance vs. Gate-to-Source Voltage



Reverse Current vs. Junction Temperature







Single Pulse Power






* $V_{GS} >$ minimum V_{GS} at which $R_{DS(on)}$ is specified

Safe Operating Area, Junction-to-Case

CHANNEL-2 TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted**SCHOTTKY TYPICAL CHARACTERISTICS** 25 °C, unless otherwise noted

SCHOTTKY TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted



Vishay Siliconix maintains worldwide manufacturing capability. Products may be manufactured at one of several qualified locations. Reliability data for Silicon Technology and Package Reliability represent a composite of all qualified locations. For related documents such as package/tape drawings, part marking, and reliability data, see www.vishay.com/ppg?73064.



Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.