

LQH3NPN220NG0#


"#" indicates a package specification code.



Last Time Buy Date: 31 Mar 2018 Date of discontinuation: 30 Sep 2018

< List of part numbers with package codes >
LQH3NPN220NG0L , LQH3NPN220NG0K

Shape



Notes

When rated current is applied to the products, inductance will be within $\pm 30\%$ of nominal inductance value.
When rated current is applied to the products, the temperature rise caused by self-generated heat shall be limited to 40 °C max.
Keep the temperature (ambient temperature plus self-generation of heat) under 125 °C.

References

Packaging code	Specifications	Minimum quantity
L	φ180mm Embossed taping	1500
K	φ330mm Embossed taping	6000

Mass (Typ.)	
1 piece	0.034g





Specifications

Inductance	22μH $\pm 30\%$
Inductance test frequency	1MHz
Rated current (I _{sat}) (Based on Inductance change)	340mA
Rated current (I _{temp}) (Based on Temperature rise)	430mA
Max. of DC resistance	1.32Ω
Avg. of DC resistance	1.1Ω $\pm 20\%$
Self resonance frequency (min.)	25MHz
Operating temperature range (Self-temperature rise is not included)	-40 °C to 85 °C
Class of magnetic shield	Magnetic Resin
Series	LQH3NPN_G0

1 of 2

Attention

- 1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
 - 2.This datasheet has only typical specifications because there is no space for detailed specifications.
- Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



Attention

- 1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2.This datasheet has only typical specifications because there is no space for detailed specifications.
Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.