

FGG.2B.514.CYCD62

SUMMARY

Wires

| Low | 8 | | |
|------------------|----------------|--|--|
| High | 0 | | |
| Coax | 0 | | |
| Triax | 0 | | |
| Quad | 0 | | |
| Fiber | 0 | | |
| Fluidic | 0 | | |
| | | | |
| Series | 2B | | |
| Termination type | Male crimp | | |
| IP rating | 50 | | |
| Cable Ø | 5.30 - 6.20 mm | | |
| Matching parts | EGG.2B.514.CYM | | |
| Status | active | | |
| Alternative part | | | |



Image is for illustrative purpose only

Download

Request a quote Catalog

TECHNICAL DETAILS

Mechanics

| Shell Style/Model | FG*: Straight plug, cable collet | | | |
|-------------------|---|--|--|--|
| Keying | 1 key (alpha=0, plug: male contacts, receptacle: female contacts) | | | |
| Housing Material | Brass (chrome plated) shell and collet nut, nickel plated brass latch sleeve and mid pieces | | | |
| Cable Fixing | D62: 5.3 - 6.2 mm | | | |
| Variant | | | | |
| Weight | 30.49 g | | | |
| Performance | | | | |
| Configuration | 2B.514: 8 high speed (CAT 6A) | | | |
| Insulator | Y: PEEK for crimp contacts | | | |
| Rated Current | | | | |


Others

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

Temp (min / max): -55°C / +250°C Humidity (max): <=95% [at 60 deg C /140 F] Vibration: 15 g [10 Hz - 2000 Hz] Shock Resistance: 100 g [6 ms] Salt Spray Corrosion: >1000 hr Climatical Category: 50/175/21 Shielding (min): 75 dB (10 MHz) Shielding (min): 40 dB (1 GHz) IP Rating: 50

DRAWINGS

Draws



Dimensions

| | А | L | м | S1 | S2 |
|-----|------|------|------|------|------|
| mm. | 15 | 50 | 38 | 13 | 12 |
| in. | 0,59 | 1,97 | 1,50 | 0,51 | 0,47 |

RECOMMENDED BY LEMO

Tools

Spanner wrench: DCD.2B.025.PA120 Caps: BFG.2B.100.PCSG

Cables

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.