

FVG.1W.308.CLAC65

SUMMARY

Wires

Low	8	
High	0	
Coax	0	
Triax	0	Download
Quad	0	Request a
Fiber	0	Catalog
Fluidic	0	
Series	1W	
Termination type	Male solder	
IP rating	68	
Cable Ø	6.10 - 6.50 mm	
Matching parts	EVG.1W.308.CLL	
Status	active	
Alternative part		
	High Coax Triax Quad Fiber Fluidic Series Termination type IP rating Cable Ø Matching parts Status	High0Coax0Triax0Quad0Fiber0Fluidic0Series1WTermination typeMale solderIP rating68Cable Ø6.10 - 6.50 mmMatching partsEVG.1W.308.CLLLStatusactive

Image is for illustrative purpose only

uest a quote alog

TECHNICAL DETAILS

Mechanics

Shell Style/Model	FV*: Straight plug, cable collet		
Keying	1 key (alpha=0; Plug: male contacts; Receptacle: female contacts)		
Housing Material	Brass (chrome plated) shell and collet nut, nickel plated brass latch sleeve and mid pieces		
Cable Fixing	C65: 6.1 - 6.5 mm		
Variant			
Weight	29.71 g		
Performance			

Configuration Insulator **Rated Current** 5 Amps

Specifications

Contact Type: Solder Max. Matings: 5000 Contact Dia.: 0.7 mm (0.028in)

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.


Bucket Dia.: 0.8 mm (0.031in) Max. Stranded Conductor: 0.34 mm^2 (AWG 22) Max. Conductor: 0.34 mm^2 (AWG 22) R (max): 6.1 mOhm Vtest (contact-contact): 950 V (AC) 1300 V (DC) Vtest (contact-shell): 1150 V (AC) 1600 V (DC)

Others

Pressure: 30 bars IP Rating: 68

DRAWINGS

Draws





Dimensions

	А	В	L	Μ	Ν	S1	\$3
mm.	19.3	11.0	43.7	35.5	14.0	18	9
in.	0,76	0,43	1,72	1,40	0,55	0,71	0,35

RECOMMENDED BY LEMO

Tools

None

Cables

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

180 240	PVC	Black	
280 250	PVC	Grey	>
335 990	PVC	Black	3
335 991	PVC	Black	36

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.