muRata Capacitor Data Sheet RCER72A334K1A2H03B "#" indicates a package specification code.					
In Production Power- train Q200 C max. Low acoustic noise Crack	Soldering crack Flow OK Welding Re	DHS REACH			
< List of part numbers with package codes > RCER72A334K1A2H03B					
Shape		Note	25		
		Meet LF(Lead Free)[*LF : Lead content is less than 1000 ppm.], HF(Halogen Free)			
		References			
€ 8 8 8 9 0.5±0.05		Packaging	Specifications	Minimum quantity	
<u>F±0.8</u>		В	Packing in bulk	500	
Lead Wire : Solder Coated Copper Wire or Solder Coated CP Wire (in mm)					
L size or outer diameter D (mm)	4.0 mm max.				
W size	3.5 mm max.				
T size	2.5 mm max.				
Lead spacing F	2.5 ±0.8mm				

Specifications

Lead diameter d

Capacitance	0.33μF ±10%
Rated voltage	100Vdc
Temperature characteristics (complied standard)	X7R(EIA)
Capacitance change rate	±15%
Temperature range of temperature characteristics	-55 to 125°C
Operating temperature range	-55 to 125°C

0.5 ±0.05mm

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications. Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



ty