



Is Now Part of



**ON Semiconductor®**

To learn more about ON Semiconductor, please visit our website at  
[www.onsemi.com](http://www.onsemi.com)

Please note: As part of the Fairchild Semiconductor integration, some of the Fairchild orderable part numbers will need to change in order to meet ON Semiconductor's system requirements. Since the ON Semiconductor product management systems do not have the ability to manage part nomenclature that utilizes an underscore (\_), the underscore (\_) in the Fairchild part numbers will be changed to a dash (-). This document may contain device numbers with an underscore (\_). Please check the ON Semiconductor website to verify the updated device numbers. The most current and up-to-date ordering information can be found at [www.onsemi.com](http://www.onsemi.com). Please email any questions regarding the system integration to [Fairchild\\_questions@onsemi.com](mailto:Fairchild_questions@onsemi.com).

ON Semiconductor and the ON Semiconductor logo are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at [www.onsemi.com/site/pdf/Patent-Marking.pdf](http://www.onsemi.com/site/pdf/Patent-Marking.pdf). ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that ON Semiconductor was negligent regarding the design or manufacture of the part. ON Semiconductor is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

# FAN7535

## PFC & Ballast Control IC

### Features

- PFC, Ballast Control, and Half-Bridge Driver in One IC
- PFC Driver Current Capability: +500mA/-800mA
- Critical Conduction Mode Control Type PFC
- Internal Clamping Zener Diode (PFC): 23V
- Under-Voltage Lockout with 3.5V of Hysteresis (PFC)
- Internal Clamping Zener Diode (Ballast): 15V
- Lower di/dt Gate Driver for Better Noise Immunity
- Under-Voltage Lockout with 1.8V Hysteresis (Ballast)
- Ballast Driver Current Capability: +350mA/-650mA
- Programmable Preheat Time & Frequency
- Programmable Run Frequency
- Programmable Ignition Sweep Time
- Internal Active ZVS Control
- Internal Protection Function (Latch Mode)

### Applications

- Fluorescent Lamp Ballast

### Description

FAN7535 provides simple, high-performance, active power factor correction (PFC), and ballast control. The FAN7535 is optimized for all kinds of fluorescent lamps, which require minimum board area and reduced external components. The FAN7535 PFC control block to reduce the input current THD lower than conventional CRM boost PFC methods. An innovative Active Zero Voltage Switching (AZVS) block reduces the switching power loss. A dedicated timing section in the FAN7535 allows the user set the necessary parameters for proper lamp preheat and ignition.

24-SOP



### Ordering Information

Part Number	Package	Operating Temperature Range	Packing Method
FAN7535M	24-SOP	-25°C ~ 125°C	Tube
FAN7535MX			Tape & Reel



All packages are lead free per JEDEC: J-STD-020B standard.

## Typical Application Diagrams




Figure 1. Typical Application Circuit for Fluorescent Lamp

# Internal Block Diagram




Figure 2. Functional Block Diagram (2chips-1PKG)

## Pin Configuration




Figure 3. Pin Configuration (Top View)

## Pin Definitions

Pin #	Name	Description
1	VDDDB	Supply voltage for ballast part
2	NC	No connection
3	RT	Oscillator frequency set resistor
4	NC	No connection
5	CPH	Preheating time set capacitor
6	GND	Ground for ballast part & PFC part
7	INV	Inverting input of the error amplifier
8	COMP	Output of the transconductance error amplifier
9	NC	No connection
10	MOT	Set the slope of the internal ramp
11	NC	No connection
12	CS	Input of the over-current protection comparator
13	ZCD	Input of the zero current detection block
14	NC	No connection
15	NC	No connection
16	OUT	Gate driver output
17	VDDP	Supply voltage for PFC block
18	LO	Low-side output
19	NC	No connection
20	VS	High-side floating supply return
21	NC	No connection
22	HO	High-side output
23	NC	No connection
24	VB	High-side floating supply

## Absolute Maximum Ratings

Stresses exceeding the absolute maximum ratings may damage the device. The device may not function or be operable above the recommended operating conditions and stressing the parts to these levels is not recommended. In addition, extended exposure to stresses above the recommended operating conditions may affect device reliability.

The absolute maximum ratings are stress ratings only.  $T_A=25^{\circ}\text{C}$ , unless otherwise specified.

Symbol	Parameter	Min.	Typ.	Max.	Unit
<b>PFC PART</b>					
$V_{DDP}$	Supply Voltage		$V_Z$		V
$I_{OH}, I_{OL}$	Peak Drive Output Current	-800		+500	mA
$I_{CLAMP}$	Driver Output Clamping Diodes $V_O > V_{CC}$ or $V_O < -0.3V$		$\pm 10$		
$I_{DET}$	Detector Clamping Diodes		$\pm 10$		
$V_{IN}$	Error Amplifier, MOT, CS Input Voltages	-0.3		6.0	V
<b>BALLAST PART</b>					
$V_B$	High-side Floating Supply	-0.3		625.0	V
$V_S$	High-side floating supply return	-0.3		600.0	
$V_{IN}$	RT, CPH Pins Input Voltage	-0.3		8.0	
$V_{CL}$	Clamping Voltage		$V_{CL}$		mA
$I_{CL}$	Clamping Current Level		25		
$dV_S/dt$	Allowable Offset Voltage Slew Rate			50	V/ns
<b>Common</b>					
$T_{OPR}$	Operating Temperature Range	-25		+125	$^{\circ}\text{C}$
$T_{STG}$	Storage Temperature Range	-65		+150	
$P_D$	Total Power Dissipation		1.5		W
$\theta_{JA}$	Thermal Resistance (Junction-to-Air)			83	$^{\circ}\text{C/W}$

### Caution:

Do not supply a low-impedance voltage source to the internal clamping Zener diode between the GND and the VDDDB and VDDP pins of this device. Use a common supply between the two ICs (PFC, Ballast) only under careful attention.

## Electrical Characteristics

$V_{DDP}=14V$ ,  $T_A = 25^{\circ}C$ , unless otherwise specified.

Symbol	Characteristics	Test Condition	Min.	Typ.	Max.	Unit
PFC PART <sup>(1)</sup>						
UNDER-VOLTAGE LOCKOUT SECTION						
V <sub>th(start)</sub>	Start Threshold Voltage	V <sub>DDP</sub> Increasing	11	12	13	V
V <sub>th(stop)</sub>	Stop Threshold Voltage	V <sub>DDP</sub> Decreasing	7.5	8.5	9.5	
H <sub>Y(UVLO)</sub>	UVLO Hysteresis		3.0	3.5	4.0	
V <sub>z</sub>	Zener Voltage	I <sub>DDP</sub> = 20mA	20	22	24	
SUPPLY CURRENT SECTION						
I <sub>st</sub>	Start-up Supply Current	V <sub>DDP</sub> = V <sub>TH(START)</sub> -0.2V		40	70	mA
I <sub>DDP</sub>	Operating Supply Current	Output not switching		1.5	3.0	mA
I <sub>DDP(dyn)</sub>	Dynamic Operating Supply Current	50kHz, C <sub>L</sub> = 1nF		2.5	4.0	
I <sub>DD(dis)</sub>	Operating Current at Disable	V <sub>INV</sub> = 0V	20	65	95	mA
ERROR AMPLIFIER SECTION						
V <sub>ref1</sub>	Voltage Feedback Input Threshold1	T <sub>A</sub> = 25°C	2.465	2.500	2.535	V
DV <sub>ref1</sub>	Line Regulation	14V ≤ V <sub>DDP</sub> ≤ 20V		0.1	10.0	mV
DV <sub>ref3</sub> <sup>(1)</sup>	Temperature Stability of V <sub>REF</sub>			20		
I <sub>b(ea)</sub>	Input Bias Current	1V ≤ V <sub>inv</sub> ≤ 4V	-0.5		0.5	mA
I <sub>source</sub>	Output Source Current	V <sub>inv</sub> = V <sub>ref1</sub> -0.1V		-12		
I <sub>sink</sub>	Output Sink Current	V <sub>inv</sub> = V <sub>ref1</sub> +0.1V		12		
V <sub>eao(H)</sub>	Output Upper Clamp Voltage	V <sub>inv</sub> = V <sub>ref1</sub> -0.1V	5.4	6.0	6.6	V
V <sub>eao(Z)</sub>	Zero Duty Cycle Output Voltage		0.9	1.0	1.1	
g <sub>m</sub> <sup>(2)</sup>	Transconductance		90	115	140	μmho
MAXIMUM ON-TIME SECTION						
V <sub>MOT</sub>	Maximum On-Time Voltage	R <sub>MOT</sub> = 40.5Ω	2.784	2.900	3.016	V
T <sub>ON-MAX</sub>	Maximum On-Time Programming	R <sub>MOT</sub> = 40.5Ω,T <sub>A</sub> = 25°C	19	24	29	μs
CURRENT-SENSE SECTION						
V <sub>CS(LIMIT)</sub>	Current Sense Input Threshold Voltage Limit		0.7	0.8	0.9	V
I <sub>b(cs)</sub>	Input Bias Current	0V ≤ V <sub>CS</sub> ≤ 1V	-1.0	-0.1	1.0	mA
T <sub>d(cs)</sub> <sup>(1)</sup>	Current Sense Delay to Output			350	500	ns

### Notes:

1. Please refer to the FAN7529 datasheet and AN-6026 application note for more detailed information. Available on Fairchild's website at:

[Datasheet: http://www.fairchildsemi.com/ds/FA%2FFAN7529.pdf](http://www.fairchildsemi.com/ds/FA%2FFAN7529.pdf)

[Application Note: http://www.fairchildsemi.com/an/AN/AN-6026.pdf](http://www.fairchildsemi.com/an/AN/AN-6026.pdf)

2. This parameter, although guaranteed, is not 100% tested in production.

**Electrical Characteristics** (Continued)V<sub>DDP</sub> = 14V, T<sub>A</sub> = 25°C, unless otherwise specified.

Symbol	Characteristics	Test Condition	Min.	Typ.	Max.	Unit
ZERO CURRENT DETECT SECTION						
V <sub>th(ZCD)</sub> <sup>(3)</sup>	Input Voltage Threshold		1.35	1.50	1.65	V
HY <sub>(ZCD)</sub> <sup>(3)</sup>	Detect Hysteresis		0.05	0.10	0.15	
V <sub>clamp(h)</sub>	Input High Clamp Voltage	I <sub>DET</sub> = 3mA	6.0	6.7	7.4	
V <sub>clamp(l)</sub>	Input Low Clamp Voltage	I <sub>DET</sub> = -3mA	0	0.65	1.00	
I <sub>b(ZCD)</sub>	Input Bias Current	1V ≤ V <sub>ZCD</sub> ≤ 5V	-1.0	-0.1	1.0	mA
I <sub>source(ZCD)</sub> <sup>(3)</sup>	Source Current Capability	T <sub>A</sub> = 25°C			-10	mA
I <sub>sink(ZCD)</sub> <sup>(3)</sup>	Sink Current Capability	T <sub>A</sub> = 25°C			10	
T <sub>DEAD</sub> <sup>(3)</sup>	Maximum Delay, ZCD to Output Turn-on		100		200	
OUTPUT SECTION						
V <sub>oh</sub>	Output Voltage High	I <sub>O</sub> = -100mA, T <sub>A</sub> = 25°C	9.2	11.0	12.8	V
V <sub>ol</sub>	Output Voltage Low	I <sub>O</sub> = 100mA, T <sub>A</sub> = 25°C		1.0	2.5	
T <sub>r</sub> <sup>(3)</sup>	Rising Time	C <sub>I</sub> = 1nF		50	100	ns
T <sub>f</sub> <sup>(3)</sup>	Falling Time	C <sub>I</sub> = 1nF		50	100	
V <sub>O(MAX)</sub>	Maximum Output Voltage	V <sub>DDP</sub> = 20V, I <sub>O</sub> = 100mA	11.5	13.0	14.5	V
V <sub>O(UVLO)</sub>	Output Voltage with UVLO Activated	V <sub>DDP</sub> = 5V, I <sub>O</sub> = 100mA			1	
RESTART TIMER SECTION						
t <sub>d(rst)</sub>	Restart Time Delay		50	150	300	ms
OVER-VOLTAGE PROTECTION SECTION						
V <sub>OVP</sub>	OVP Threshold Voltage	T <sub>A</sub> = 25°C	2.620	2.675	2.730	V
HY <sub>(OVP)</sub>	OVP Hysteresis	T <sub>A</sub> = 25°C	0.120	0.175	0.230	
ENABLE SECTION						
V <sub>th(en)</sub>	Enable Threshold Voltage		0.40	0.45	0.50	V
HY <sub>(en)</sub>	Enable Hysteresis		0.05	0.10	0.15	

**Note:**

3. These parameters, although guaranteed, are not 100% tested in production.

**Electrical Characteristics** (Continued)

$V_{BIAS}$  ( $V_{DDB}$ ,  $V_{BS}$ ) = 14.0V,  $T_A$  = 25°C, unless otherwise specified.

Symbol	Characteristics	Condition	Min.	Typ.	Max.	Unit
<b>BALLAST PART<sup>(4)</sup></b>						
<b>Supply Voltage Section</b>						
$V_{DDTH(ST+)}$	$V_{DDB}$ UVLO Positive Going Threshold	$V_{DDB}$ Increasing	12.4	13.4	14.4	V
$V_{DDTH(ST-)}$	$V_{DDB}$ UVLO Negative Going Threshold	$V_{DDB}$ Decreasing	10.8	11.6	12.4	
$V_{DDHY(ST)}$	$V_{DDB}$ -side UVLO Hysteresis			1.8		
$V_{CL}$	Supply Clamping Voltage	$I_{DDB} = 10\text{mA}$	14.8	15.2		
$I_{ST}$	Start-up Supply Current	$V_{DDB} = 12\text{V}$		150		$\mu\text{A}$
$I_{DDB(dyn)}$	Dynamic Operating Supply Current	50kHz, $C_L = 1\text{nF}$		3.2		mA
<b>High-Side Supply Section (<math>V_B</math>-<math>V_S</math>)</b>						
$V_{HSTH(ST+)}$	High-side UVLO Positive Going Threshold	$V_{BS}$ Increasing	8.5	9.2	10.0	V
$V_{HSTH(ST-)}$	High-side UVLO Negative Going Threshold	$V_{BS}$ Decreasing	7.9	8.6	9.5	
$V_{HSHY(ST)}$	High-side UVLO Hysteresis			0.6		
$I_{HST}$	High-side Quiescent Supply Current	$V_{BS} = 14\text{V}$		50		$\mu\text{A}$
$I_{HD}$	High-side Dynamic Operating Supply Current	50kHz, $C_L = 1\text{nF}$		1		mA
$I_{LK}$	Offset Supply Leakage Current	$V_B = V_S = 600\text{V}$			45	$\mu\text{A}$
<b>Oscillator Section</b>						
$V_{MPH}$	CPH Pin Preheating Voltage Range		2.5	3.0	3.5	V
$I_{PH}$	CPH Pin Charging Current During Preheating	$V_{CPH} = 1\text{V}$	1.25	2.00	2.85	$\mu\text{A}$
$I_{IG}$	CPH Pin Charging Current During Ignition	$V_{CPH} = 4\text{V}$	8	12	16	
$V_{MO}$	CPH Pin Voltage Level at Running Mode			7.0		V
$f_{PRE}$	Preheating Frequency	$R_T = 80\text{k}\Omega$ , $V_{CPH} = 2\text{V}$	72	85	98	kHz
$f_{OSC}$	Running Frequency	$R_T = 80\text{k}\Omega$	48.2	53.0	57.8	kHz
$DT_{MAX}$	Maximum Dead Time	$V_{CPH} = 1\text{V}$ , $V_S = \text{GND}$ in Preheat Mode		3.1		$\mu\text{s}$
$DT_{MIN}$	Minimum Dead Time	$V_{CPH} = 6\text{V}$ , $V_S = \text{GND}$ in Run Mode		1.0		$\mu\text{s}$
<b>Output Section</b>						
$I_{OH+}$	High-side Driver Sourcing Current	$PW = 10\mu\text{s}$	250	350		mA
$I_{OH-}$	High-side Driver Sinking Current	$PW = 10\mu\text{s}$	500	650		
$I_{OL+}$	Low-side Driver Sourcing Current	$PW = 10\mu\text{s}$	250	350		
$I_{OL-}$	Low-side Driver Sink Current	$PW = 10\mu\text{s}$	500	650		
$t_{HOR}$	High-side Driver Turn-on Rising Time	$C_L = 1\text{nF}$ , $V_{BS} = 15\text{V}$		45		ns
$t_{HOL}$	High-side Driver Turn-off Rising Time	$C_L = 1\text{nF}$ , $V_{BS} = 15\text{V}$		25		
$t_{LOR}$	Low-side Driver Turn-on Rising Time	$C_L = 1\text{nF}$ , $V_{BS} = 15\text{V}$		45		
$t_{LOL}$	Low-side Driver Turn-off Rising Time	$C_L = 1\text{nF}$ , $V_{BS} = 15\text{V}$		25		
$V_S^{(5)}$	Maximum Negative $V_S$ Swing Range for Signal Propagation to High-side Output			-9.8		V

**Electrical Characteristics** (Continued)

$V_{BIAS}$  ( $V_{DDB}$ ,  $V_{BS}$ ) = 14.0V,  $T_A$  = 25°C, unless otherwise specified.

Symbol	Characteristics	Condition	Min.	Typ.	Max.	Unit
<b>Protection Section</b>						
$V_{CPHSD}$	Shutdown Voltage	$V_{RT} = 0$ After Run Mode	2.6			V
$I_{SD}$	Shutdown Current			250	450	$\mu$ A
$TSD^{(5)}$	Thermal Shutdown			165		°C

**Notes:**

4. Please refer to the FAN7711 datasheet for more detailed information. Available on Fairchild's website at:


[Datasheet: http://www.fairchildsemi.com/ds/FA%2FFAN7711.pdf](http://www.fairchildsemi.com/ds/FA%2FFAN7711.pdf)

5. This parameter, although guaranteed, is not 100% tested in production.

## Component List for 32W Two Lamps

Part	Value	Note	Part	Value	Note
<b>Resistor</b>			C55	15nF/630V	Miller Capacitor
R1	330k $\Omega$	1/2W	C56	2.7nF/1kV	Miller Capacitor
R2	750k $\Omega$	1/4W	C57	15nF/630V	Miller Capacitor
R3	100 $\Omega$	1/2W	C58	2.7nF/1kV	Miller Capacitor
R4	20k $\Omega$	1/4W	<b>Diode</b>		
R5	47 $\Omega$	1/4W	D1	1N4007	1kV,1A
R6	10k $\Omega$	1/4W	D2	1N4007	1kV,1A
R7	50k $\Omega$	1/4W	D3	1N4007	1kV,1A
R8	47k $\Omega$	1/4W	D4	1N4007	1kV,1A
R9	0.3 $\Omega$	1W	D5	UF4007	Ultra Fast,1kV,1A
R10	1M $\Omega$	1/4W	D6	UF4007	Ultra Fast,1kV,1A
R11	1M $\Omega$	1/4W	D7	1N4148	100V,1A
R12	12.6k $\Omega$	1/4W,1%	D8	1N4148	100V,1A
R13	220k $\Omega$	2W	D50	UF4007	Ultra Fast,1kV,1A
R50	150k $\Omega$	1/4W	D51	UF4007	Ultra Fast,1kV,1A
R51	150k $\Omega$	1/4W	D52	UF4007	Ultra Fast,1kV,1A
R52	150k $\Omega$	1/4W	ZD1	1N4746A	Zener 18V, 1W
R53	90k $\Omega$	1/4W,1%	<b>MOSFET</b>		
R54	10 $\Omega$	1/4W	M1	FQPF5N60C	500V,6A
R55	47 $\Omega$	1/4W	M2	FQPF5N50C	500V,5A
R56	47k $\Omega$	1/4W	M3	FQPF5N50C	500V,5A
R57	47 $\Omega$	1/4W	<b>Fuse</b>		
R58	47k $\Omega$	1/4W	Fuse	3A/250V	
<b>Capacitor</b>			<b>TNR</b>		
C1	47nF/275V <sub>AC</sub>	Box Capacitor	TNR	471	
C2	150nF/275V <sub>AC</sub>	Box Capacitor			
C3	2200pF/3kV	Ceramic Capacitor	<b>NTC</b>		
C4	2200pF/3kV	Ceramic Capacitor	NTC	10D-09	
C5	0.22 $\mu$ F/630V	Miller Capacitor	<b>Line Filter</b>		
C6	12nF/50V	Ceramic Capacitor	LF1	40mH	
C7	22 $\mu$ F/50V	Electrolytic Capacitor	<b>Transformer</b>		
C8	39pF/50V	Ceramic Capacitor	L1	0.94mH (75T:10T)	EI2820
C9	1 $\mu$ F/50V	Ceramic Capacitor	<b>Inductor</b>		
C10	0.1 $\mu$ F/50V	Ceramic Capacitor	L2	3.2mH (130T)	EI2820
C11	47 $\mu$ F/450V	Electrolytic Capacitor	L3	3.2mH (130T)	EI2820
C50	10 $\mu$ F/50V	Electrolytic Capacitor	<b>IC</b>		
C51	1 $\mu$ F/50V	Ceramic Capacitor	U1	FAN7535	Fairchild Semiconductor
C52	0.47 $\mu$ F/25V	Ceramic Capacitor, 5%			
C53	100nF/50V	Ceramic Capacitor			
C54	470pF/1kV	Ceramic Capacitor			

## Package Dimensions



M24BREV2

### Figure 4. 24-Lead Small Outline Package (SOP)

*Package drawings are provided as a service to customers considering Fairchild components. Drawings may change in any manner without notice. Please note the revision and/or date on the drawing and contact a Fairchild Semiconductor representative to verify or obtain the most recent revision. Package specifications do not expand the terms of Fairchild's worldwide terms and conditions, specifically the warranty therein, which covers Fairchild products.*

*Always visit Fairchild Semiconductor's online packaging area for the most recent package drawings:*

<http://www.fairchildsemi.com/packaging/>



## TRADEMARKS

The following includes registered and unregistered trademarks and service marks, owned by Fairchild Semiconductor and/or its global subsidiaries, and is not intended to be an exhaustive list of all such trademarks.

ACEX <sup>®</sup>	FPS <sup>™</sup>	PDP-SPM <sup>™</sup>	SyncFET <sup>™</sup>
Build it Now <sup>™</sup>	FRFET <sup>®</sup>	Power220 <sup>®</sup>	 SYSTEM GENERAL <sup>®</sup>
CorePLUS <sup>™</sup>	Global Power Resource <sup>SM</sup>	Power247 <sup>®</sup>	The Power Franchise <sup>®</sup>
CROSSVOLT <sup>™</sup>	Green FPS <sup>™</sup>	POWEREDGE <sup>®</sup>	 the power franchise
CTL <sup>™</sup>	Green FPS <sup>™</sup> e-Series <sup>™</sup>	Power-SPM <sup>™</sup>	TinyBoost <sup>™</sup>
Current Transfer Logic <sup>™</sup>	GTO <sup>™</sup>	PowerTrench <sup>®</sup>	TinyBuck <sup>™</sup>
EcoSPARK <sup>®</sup>	i-Lo <sup>™</sup>	Programmable Active Droop <sup>™</sup>	TinyLogic <sup>®</sup>
EZSWITCH <sup>™</sup> *	IntelliMAX <sup>™</sup>	QFET <sup>®</sup>	TINYOPTO <sup>™</sup>
 <sup>™</sup>	ISOPLANAR <sup>™</sup>	QS <sup>™</sup>	TinyPower <sup>™</sup>
 <sup>®</sup>	MegaBuck <sup>™</sup>	QT Optoelectronics <sup>™</sup>	TinyPWM <sup>™</sup>
Fairchild <sup>®</sup>	MICROCOUPLER <sup>™</sup>	Quiet Series <sup>™</sup>	TinyWire <sup>™</sup>
Fairchild Semiconductor <sup>®</sup>	MicroFET <sup>™</sup>	RapidConfigure <sup>™</sup>	μSerDes <sup>™</sup>
FACT Quiet Series <sup>™</sup>	MicroPak <sup>™</sup>	SMART START <sup>™</sup>	UHC <sup>®</sup>
FACT <sup>®</sup>	MillerDrive <sup>™</sup>	SPM <sup>®</sup>	Ultra FRFET <sup>™</sup>
FAST <sup>®</sup>	Motion-SPM <sup>™</sup>	STEALTH <sup>™</sup>	UniFET <sup>™</sup>
FastvCore <sup>™</sup>	OPTOLOGIC <sup>®</sup>	SuperFET <sup>™</sup>	VCX <sup>™</sup>
FlashWriter <sup>®</sup> *	OPTOPLANAR <sup>®</sup>	SuperSOT <sup>™</sup> 3	
		SuperSOT <sup>™</sup> 6	
		SuperSOT <sup>™</sup> 8	

\* EZSWITCH<sup>™</sup> and FlashWriter<sup>®</sup> are trademarks of System General Corporation, used under license by Fairchild Semiconductor.

## DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION, OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS. THESE SPECIFICATIONS DO NOT EXPAND THE TERMS OF FAIRCHILD'S WORLDWIDE TERMS AND CONDITIONS, SPECIFICALLY THE WARRANTY THEREIN, WHICH COVERS THESE PRODUCTS.

## LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR CORPORATION.

As used herein:


1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury of the user.
2. A critical component in any component of a life support, device, or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

## PRODUCT STATUS DEFINITIONS

### Definition of Terms

Datasheet Identification	Product Status	Definition
Advance Information	Formative or In Design	This datasheet contains the design specifications for product development. Specifications may change in any manner without notice.
Preliminary	First Production	This datasheet contains preliminary data; supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve design.
No Identification Needed	Full Production	This datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve the design.
Obsolete	Not In Production	This datasheet contains specifications on a product that has been discontinued by Fairchild Semiconductor. The datasheet is printed for reference information only.

Rev. I32

ON Semiconductor and  are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at [www.onsemi.com/site/pdf/Patent-Marking.pdf](http://www.onsemi.com/site/pdf/Patent-Marking.pdf). ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that ON Semiconductor was negligent regarding the design or manufacture of the part. ON Semiconductor is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## PUBLICATION ORDERING INFORMATION

### LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor  
19521 E. 32nd Pkwy, Aurora, Colorado 80011 USA  
**Phone:** 303-675-2175 or 800-344-3860 Toll Free USA/Canada  
**Fax:** 303-675-2176 or 800-344-3867 Toll Free USA/Canada  
**Email:** [orderlit@onsemi.com](mailto:orderlit@onsemi.com)

**N. American Technical Support:** 800-282-9855 Toll Free  
USA/Canada

**Europe, Middle East and Africa Technical Support:**  
Phone: 421 33 790 2910

**Japan Customer Focus Center**  
Phone: 81-3-5817-1050

**ON Semiconductor Website:** [www.onsemi.com](http://www.onsemi.com)

**Order Literature:** <http://www.onsemi.com/orderlit>

For additional information, please contact your local  
Sales Representative