

www.lemo.com

FFR.3Y.425.CFAE55R

SUMMARY

Wires

 Low
 0

 High
 0

 Coax
 0

Triax 0

Quad 0

Fiber 0

Fluidic 0

Series 3Y

Termination type Male solder High-Voltage

IP rating 50

Cable Ø 0.00 - 6.00 mm

Matching parts ERA.3Y.425.CLL

Status active

Alternative part



Image is for illustrative purpose only

Download

Request a quote

Catalog

TECHNICAL DETAILS

Mechanics

Shell Style/Model FFR*: Straight plug for cable crimping with bend relief and safety locking ring

Keying Circular (can rotate)

Housing Material Brass (chrome plated) shell and collet nut, nickel plated brass latch sleeve and mid pieces

Cable Fixing : 0 - 6 mm

Variant

Weight 97.45 g

Performance

Configuration 3Y.425 : 1 High Voltage
Insulator F: Silicon (LSR)/ Y series

Rated Current 8 Amps

Specifications

Contact Type: Solder Test voltage (kV DC) 52 Test voltage (kV AC) 37

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.


Creepage dist. (mm): 25.5

Others

IP Rating: 50

DRAWINGS

Draws







Dimensions

	А	L	М	S1
mm.	19	120	92	15
in.	0,75	4,72	3,62	0,59

RECOMMENDED BY LEMO

Tools

None

Cables

120 222		
121 221		
130 222		

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

131 221 151 221	-	
161 221		

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.