

# FFA.1Y.405.CTLC52

# SUMMARY

#### # Wires

		and the second sec
Low	0	
High	1	
Coax	0	
Triax	0	Download
Quad	0	Request a quote
Fiber	0	Catalog
Fluidic	0	<u> </u>
Series	1Y	
Termination type	Female solder High-Voltage	
IP rating	50	
Cable Ø	4.20 - 5.20 mm	
Matching parts	ERA.1Y.405.CTA	
Status	active	
Alternative part		

Image is for illustrative purpose only

## **TECHNICAL DETAILS**

#### Mechanics

Shell Style/I	Nodel	FFA*: Straight plug with cable collet
Keying		Circular (can rotate)
Housing Mat	erial	Brass (chrome plated) shell and collet nut, nickel plated brass latch sleeve and mid pieces
Cable Fixing	B	C52: 4.2 - 5.2 mm
Variant		
Weight		36.01 g
Performance	5	
Configuratio	on	
Insulator		T: PTFE
Rated Curre	ent	8 Amps

#### Specifications

Contact Type: Solder Test voltage (kV DC) 10.5 Test voltage (kV AC) 7.5

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.


Creepage dist. (mm): 16

#### Others

IP Rating: 50

### **DRAWINGS**

Draws



#### Dimensions

	А	L	м	S1
mm.	13	67	30.5	9
in.	0,51	2,64	1,20	0,35

### **RECOMMENDED BY LEMO**

Tools

None

#### Cables

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.