

www.lemo.com

FVG.2W.306.CLAC15

SUMMARY

Wires

 Low
 6

 High
 0

 Coax
 0

 Triax
 0

 Quad
 0

 Fiber
 0

Fluidic 0

Series 2W

Termination type Male solder

IP rating 68

Cable Ø 1.30 - 1.50 mm

Matching parts EVG.2W.306.CLL

Status active

Alternative part



Image is for illustrative purpose only

Download

Request a quote

Catalog

TECHNICAL DETAILS

Mechanics

Shell Style/Model FV*: Straight plug, cable collet

Keying 1 key (alpha=0; Plug: male contacts; Receptacle: female contacts)

Housing Material Brass (chrome plated) shell and collet nut, nickel plated brass latch sleeve and mid pieces

Cable Fixing C15: 1.3 - 1.5 mm

Variant

Weight 54.80 g

Performance

Configuration

Insulator

Rated Current 12 Amps

Specifications

Contact Type: Solder Max. Matings: 5000

Contact Dia.: 1.3 mm (0.051in)

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

Bucket Dia.: 1 mm (0.039in)

Max. Solid Conductor: 0.5 mm² (AWG 20) Max. Stranded Conductor: 0.5 mm² (AWG 20)

R (max): 3.6 mOhm


Vtest (contact-contact): 1350 V (AC) 1900 V (DC) Vtest (contact-shell): 1450 V (AC) 2100 V (DC)

Others

Pressure: 30 bars IP Rating: 68

DRAWINGS

Draws





Dimensions

	А	В	L	М	N	S1	S 3
mm.	23.5	14.0	52.5	43.0	15.5	22	12
in.	0,93	0,55	2,07	1,69	0,61	0,87	0,47

RECOMMENDED BY LEMO

Tools

None

Cables

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

