

Cree® XLamp® CXB2530 LED



PRODUCT DESCRIPTION

XLamp® CXA2 LED Arrays lead the industry in efficacy and reliability for ceramic-based COB LEDs. Cree CXA2 LEDs easily deliver TM-21 lifetimes well beyond L90 60,000 hours under a wide range of operating conditions. CXA2 LED Arrays share the same physical design as XLamp CXA and CMA LED families, allowing lighting manufacturers to leverage the existing optical, mechanical and electrical design elements to accelerate time to market without additional cost.

CXA2 Standard Density LED Arrays are now available in two different versions: Standard and eTone™ LEDs. The eTone version delivers beautiful 90 CRI light quality at the same efficacy as today's standard 80 CRI LEDs.

FEATURES

- 19-mm optical source
- Mechanical and optical design consistent with other CXA25 and CXB25 LEDs
- Cree EasyWhite® 2-, 3- and 5-step binning
- Premium Color 2- and 3-step binning
- Standard & Premium Color LEDs available in 70, 80, 90 and 95 CRI minimum options
- eTone™ LEDs available in 90 CRI minimum option
- Forward voltage option: 36-V class
- 85 °C binning and characterization
- Extremely uniform color over viewing angle
- Top-side solder connections
- Thermocouple attach point
- NEMA SSL-3 2011 standard flux bins
- RoHS and REACH compliant
- UL® recognized component (E349212)

TABLE OF CONTENTS

| | |
|------------------------------------------------------------------------------|----|
| Characteristics | 2 |
| Operating Limits..... | 3 |
| Flux Characteristics, Order Codes & Bins - Standard LEDs..... | 4 |
| Flux Characteristics, Order Codes & Bins - Standard LEDs, Premium Color..... | 7 |
| Flux Characteristics, Order Codes and Bins - eTone™ LEDs..... | 8 |
| Relative Spectral Power Distribution - Standard LEDs..... | 9 |
| Relative Spectral Power Distribution - Standard LEDs, Premium Color..... | 10 |
| Relative Spectral Power Distribution - eTone™ LEDs | 11 |
| Electrical Characteristics..... | 11 |
| Relative Luminous Flux vs. Current..... | 12 |
| Typical Spatial Distribution..... | 13 |
| Performance Groups - Brightness | 13 |
| EasyWhite® Performance Groups - Chromaticity | 14 |
| Premium Color Performance Groups - Chromaticity | 15 |
| Cree EasyWhite® Bins Plotted on the 1931 CIE Color Space | 16 |
| Cree Premium Color Bins Plotted on the 1931 CIE Color Space | 17 |
| Bin and Order Code Formats | 19 |
| Mechanical Dimensions | 20 |
| Thermal Design | 21 |
| Notes | 22 |
| Packaging..... | 23 |



CHARACTERISTICS



| Characteristics | Unit | Minimum | Typical | Maximum |
|-------------------------------------------|---------|---------|---------|---------|
| Viewing angle (FWHM) | degrees | | 115 | |
| ESD classification (HBM per Mil-Std-883D) | V | | | 8000 |
| DC forward current - Standard | mA | | | 1600* |
| DC forward current - eTone | mA | | | 1600* |
| Reverse current | mA | | | 0.1 |
| Forward voltage (@ 800 mA, 85 °C) | V | | 35 | 38 |

* Refer to the Operating Limits section.

OPERATING LIMITS

The maximum current rating of the CXB2530 depends on the case temperature (T_c) when the LED has reached thermal equilibrium under steady-state operation. The graph shown below assumes that the system design employs good thermal management (thermal interface material and heat sink) and may vary when poor thermal management is employed. Please refer to the Mechanical Dimensions section on page 20 for the location of the T_c measurement point.

Another important factor in good thermal management is the temperature of the Light Emitting Surface (LES). Cree recommends a maximum LES temperature of 135 °C to ensure optimal LED lifetime. Please refer to the Thermal Design section on page 21 for more information on LES temperature measurement.



FLUX CHARACTERISTICS, ORDER CODES & BINS - STANDARD LEDS ($I_F = 800 \text{ mA}$, $T_J = 85 \text{ °C}$)

The following table provides order codes for XLamp CXB2530 LEDs. For a complete description of the order code nomenclature, please see the Bin and Order Code Formats section (page 19).

| Nominal CCT | CRI* | | Minimum Luminous Flux | | | 2-Step | | 3-Step | | 5-Step | |
|-------------|------|-----|-----------------------|-------------------|---------------------|--------|------------|--------|------------|--------|--------------------------|
| | Min | Typ | Group | Flux (lm) @ 85 °C | Flux (lm) @ 25 °C** | Group | Order Code | Group | Order Code | Group | Order Code |
| 6500 K | 70 | --- | U2 | 3680 | 4031 | | | | | 65E | CXB2530-0000-000N0BU265E |
| | | | U4 | 3955 | 4332 | | | | | | CXB2530-0000-000N0BU465E |
| | | | V2 | 4230 | 4670 | | | | | | CXB2530-0000-000N0BV265E |
| | | | V4 | 4545 | 5018 | | | | | | CXB2530-0000-000N0BV465E |
| | 80 | --- | U2 | 3680 | 4031 | | | | | 65E | CXB2530-0000-000N0HU265E |
| | | | U4 | 3955 | 4366 | | | | | | CXB2530-0000-000N0HU465E |
| | | | V2 | 4230 | 4670 | | | | | | CXB2530-0000-000N0HV265E |
| | | | | | | | | | | | |
| 5700 K | 70 | --- | U2 | 3680 | 4031 | | | | | 57E | CXB2530-0000-000N0BU257E |
| | | | U4 | 3955 | 4332 | | | | | | CXB2530-0000-000N0BU457E |
| | | | V2 | 4230 | 4670 | | | | | | CXB2530-0000-000N0BV257E |
| | | | V4 | 4545 | 5018 | | | | | | CXB2530-0000-000N0BV457E |
| | 80 | --- | U2 | 3680 | 4031 | | | | | 57E | CXB2530-0000-000N0HU257E |
| | | | U4 | 3955 | 4366 | | | | | | CXB2530-0000-000N0HU457E |
| | | | V2 | 4230 | 4670 | | | | | | CXB2530-0000-000N0HV257E |
| | | | | | | | | | | | |

Notes

- Cree maintains a tolerance of $\pm 7\%$ on flux and power measurements, ± 0.005 on chromaticity (CCx, CCy) measurements and a tolerance of ± 2 on CRI measurements. See the Measurements section (page 22).
- Cree XLamp CXB2530 LED order codes specify only a minimum flux bin and not a maximum. Cree may ship reels in flux bins higher than the minimum specified by the order code without advance notice. Shipments will always adhere to the chromaticity bin restrictions specified by the order code.
- * For 80 CRI minimum LEDs, CRI R9 minimum is 0 with a ± 2 tolerance. For 90 CRI minimum LEDs, CRI R9 typical is 60.
- ** Flux values @ 25 °C are calculated and for reference only.

FLUX CHARACTERISTICS, ORDER CODES & BINS - STANDARD LEDS ($I_F = 800 \text{ mA}$, $T_J = 85^\circ\text{C}$) - CONTINUED

| Nominal CCT | CRI* | | Minimum Luminous Flux | | | 2-Step | | 3-Step | | 5-Step | |
|-------------|--------|-----|-----------------------|-------------------|---------------------|--------|--------------------------|--------------------------|--------------------------|--------------------------|--------------------------|
| | Min | Typ | Group | Flux (lm) @ 85 °C | Flux (lm) @ 25 °C** | Group | Order Code | Group | Order Code | Group | Order Code |
| 5000 K | 70 | — | U2 | 3680 | 4031 | | | | | 50E | CXB2530-0000-000N0BU250E |
| | | | U4 | 3955 | 4332 | | | | | | CXB2530-0000-000N0BU450E |
| | | | V2 | 4230 | 4670 | | | | | | CXB2530-0000-000N0BV250E |
| | | | V4 | 4545 | 5018 | | | | | | CXB2530-0000-000N0BV450E |
| | 80 | — | U2 | 3680 | 4031 | | 50G | CXB2530-0000-000N0HU250G | 50E | CXB2530-0000-000N0HU250E | |
| | | | U4 | 3955 | 4366 | | | CXB2530-0000-000N0HU450G | | CXB2530-0000-000N0HU450E | |
| | | | V2 | 4230 | 4670 | | | CXB2530-0000-000N0HV250G | | | |
| | 90 | 92 | T4 | 3440 | 3768 | | 50G | CXB2530-0000-000N0UT450G | | | |
| | | | U2 | 3680 | 4031 | | | CXB2530-0000-000N0UU250G | | | |
| | 4000 K | 70 | — | U2 | 3680 | 4031 | | | | | 40E |
| U4 | | | | 3955 | 4332 | | | CXB2530-0000-000N0BU440E | | | |
| V2 | | | | 4230 | 4670 | | | CXB2530-0000-000N0BV240E | | | |
| V4 | | | | 4545 | 5018 | | | CXB2530-0000-000N0BV440E | | | |
| 80 | | — | U2 | 3680 | 4031 | 40H | CXB2530-0000-000N0HU240H | 40G | CXB2530-0000-000N0HU240G | | |
| | | | U4 | 3955 | 4366 | | CXB2530-0000-000N0HU440H | | CXB2530-0000-000N0HU440G | | |
| | | | V2 | 4230 | 4670 | | CXB2530-0000-000N0HV240H | | CXB2530-0000-000N0HV240G | | |
| 90 | | 92 | T2 | 3200 | 3505 | 40H | CXB2530-0000-000N0UT240H | 40G | CXB2530-0000-000N0UT240G | | |
| | | | T4 | 3440 | 3798 | | CXB2530-0000-000N0UT440H | | CXB2530-0000-000N0UT440G | | |
| | | | U2 | 3680 | 4063 | | CXB2530-0000-000N0UU240H | | CXB2530-0000-000N0UU240G | | |

- Notes
- Cree maintains a tolerance of $\pm 7\%$ on flux and power measurements, ± 0.005 on chromaticity (CCx, CCy) measurements and a tolerance of ± 2 on CRI measurements. See the Measurements section (page 22).
 - Cree XLamp CXB2530 LED order codes specify only a minimum flux bin and not a maximum. Cree may ship reels in flux bins higher than the minimum specified by the order code without advance notice. Shipments will always adhere to the chromaticity bin restrictions specified by the order code.
- * For 80 CRI minimum LEDs, CRI R9 minimum is 0 with a ± 2 tolerance. For 90 CRI minimum LEDs, CRI R9 typical is 60.
- ** Flux values @ 25 °C are calculated and for reference only.

FLUX CHARACTERISTICS, ORDER CODES & BINS - STANDARD LEDS (I_F = 800 mA, T_J = 85 °C) - CONTINUED

| Nominal CCT | CRI* | | Minimum Luminous Flux | | | 2-Step | | 3-Step | | 5-Step | |
|-------------|------|-----|-----------------------|-------------------|---------------------|--------|--------------------------|--------|--------------------------|--------|------------|
| | Min | Typ | Group | Flux (lm) @ 85 °C | Flux (lm) @ 25 °C** | Group | Order Code | Group | Order Code | Group | Order Code |
| 3500 K | 80 | --- | T4 | 3440 | 3768 | 35H | CXB2530-0000-000N0HT435H | 35G | CXB2530-0000-000N0HT435G | | |
| | | | U2 | 3680 | 4063 | | CXB2530-0000-000N0HU235H | | CXB2530-0000-000N0HU235G | | |
| | | | U4 | 3955 | 4366 | | CXB2530-0000-000N0HU435H | | CXB2530-0000-000N0HU435G | | |
| | 90 | 92 | S4 | 2990 | 3275 | 35H | CXB2530-0000-000N0US435H | 35G | CXB2530-0000-000N0US435G | | |
| | | | T2 | 3200 | 3533 | | CXB2530-0000-000N0UT235H | | CXB2530-0000-000N0UT235G | | |
| | | | T4 | 3440 | 3798 | | CXB2530-0000-000N0UT435H | | CXB2530-0000-000N0UT435G | | |
| 3000 K | 80 | --- | T4 | 3440 | 3768 | 30H | CXB2530-0000-000N0HT430H | 30G | CXB2530-0000-000N0HT430G | | |
| | | | U2 | 3680 | 4063 | | CXB2530-0000-000N0HU230H | | CXB2530-0000-000N0HU230G | | |
| | | | U4 | 3955 | 4366 | | CXB2530-0000-000N0HU430H | | CXB2530-0000-000N0HU430G | | |
| | 90 | 92 | S4 | 2990 | 3275 | 30H | CXB2530-0000-000N0US430H | 30G | CXB2530-0000-000N0US430G | | |
| | | | T2 | 3200 | 3533 | | CXB2530-0000-000N0UT230H | | CXB2530-0000-000N0UT230G | | |
| | | | T4 | 3440 | 3798 | | CXB2530-0000-000N0UT430H | | CXB2530-0000-000N0UT430G | | |
| 2700 K | 80 | --- | T2 | 3200 | 3505 | 27H | CXB2530-0000-000N0HT227H | 27G | CXB2530-0000-000N0HT227G | | |
| | | | T4 | 3440 | 3798 | | CXB2530-0000-000N0HT427H | | CXB2530-0000-000N0HT427G | | |
| | | | U2 | 3680 | 4063 | | CXB2530-0000-000N0HU227H | | CXB2530-0000-000N0HU227G | | |
| | 90 | 92 | S2 | 2780 | 3045 | 27H | CXB2530-0000-000N0US227H | 27G | CXB2530-0000-000N0US227G | | |
| | | | S4 | 2990 | 3301 | | CXB2530-0000-000N0US427H | | CXB2530-0000-000N0US427G | | |
| | | | T2 | 3200 | 3533 | | CXB2530-0000-000N0UT227H | | CXB2530-0000-000N0UT227G | | |
| 2200 K | 80 | --- | T2 | 3200 | 3533 | | | 22G | CXB2530-0000-000N0HT222G | | |

- Notes
- Cree maintains a tolerance of ±7% on flux and power measurements, ±0.005 on chromaticity (CCx, CCy) measurements and a tolerance of ±2 on CRI measurements. See the Measurements section (page 22).
 - Cree XLamp CXB2530 LED order codes specify only a minimum flux bin and not a maximum. Cree may ship reels in flux bins higher than the minimum specified by the order code without advance notice. Shipments will always adhere to the chromaticity bin restrictions specified by the order code.
 - * For 80 CRI minimum LEDs, CRI R9 minimum is 0 with a ±2 tolerance. For 90 CRI minimum LEDs, CRI R9 typical is 60.
 - ** Flux values @ 25 °C are calculated and for reference only.

FLUX CHARACTERISTICS, ORDER CODES & BINS - STANDARD LEDS, PREMIUM COLOR ($I_F = 800\text{ mA}$, $T_J = 85\text{ °C}$)

Fidelity

| Nominal CCT | CRI* | | Minimum Luminous Flux | | | Typical Luminous Flux (lm) @ 85 °C | 2-Step | |
|-------------|------|-----|-----------------------|-------------------|---------------------|------------------------------------|--------|--------------------------|
| | Min | Typ | Group | Flux (lm) @ 85 °C | Flux (lm) @ 25 °C** | | Group | Order Code |
| 4000 K | 95 | 98 | S4 | 2990 | 3301 | 3238 | L5A | CXB2530-0000-000N0ZS4L5A |
| 3500 K | 95 | 98 | S2 | 2780 | 3069 | 3118 | 35H | CXB2530-0000-000N0ZS235H |
| 3000 K | 95 | 98 | S2 | 2780 | 3069 | 2998 | 30H | CXB2530-0000-000N0ZS230H |
| 2700 K | 95 | 98 | R4 | 2600 | 2870 | 2829 | 27H | CXB2530-0000-000N0ZR427H |

Specialty

| Nominal CCT | CRI | | Minimum Luminous Flux | | | Typical Luminous Flux (lm) @ 85 °C | 2-Step | | 3-Step | | | |
|-------------|-----|-----|-----------------------|-------------------|---------------------|------------------------------------|--------|--------------------------|--------|--------------------------|-------|--------------------------|
| | Min | Typ | Group | Flux (lm) @ 85 °C | Flux (lm) @ 25 °C** | | Group | Order Code | Group | Order Code | Group | Order Code |
| 3100 K | 90 | 92 | S4 | 2990 | 3301 | 3455 | | | 31Q | CXB2530-0000-000N0US431Q | | |
| | | | T2 | 3200 | 3533 | | | | | CXB2530-0000-000N0UT231Q | | |
| 3000 K | 80 | --- | T4 | 3440 | 3798 | 4018 | L7B | CXB2530-0000-000N0HT4L7B | | | | |
| | 90 | 92 | S4 | 2990 | 3301 | 3455 | | | 30Q | CXB2530-0000-000N0US430Q | 30U | CXB2530-0000-000N0US430U |
| | | | T2 | 3200 | 3533 | | | | | CXB2530-0000-000N0UT230Q | | CXB2530-0000-000N0UT230U |
| | 95 | 98 | R4 | 2600 | 2870 | 2829 | L7C | CXB2530-0000-000N0ZR4L7C | | | | |

Notes

- Cree maintains a tolerance of $\pm 7\%$ on flux and power measurements, ± 0.005 on chromaticity (CCx, CCy) measurements and a tolerance of ± 2 on CRI measurements. See the Measurements section (page 22).
- Cree XLamp CXB2530 LED order codes specify only a minimum flux bin and not a maximum. Cree may ship reels in flux bins higher than the minimum specified by the order code without advance notice. Shipments will always adhere to the chromaticity bin restrictions specified by the order code.
- * For 80 CRI minimum LEDs, CRI R9 minimum is 0 with a ± 2 tolerance. For 90 CRI minimum LEDs, CRI R9 typical is 60.
- ** Flux values @ 25 °C are calculated and for reference only.

FLUX CHARACTERISTICS, ORDER CODES AND BINS - ETONE™ LEDS ($I_F = 800\text{ mA}$, $T_J = 85\text{ }^\circ\text{C}$)

| Nominal CCT | CRI* | | Minimum Luminous Flux (lm) | Typical Luminous Flux (lm) | 2-Step | | 3-Step | |
|-------------|------|-----|----------------------------|----------------------------|--------|--------------------------|--------|--------------------------|
| | Min. | Typ | | | Group | Order Code | Group | Order Code |
| 4000 K | 90 | 92 | 3386 | 3922 | 40H | CXB2530-0000-00PN0U0A40H | 40G | CXB2530-0000-00PN0U0A40G |
| 3500 K | 90 | 92 | 3199 | 3856 | 35H | CXB2530-0000-00PN0U0A35H | 35G | CXB2530-0000-00PN0U0A35G |
| 3000 K | 90 | 92 | 3268 | 3817 | 30H | CXB2530-0000-00PN0U0A30H | 30G | CXB2530-0000-00PN0U0A30G |
| 2700 K | 90 | 92 | 3040 | 3693 | 27H | CXB2530-0000-00PN0U0A27H | 27G | CXB2530-0000-00PN0U0A27G |

Specialty


| Nominal CCT | CRI | | Minimum Luminous Flux (lm) | Typical Luminous Flux (lm) | 3-Step | | | |
|-------------|------|-----|----------------------------|----------------------------|--------|--------------------------|-------|--------------------------|
| | Min. | Typ | | | Group | Order Code | Group | Order Code |
| 3100 K | 90 | 92 | 3234 | 3777 | 31Q | CXB2530-0000-00PN0U0A31Q | | |
| 3000 K | 90 | 92 | 3268 | 3817 | 30Q | CXB2530-0000-00PN0U0A30Q | 30U | CXB2530-0000-00PN0U0A30U |

Notes

- Cree maintains a tolerance of $\pm 7\%$ on flux and power measurements, ± 0.005 on chromaticity (CCx, CCy) measurements and a tolerance of ± 2 on CRI measurements. See the Measurements section (page 22).
- Cree XLamp CXB2530 LED order codes specify only a minimum flux bin and not a maximum. Cree may ship reels in flux bins higher than the minimum specified by the order code without advance notice. Shipments will always adhere to the chromaticity bin restrictions specified by the order code.
- * For 80 CRI minimum LEDs, CRI R9 minimum is 0 with a ± 2 tolerance. For 90 CRI minimum LEDs, CRI R9 typical is 60.

RELATIVE SPECTRAL POWER DISTRIBUTION - STANDARD LEDS


The following graph is the result of a series of pulsed measurements at 800 mA and $T_j = 85^\circ\text{C}$.




RELATIVE SPECTRAL POWER DISTRIBUTION - STANDARD LEDS, PREMIUM COLOR

The following graphs are the result of a series of pulsed measurements at 800 mA and $T_j = 85^\circ\text{C}$.

Fidelity




Specialty




RELATIVE SPECTRAL POWER DISTRIBUTION - ETONE™ LEDS

The following graph is the result of a series of pulsed measurements at 800 mA and $T_j = 85^\circ\text{C}$.



ELECTRICAL CHARACTERISTICS


The following graph is the result of a series of steady-state measurements.




RELATIVE LUMINOUS FLUX VS. CURRENT ($T_J = 85^\circ\text{C}$)

The relative luminous flux values provided below are the ratio of measurements of the CXB2530 LED at steady-state operation at the given conditions, divided by flux measured during binning, which is a pulsed measurement at 800 mA at $T_J = 85^\circ\text{C}$.

For example, at steady-state operation of $T_c = 25^\circ\text{C}$, $I_F = 1080\text{ mA}$, the relative luminous flux ratio is 140% in the chart below. A CXB2530 LED that measures 3200 lm during binning will deliver 4480 lm (3200×1.4) at steady-state operation of $T_c = 25^\circ\text{C}$, $I_F = 1080\text{ mA}$.



TYPICAL SPATIAL DISTRIBUTION



PERFORMANCE GROUPS - BRIGHTNESS ($I_F = 800 \text{ mA}$, $T_J = 85^\circ\text{C}$)

XLamp CXB2530 LEDs are tested for luminous flux and placed into one of the following bins.

| Group Code | Minimum Luminous Flux | Maximum Luminous Flux |
|------------|-----------------------|-----------------------|
| R4 | 2600 | 2780 |
| S2 | 2780 | 2990 |
| S4 | 2990 | 3200 |
| T2 | 3200 | 3440 |
| T4 | 3440 | 3680 |
| U2 | 3680 | 3955 |
| U4 | 3955 | 4230 |
| V2 | 4230 | 4545 |
| V4 | 4545 | 4860 |
| W2 | 4860 | 5225 |

EASYWHITE® PERFORMANCE GROUPS - CHROMATICITY ($T_j = 85\text{ }^{\circ}\text{C}$)

XLamp CXB2530 LEDs are tested for chromaticity and placed into one of the regions defined by the following bounding coordinates.

| EasyWhite Color Temperatures – 2-Step | | | |
|---------------------------------------|--------|--------|--------|
| Code | CCT | x | y |
| 40H | 4000 K | 0.3777 | 0.3739 |
| | | 0.3797 | 0.3816 |
| | | 0.3861 | 0.3855 |
| | | 0.3838 | 0.3777 |
| 35H | 3500 K | 0.4022 | 0.3858 |
| | | 0.4053 | 0.3942 |
| | | 0.4125 | 0.3977 |
| | | 0.4091 | 0.3891 |
| 30H | 3000 K | 0.4287 | 0.3975 |
| | | 0.4328 | 0.4064 |
| | | 0.4390 | 0.4086 |
| | | 0.4347 | 0.3996 |
| 27H | 2700 K | 0.4524 | 0.4048 |
| | | 0.4574 | 0.4140 |
| | | 0.4633 | 0.4154 |
| | | 0.4581 | 0.4062 |

| EasyWhite Color Temperatures – 3-Step Ellipse | | | | | | |
|-----------------------------------------------|--------|--------------|--------|------------|------------|--------------------|
| Bin Code | CCT | Center Point | | Major Axis | Minor Axis | Rotation Angle (°) |
| | | x | y | a | b | |
| 50G | 5000 K | 0.3447 | 0.3553 | 0.00840 | 0.00312 | 65.0 |
| 40G | 4000 K | 0.3818 | 0.3797 | 0.00939 | 0.00402 | 53.7 |
| 35G | 3500 K | 0.4073 | 0.3917 | 0.00927 | 0.00414 | 54.0 |
| 30G | 3000 K | 0.4338 | 0.4030 | 0.00834 | 0.00408 | 53.2 |
| 27G | 2700 K | 0.4577 | 0.4099 | 0.00834 | 0.00420 | 48.5 |
| 22G | 2200 K | 0.5066 | 0.4158 | 0.00980 | 0.00480 | 45.5 |

| EasyWhite Color Temperatures – 5-Step Ellipse | | | | | | |
|-----------------------------------------------|--------|--------------|--------|------------|------------|--------------------|
| Bin Code | CCT | Center Point | | Major Axis | Minor Axis | Rotation Angle (°) |
| | | x | y | a | b | |
| 65E | 6500 K | 0.3123 | 0.3282 | 0.01110 | 0.00550 | 61.0 |
| 57E | 5700 K | 0.3287 | 0.3417 | 0.01230 | 0.00600 | 72.0 |
| 50E | 5000 K | 0.3447 | 0.3553 | 0.01400 | 0.00520 | 65.0 |
| 40E | 4000 K | 0.3818 | 0.3797 | 0.01565 | 0.00670 | 53.7 |

PREMIUM COLOR PERFORMANCE GROUPS - CHROMATICITY ($T_j = 85\text{ }^{\circ}\text{C}$)

XLamp CXB2530 LEDs are tested for chromaticity and placed into one of the regions defined by the following bounding coordinates.

Fidelity


| EasyWhite Color Temperatures – 2-Step | | | |
|---------------------------------------|--------|--------|--------|
| Code | CCT | x | y |
| L5A | 4000 K | 0.3764 | 0.3711 |
| | | 0.3784 | 0.3787 |
| | | 0.3847 | 0.3826 |
| | | 0.3825 | 0.3748 |
| 35H | 3500 K | 0.4022 | 0.3858 |
| | | 0.4053 | 0.3942 |
| | | 0.4125 | 0.3977 |
| | | 0.4091 | 0.3891 |
| 30H | 3000 K | 0.4287 | 0.3975 |
| | | 0.4328 | 0.4064 |
| | | 0.4390 | 0.4086 |
| | | 0.4347 | 0.3996 |
| 27H | 2700 K | 0.4524 | 0.4048 |
| | | 0.4574 | 0.4140 |
| | | 0.4633 | 0.4154 |
| | | 0.4581 | 0.4062 |

Specialty

| EasyWhite Color Temperatures – 2-Step | | | |
|---------------------------------------|--------|--------|--------|
| Code | CCT | x | y |
| L7B | 3000 K | 0.4263 | 0.3848 |
| | | 0.4296 | 0.3916 |
| | | 0.4361 | 0.3938 |
| | | 0.4326 | 0.3868 |
| L7C | 3000 K | 0.4192 | 0.3754 |
| | | 0.4224 | 0.3823 |
| | | 0.4291 | 0.3847 |
| | | 0.4257 | 0.3777 |


| EasyWhite Color Temperatures – 3-Step Ellipse | | | | | | |
|-----------------------------------------------|--------|--------------|--------|------------|------------|--------------------|
| Bin Code | CCT | Center Point | | Major Axis | Minor Axis | Rotation Angle (°) |
| | | x | y | a | b | |
| 31Q | 3100 K | 0.4236 | 0.3888 | 0.00848 | 0.00455 | 50.3 |
| 30Q | 3000 K | 0.4305 | 0.3935 | 0.00834 | 0.00408 | 53.2 |
| 30U | 3000 K | 0.4274 | 0.3837 | 0.00834 | 0.00408 | 53.2 |

CREE EASYWHITE® BINS PLOTTED ON THE 1931 CIE COLOR SPACE ($T_j = 85^\circ\text{C}$)




CREE PREMIUM COLOR BINS PLOTTED ON THE 1931 CIE COLOR SPACE ($T_j = 85^\circ\text{C}$)

Fidelity (2-step)




CREE PREMIUM COLOR BINS PLOTTED ON THE 1931 CIE COLOR SPACE ($T_j = 85^\circ\text{C}$) - CONTINUED

Speciality (2-step)





Speciality (3-step)



BIN AND ORDER CODE FORMATS

Bin codes and order codes are configured as follows:



MECHANICAL DIMENSIONS

Dimensions are in mm.

Tolerances unless otherwise


specified: ± 0.13

$\chi^\circ +1^\circ$

Meaning of LED marking

B2530N = 36-V CXB2530

B2530Ne = 36-V CXB2530 eTone





THERMAL DESIGN

The CXB family of LED arrays can include over a hundred different LED die inside one package, and thus over a hundred different junction temperatures (T_j). Cree has intentionally removed junction-temperature-based operating limits and replaced the commonplace maximum T_j calculations with maximum ratings based on forward current (I_f) and case temperature (T_c). No additional calculations are required to ensure that the CXB LED is being operated within its designed limits. LES temperature measurement provides additional verification of good thermal design. Please refer to page 3 for the Operating Limit specifications.

There is no need to calculate for T_j inside the package, as the thermal management design process, specifically from T_{sp} to ambient (T_a), remains identical to any other LED component. For more information on thermal management of Cree XLamp LEDs, please refer to the [Thermal Management application note](#). For CXB soldering recommendations and more information on thermal interface materials (TIM), LES temperature measurement, and connection methods, please refer to the [Cree XLamp CX Family LEDs soldering and handling document](#). The [CX Family LED Design Guide](#) provides basic information on the requirements to use Cree XLamp CXB LEDs successfully in luminaire designs.

To keep the CXB2530 LED at or below the maximum rated T_c , the case to ambient temperature thermal resistance (R_{c-a}) must be at or below the maximum R_{c-a} value shown on the following graph, depending on the operating environment. The y-axis in the graph is a base 10 logarithmic scale.

As the figure at right shows, the R_{c-a} value is the sum of the thermal resistance of the TIM (R_{tim}) plus the thermal resistance of the heat sink (R_{hs}).



NOTES

Measurements

The luminous flux, radiant power, chromaticity, forward voltage and CRI measurements in this document are binning specifications only and solely represent product measurements as of the date of shipment. These measurements will change over time based on a number of factors that are not within Cree's control and are not intended or provided as operational specifications for the products. Calculated values are provided for informational purposes only and are not intended or provided as specifications.

Pre-Release Qualification Testing

Please read the [LED Reliability Overview](#) for details of the qualification process Cree applies to ensure long-term reliability for XLamp LEDs and details of Cree's pre-release qualification testing for XLamp LEDs.

Lumen Maintenance

Cree now uses standardized IES LM-80-08 and TM-21-11 methods for collecting long-term data and extrapolating LED lumen maintenance. For information on the specific LM-80 data sets available for this LED, refer to the public [LM-80 results document](#).

Please read the [Long-Term Lumen Maintenance application note](#) for more details on Cree's lumen maintenance testing and forecasting. Please read the [Thermal Management application note](#) for details on how thermal design, ambient temperature, and drive current affect the LED junction temperature.

RoHS Compliance

The levels of RoHS restricted materials in this product are below the maximum concentration values (also referred to as the threshold limits) permitted for such substances, or are used in an exempted application, in accordance with EU Directive 2011/65/EC (RoHS2), as implemented January 2, 2013. RoHS Declarations for this product can be obtained from your Cree representative or from the [Product Ecology](#) section of the Cree website.

REACH Compliance

REACH substances of very high concern (SVHCs) information is available for this product. Since the European Chemical Agency (ECHA) has published notice of their intent to frequently revise the SVHC listing for the foreseeable future, please contact a Cree representative to insure you get the most up-to-date REACH Declaration. REACH banned substance information (REACH Article 67) is also available upon request.

UL® Recognized Component

This product meets the requirements to be considered a UL Recognized Component with Level 4 enclosure consideration. The LED package or a portion thereof has been investigated as a fire and electrical enclosure per ANSI/UL 8750.

Vision Advisory

WARNING: Do not look at an exposed lamp in operation. Eye injury can result. For more information about LEDs and eye safety, please refer to the [LED Eye Safety application note](#).

PACKAGING

Cree CXB2530 LEDs are packaged in trays of 20. Five trays are sealed in an anti-static bag and placed inside a carton, for a total of 100 LEDs per carton. Each carton contains 100 LEDs from the same performance bin.

Dimensions are in inches.

Tolerances: $\pm .13$

$\alpha^\circ \pm 1^\circ$

