

# www.lemo.com

# PSA.3S.405.CTLC52

# **SUMMARY**

#### # Wires

 Low
 0

 High
 1

 Coax
 0

Triax 0

Quad 0

Fiber 0

Fluidic 0

Series 3S

**Termination type** Female solder High-Voltage

IP rating 50

**Cable Ø** 4.30 - 5.70 mm

Matching parts

**Status** active

Alternative part



Image is for illustrative purpose only

### **Download**

Request a quote

Catalog

# **TECHNICAL DETAILS**

### **Mechanics**

Shell Style/Model PSA\*: Fixed receptacle, nut fixing, cable collet

**Keying** Circular (can rotate), plug has male contact(s)

Housing Material Brass (chrome plated) shell and collet nut, nickel plated brass latch sleeve and mid pieces

Cable Fixing : 4.3 - 5.7 mm

Variant

Weight 57.00 g

### **Performance**

**Configuration** 3S.405 : 1 High Voltage

Insulator T: PTFE Rated Current 15 Amps

## **Specifications**

Contact Type: Solder Test voltage (kV DC) 10.5

Test voltage (kV AC) 7.5

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

Air clearance (mm): 12.8 Creepage dist.(mm): 12.9

### **Others**

Endurance (Shell): 5000 mating cycles Temp (min / max): -55°C / +250°C


Humidity (max): <=95% [at 60 deg C /140 F]

Vibration: 15 g [10 Hz - 2000 Hz] Shock Resistance: 100 g [ 6 ms] Salt Spray Corrosion: >144 hr Climatical Category: 50/175/21 Shielding (min): 75 dB (10 MHz) Shielding (min): 40 dB (1 GHz)

IP Rating: 50

# **DRAWINGS**

#### **Draws**







### **Dimensions**

	А	В	Е	L	М	<b>S</b> 1	S2	\$3	e
mm.	22	25.2	11.5	59	2	16.5	14	22	M18x1.0
in.	0,87	0,99	0,45	2,32	0,08	0,65	0,55	0,87	

# **RECOMMENDED BY LEMO**

# Tools

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

Spanner wrench: MTZ.3S.500.014 Cables