

SUMMARY

Wires

Low	0		
High	0		
Coax	0		Image is for illustrative purpose only
Triax	1	Download	
Quad	0	Request a quote	
Fiber	0	Catalog	
Fluidic	0	<u>eatatos</u>	
Series	OS		
Termination type	Female solder		
IP rating	50		
Cable Ø	2.30 - 3.20 mm		
Matching parts	FFA.0S.650.CTAC32		
Status	active		
Alternative part			

TECHNICAL DETAILS

Mechanics

Shell Style/Model	*.
Keying	
Housing Material	Brass (chrome plated) shell and collet nut, nickel plated brass latch sleeve and mid pieces
Cable Fixing	: 2.3 - 3.2 mm
Variant	
Weight	8.75 g
Performance	
Configuration	0S.650 : 1 Triax (50 Ohm)

Insulator	T: PTFE
Rated Current	6 Amps

Specifications

Contact Type: Triaxial 50 Ohm (Solder) Max. Matings: 1000 Contact Dia.: 0.9 mm (0.035"in)

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

Vtest: 1200 V (AC), 1700 V (DC) Impedance: 50 Ohm VSWR: 1.03 + 0.34 * f/GHz Cable type: RGT 178, RGT 174

Others

Endurance (Shell): 5000 mating cycles Temp (min / max): -55°C / +250°C Humidity (max): <=95% [at 60 deg C /140 F] Vibration: 15 g [10 Hz - 2000 Hz] Shock Resistance: 100 g [6 ms] Salt Spray Corrosion: >144 hr Climatical Category: 50/175/21 Shielding (min): 75 dB (10 MHz) Shielding (min): 40 dB (1 GHz) IP Rating: 50

DRAWINGS

Draws



Dimensions

RECOMMENDED BY LEMO

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

Tools

Spanner wrench: DCD.0S.005.PA065

Cables

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.