



0.3 PSI-D-4V-MIL Information



For Reference Only

Part Number 0.3 PSI-D-4V-MIL

Manufacturer All Sensors Corporation

Category Sensors, Transducers

Pressure Sensors, Transducers SENSOR 0.3PSID 4V DUAL

Package 4-SIP Module

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.

Description









0.3 PSI-D-4V-MIL Specifications

Manufacturer Part Number 0.3 PSI-D-4V-MIL Manufacturer All Sensors Corporation Category Sensors, Transducers Pressure Sensors, Transducers Package 4-SIP Module Series AXCA Pressure Type Differential Operating Pressure ±0.3 PSI (±2.07 kPa) Output Type Analog Voltage Output 0.25 V ~ 4.25 V Accuracy ±0.5% Voltage - Supply 4.5 V ~ 5.5 V Port Size Male - 0.19" (4.8mm) Tube, Dual Port Style Barbless Features Amplified Output, Temperature Compensated Termination Style PCB Maximum Pressure ±5 PSI (±34.47 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-SIP Module Supplier Device Package - **Report errors?			
Category Sensors, Transducers Pressure Sensors, Transducers 4-SIP Module Series AXCA Pressure Type Differential Operating Pressure ±0.3 PSI (±2.07 kPa) Output Type Analog Voltage Output 0.25 V ~ 4.25 V Accuracy ±0.5% Voltage - Supply 4.5 V ~ 5.5 V Port Size Male - 0.19" (4.8mm) Tube, Dual Port Style Barbless Features Amplified Output, Temperature Compensated Termination Style Maximum Pressure ±5 PSI (±34.47 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-SIP Module Supplier Device Package	Manufacturer Part Number	0.3 PSI-D-4V-MIL	
Pressure Sensors, Transducers Package 4-SIP Module Series AXCA Pressure Type Differential Operating Pressure	Manufacturer	All Sensors Corporation	
Package4-SIP ModuleSeriesAXCAPressure TypeDifferentialOperating Pressure±0.3 PSI (±2.07 kPa)Output TypeAnalog VoltageOutput0.25 V ~ 4.25 VAccuracy±0.5%Voltage - Supply4.5 V ~ 5.5 VPort SizeMale - 0.19" (4.8mm) Tube, DualPort StyleBarblessFeaturesAmplified Output, Temperature CompensatedTermination StylePCBMaximum Pressure±5 PSI (±34.47 kPa)Operating Temperature-40°C ~ 125°CPackage / Case4-SIP ModuleSupplier Device Package-	Category	Sensors, Transducers	
SeriesAXCAPressure TypeDifferentialOperating Pressure±0.3 PSI (±2.07 kPa)Output TypeAnalog VoltageOutput0.25 V ~ 4.25 VAccuracy±0.5%Voltage - Supply4.5 V ~ 5.5 VPort SizeMale - 0.19" (4.8mm) Tube, DualPort StyleBarblessFeaturesAmplified Output, Temperature CompensatedTermination StylePCBMaximum Pressure±5 PSI (±34.47 kPa)Operating Temperature-40°C ~ 125°CPackage / Case4-SIP ModuleSupplier Device Package-		Pressure Sensors, Transducers	
Pressure Type Differential Operating Pressure ±0.3 PSI (±2.07 kPa) Output Type Analog Voltage Output 0.25 V ~ 4.25 V Accuracy ±0.5% Voltage - Supply 4.5 V ~ 5.5 V Port Size Male - 0.19" (4.8mm) Tube, Dual Port Style Barbless Features Amplified Output, Temperature Compensated Termination Style PCB Maximum Pressure ±5 PSI (±34.47 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-SIP Module Supplier Device Package	Package	4-SIP Module	
Operating Pressure $\pm 0.3 \text{ PSI } (\pm 2.07 \text{ kPa})$ Output Type Analog Voltage Output $0.25 \text{ V} \sim 4.25 \text{ V}$ Accuracy $\pm 0.5\%$ Voltage - Supply $4.5 \text{ V} \sim 5.5 \text{ V}$ Port Size Male - 0.19 " (4.8mm) Tube, Dual Port Style Barbless Features Amplified Output, Temperature Compensated Termination Style PCB Maximum Pressure $\pm 5 \text{ PSI } (\pm 34.47 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Package / Case $4-\text{SIP Module}$ Supplier Device Package	Series	AXCA	
Output Type	Pressure Type	Differential	
Output $0.25 \text{ V} \sim 4.25 \text{ V}$ Accuracy $\pm 0.5\%$ Voltage - Supply $4.5 \text{ V} \sim 5.5 \text{ V}$ Port SizeMale - 0.19 " (4.8mm) Tube, DualPort StyleBarblessFeaturesAmplified Output, Temperature CompensatedTermination StylePCBMaximum Pressure $\pm 5 \text{ PSI } (\pm 34.47 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Package / Case $4-\text{SIP Module}$ Supplier Device Package-	Operating Pressure	±0.3 PSI (±2.07 kPa)	
Accuracy ±0.5% Voltage - Supply 4.5 V ~ 5.5 V Port Size Male - 0.19" (4.8mm) Tube, Dual Port Style Barbless Features Amplified Output, Temperature Compensated Termination Style PCB Maximum Pressure ±5 PSI (±34.47 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-SIP Module Supplier Device Package	Output Type	Analog Voltage	
Voltage - Supply 4.5 V ~ 5.5 V Port Size Male - 0.19" (4.8mm) Tube, Dual Port Style Barbless Features Amplified Output, Temperature Compensated Termination Style PCB Maximum Pressure ±5 PSI (±34.47 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-SIP Module Supplier Device Package	Output	0.25 V ~ 4.25 V	
Port Size Male - 0.19" (4.8mm) Tube, Dual Port Style Barbless Features Amplified Output, Temperature Compensated Termination Style PCB Maximum Pressure ±5 PSI (±34.47 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-SIP Module Supplier Device Package	Accuracy	±0.5%	
Port Style Barbless Features Amplified Output, Temperature Compensated Termination Style PCB Maximum Pressure ±5 PSI (±34.47 kPa) Operating Temperature -40°C ~ 125°C Package / Case 4-SIP Module Supplier Device Package	Voltage - Supply	4.5 V ~ 5.5 V	
FeaturesAmplified Output, Temperature CompensatedTermination StylePCBMaximum Pressure ± 5 PSI (± 34.47 kPa)Operating Temperature -40° C $\sim 125^{\circ}$ CPackage / Case 4 -SIP ModuleSupplier Device Package $-$	Port Size	Male - 0.19" (4.8mm) Tube, Dual	
Termination Style PCB Maximum Pressure ± 5 PSI (± 34.47 kPa) Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Package / Case 4-SIP Module Supplier Device Package	Port Style	Barbless	
Maximum Pressure ± 5 PSI (± 34.47 kPa)Operating Temperature -40° C $\sim 125^{\circ}$ CPackage / Case 4 -SIP ModuleSupplier Device Package $-$	Features	Amplified Output, Temperature Compensated	
Operating Temperature-40°C ~ 125°CPackage / Case4-SIP ModuleSupplier Device Package-	Termination Style	PCB	
Package / Case 4-SIP Module Supplier Device Package -	Maximum Pressure	±5 PSI (±34.47 kPa)	
Supplier Device Package -	Operating Temperature	-40°C ~ 125°C	
	Package / Case	4-SIP Module	
Report errors?	Supplier Device Package	-	
		F	Report errors?

0.3 PSI-D-4V-MIL Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

0.3 PSI-D-4V-MIL Payment Methods



















0.3 PSI-D-4V-MIL Shipping Methods













If you have any question about 0.3 PSI-D-4V-MIL, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com