

0.3 PSI-G-4V-PRIME

0.3 PSI-G-4V-PRIME Information



Part Number	0.3 PSI-G-4V-PRIME	
Manufacturer	All Sensors Corporation	
Category	Sensors, Transducers Pressure Sensors, Transducers	
Description	SENSOR 0.3PSIG 4V DUAL	
Package	4-SIP Module	
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



0.3 PSI-G-4V-PRIME Specifications

Manufacturer Part Number 0.3 PSI-G-4V-PRIME Manufacturer All Sensors Corporation Category Sensors, Transducers Package 4SIP Module Series AXCA Pressure Sensors, Transducers Vented Gauge Operating Pressure 0.3 PSI (2.07 kPa) Output Type Analog Voltage Output Type Analog Voltage Output 0.25 V ~ 4.25 V Accuracy 4.51 V ~ 5.5 V Port Size Male Output, Temperature Compensated Port Size Amplified Output, Temperature Compensated Port Size SPSI (3.47 kPa) Operating Temperature 4.50° C ~ 215°C Package / Case 4.51P Module		
CategorySensors, TransducersPackage4-SIP ModulePackage4-SIP ModuleSeriesAXCAPressure TypeVented GaugeOperating Pressure0.3 PSI (2.07 kPa)Output TypeAnalog VoltageOutput0.25 V ~ 4.25 VAccuracy±0.5%Voltage - SupplyAsch - 0.19" (4.8mm) TubePort SizeMarlief Output, Temperature CompensatedPort StyleBarblessTermination Style5 PSI (34.47 kPa)Operating Temperature-40°C ~ 125°CPackage / Case-Supplier Device Package-	Manufacturer Part Number	0.3 PSI-G-4V-PRIME
PackagePressure Sensors, TransducersPackage4-SIP ModuleSeriesAXCAPressure TypeVented GaugeOperating Pressure0.3 PSI (2.07 kPa)Output TypeAnalog VoltageOutput0.25 V ~ 4.25 VAccuracy±0.5%Voltage - Supply4.5 V ~ 5.5 VPort SizeMale - 0.19" (4.8mm) TubePort StyleBarblessFeaturesAmplified Output, Temperature CompensatedMaximum Pressure5 PSI (34.47 kPa)Operating Temperature-40°C ~ 125°CPackage / Case-Supplier Device Package-	Manufacturer	All Sensors Corporation
Package4-SIP ModuleSeriesAXCAPressure TypeVented GaugeOperating Pressure0.3 PSI (2.07 kPa)Output TypeAnalog VoltageOutput0.25 V ~ 4.25 VAccuracy±0.5%Voltage - SupplyAsol vo.19" (4.8mm) TubePort SizeMale - 0.19" (4.8mm) TubePort StyleBarblessFeaturesAmplified Output, Temperature CompensatedMaximum Pressure5 PSI (34.47 kPa)Operating Temperature-40°C ~ 125°CPackage / Case-Supplier Device Package-	Category	Sensors, Transducers
SeriesAXCAPressure TypeVented GaugeOperating Pressure0.3 PSI (2.07 kPa)Output TypeAnalog VoltageOutput0.25 V ~ 4.25 VAccuracy±0.5%Voltage - Supply4.5 V ~ 5.5 VPort SizeMale - 0.19" (4.8mm) TubePort StyleBarblessFeaturesAmplified Output, Temperature CompensatedTermination Style9CBMaximum Pressure5 PSI (34.47 kPa)Operating Temperature-40°C ~ 125°CPackage / Case4.SIP ModuleSupplier Device Package-		Pressure Sensors, Transducers
Pressure TypeVented GaugeOperating Pressure0.3 PSI (2.07 kPa)Output TypeAnalog VoltageOutput0.25 V ~ 4.25 VAccuracy±0.5%Voltage - Supply4.5 V ~ 5.5 VPort SizeMale - 0.19" (4.8mm) TubePort StyleBarblessFeaturesAmplified Output, Temperature CompensatedTermination Style5 PSI (34.47 kPa)Operating Temperature-40°C ~ 125°CPackage / Case-Supplier Device Package-	Package	4-SIP Module
Operating Pressure0.3 PSI (2.07 kPa)Output TypeAnalog VoltageOutput0.25 V ~ 4.25 VAccuracy±0.5%Voltage - Supply4.5 V ~ 5.5 VPort SizeMale - 0.19" (4.8mm) TubePort StyleBarblessFeaturesAmplified Output, Temperature CompensatedTermination Style5 PSI (34.47 kPa)Operating Temperature-40°C ~ 125°CPackage / Case4.SIP ModuleSupplier Device Package-	Series	AXCA
Output TypeAnalog VoltageOutput0.25 V ~ 4.25 VAccuracy±0.5%Voltage - Supply4.5 V ~ 5.5 VPort SizeMale - 0.19" (4.8mm) TubePort StyleBarblessFeaturesAmplified Output, Temperature CompensatedTermination Style9CBMaximum Pressure5 PSI (34.47 kPa)Operating Temperature-40°C ~ 125°CPackage / Case4-SIP ModuleSupplier Device Package-	Pressure Type	Vented Gauge
Output0.25 V ~ 4.25 VAccuracy±0.5%Voltage - Supply4.5 V ~ 5.5 VPort SizeMale - 0.19" (4.8mm) TubePort StyleBarblessFeaturesAmplified Output, Temperature CompensatedTermination StylePCBMaximum Pressure5 PSI (34.47 kPa)Operating Temperature-40°C ~ 125°CPackage / Case4-SIP ModuleSupplier Device Package-	Operating Pressure	0.3 PSI (2.07 kPa)
Accuracy±0.5%Voltage - Supply4.5 V ~ 5.5 VPort SizeMale - 0.19" (4.8mm) TubePort StyleBarblessFeaturesAmplified Output, Temperature CompensatedTermination StylePCBMaximum Pressure5 PSI (34.47 kPa)Operating Temperature-40°C ~ 125°CPackage / Case4-SIP ModuleSupplier Device Package-	Output Type	Analog Voltage
Voltage - Supply4.5 V ~ 5.5 VPort SizeMale - 0.19" (4.8mm) TubePort StyleBarblessFeaturesAmplified Output, Temperature CompensatedTermination StylePCBMaximum Pressure5 PSI (34.47 kPa)Operating Temperature-40°C ~ 125°CPackage / Case4-SIP ModuleSupplier Device Package-	Output	0.25 V ~ 4.25 V
Port SizeMale - 0.19" (4.8mm) TubePort StyleBarblessFeaturesAmplified Output, Temperature CompensatedTermination StylePCBMaximum Pressure5 PSI (34.47 kPa)Operating Temperature-40°C ~ 125°CPackage / Case4-SIP ModuleSupplier Device Package-	Accuracy	$\pm 0.5\%$
Port StyleBarblessFeaturesAmplified Output, Temperature CompensatedTermination StylePCBMaximum Pressure5 PSI (34.47 kPa)Operating Temperature-40°C ~ 125°CPackage / Case4-SIP ModuleSupplier Device Package-	Voltage - Supply	4.5 V ~ 5.5 V
FeaturesAmplified Output, Temperature CompensatedTermination StylePCBMaximum Pressure5 PSI (34.47 kPa)Operating Temperature-40°C ~ 125°CPackage / Case4-SIP ModuleSupplier Device Package-	Port Size	Male - 0.19" (4.8mm) Tube
Termination StylePCBMaximum Pressure5 PSI (34.47 kPa)Operating Temperature-40°C ~ 125°CPackage / Case4-SIP ModuleSupplier Device Package-	Port Style	Barbless
Maximum Pressure5 PSI (34.47 kPa)Operating Temperature-40°C ~ 125°CPackage / Case4-SIP ModuleSupplier Device Package-	Features	Amplified Output, Temperature Compensated
Operating Temperature-40°C ~ 125°CPackage / Case4-SIP ModuleSupplier Device Package-	Termination Style	PCB
Package / Case 4-SIP Module Supplier Device Package -	Maximum Pressure	5 PSI (34.47 kPa)
Supplier Device Package -	Operating Temperature	-40°C ~ 125°C
	Package / Case	4-SIP Module
Report errors	Supplier Device Package	-
		Report errors?

0.3 PSI-G-4V-PRIME Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

0.3 PSI-G-4V-PRIME Payment Methods



0.3 PSI-G-4V-PRIME Shipping Methods



If you have any question about 0.3 PSI-G-4V-PRIME, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com