

0015445114

equest a Quote

0015445114 Information

Heisener.com	Part Number	0015445114	
	Manufacturer	Molex, LLC	
	Category	Connectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female Sockets	
	Description	CONN RCPT 14POS .100 VERT T/H	
	Package	-	
For Reference Only		For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com	
		E-mail: salesdept@heisener.com	

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



0015445114 Specifications

Manufacturer Part Number0015445114ManufacturerMolex, LLCCategoryConnectors, InterconnectsPackage-Package-SeriesCordr? 71850Connector TypeReceptacleContact TypeFemale SocketStyleBoard to Board or CableNumber of Positions14Number of Positions Loaded0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough HoleMounting TypeSolderFastening TypeQuin (0.76um)Fastening TypeSolderFastening TypeSoldin (0.76um)Contact Finish - MatingSoldin (0.76um)Contact Finish Thickness - MatingSoldin (0.76um)Contact Finish Thickness - MatingBoard Contact PackaContact Finish Thickness			
CategoryConnectors, InterconnectsRectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesC-Grid? 71850Connector TypeReceptacleContact TypeFemale SocketStyleBoard to Board or CableNumber of PositionsAllNumber of Positions Loaded1Number of Rows2Row Spacing - Mating0.100° (2.54mm)Mounting TypeSolderTerminationSolderFastening TypeOlderContact Finish - MatingGoldContact Finish - MatingSolderState TypeSolderState TypeSolderState TypeSolderContact Finish - MatingGoldContact Finish - MatingSolin (0.76µm)Contact Finish - MatingSolin (0.76µm)	Manufacturer Part Number	0015445114	
NumberRectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesC-Grid? 71850Connector TypeReceptacleContact TypeFemale SocketStyleBoard to Board or CableNumber of Positions14Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish - MatingSolup (0.76µm)	Manufacturer	Molex, LLC	
Package-SeriesC-Grid? 71850Connector TypeReceptacleContact TypeFemale SocketStyleBoard to Board or CableNumber of Positions14Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough HoleFastening TypeSolderFastening TypeGoldContact Finish - MatingGoldSolur (2.54mm)Solur)	Category	Connectors, Interconnects	
SeriesC-Grid? 71850Sonector TypeReceptacleContact TypeFemale SocketStyleBoard to Board or CableNumber of Positions14Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough HoleFastening TypeSolderFastening TypeGoldContact Finish - MatingGoldSolman Contact Finish - MatingSolim (0.76µm)		Rectangular Connectors - Headers, Receptacles, Female Sockets	
Connector TypeReceptacleContact TypeFemale SocketStyleBoard to Board or CableNumber of Positions14Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeSolderFareninationSolderFastening TypeGoldContact Finish - MatingSolderContact Finish - MatingSolym (0.76µm)	Package	-	
Contact TypeFemale SocketStyleBoard to Board or CableNumber of Positions14Number of Positions LoadedAllPitch - Mating0.100° (2.54mm)Number of Rows2Row Spacing - Mating0.100° (2.54mm)Mounting Type0.100° (2.54mm)Fastening TypeSolderFastening TypePush-PullContact Finish - MatingGoldYoung Contact Finish Thickness - Mating30µin (0.76µm)	Series	C-Grid? 71850	
StyleBoard to Board or CableNumber of Positions14Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting Type0.100" (2.54mm)TerminationSolderFastening TypePush-PullContact Finish - MatingGoldYoung Contact Finish - Mating30µin (0.76µm)	Connector Type	Receptacle	
Number of Positions14Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeOn00" (2.54mm)TerminationSolderFastening TypePush-PullContact Finish - MatingGoldSolup (0.76µm)Solup (0.76µm)	Contact Type	Female Socket	
Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldYour Contact Finish - Mating30µin (0.76µm)	Style	Board to Board or Cable	
Pitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldKontact Finish - Mating30µin (0.76µm)	Number of Positions	14	
Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)	Number of Positions Loaded	All	
Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)	Pitch - Mating	0.100" (2.54mm)	
Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)	Number of Rows	2	
TerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)	Row Spacing - Mating	0.100" (2.54mm)	
Fastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30μin (0.76μm)	Mounting Type	Through Hole	
Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)	Termination	Solder	
Contact Finish Thickness - Mating 30µin (0.76µm)	Fastening Type	Push-Pull	
	Contact Finish - Mating	Gold	
Insulation Color Plack	Contact Finish Thickness - Mating	30µin (0.76µm)	
Institution Color Diack	Insulation Color	Black	
Insulation Height 0.340" (8.64mm)	Insulation Height	0.340" (8.64mm)	
Contact Length - Post 0.120" (3.05mm)	Contact Length - Post	0.120" (3.05mm)	
Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Operating Temperature	-40°C ~ 125°C	
Material Flammability Rating UL94 V-0	Material Flammability Rating	UL94 V-0	

Contact Finish - Post	Tin		
Mated Stacking Heights	-		
Ingress Protection	-		
Features	-		
			Report errors?

0015445114 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about 0015445114, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com