

0022182174

est a Quote

0022182174 Information

Container com	Part Number	0022182174
	Manufacturer	Molex, LLC
	Category	Connectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female Sockets
	Description	KK 100 PCB ASSY TOP 17POS GOLD
	Package	-
For Reference Only		For the pricing/inventory/lead time, please contact us
		Website: https://www.heisener.com E-mail: salesdept@heisener.com

Certified Quality


Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



0022182174 Specifications

Manufacturer Part Number0022182174ManufacturerMolex, LLCCategoryConnectors, InterconnectsPackage-SeriesKK? 4455Connector TypeReceptacleContact TypeNon-GenderedStyleBoard to Board or CableNumber of Positions1Number of Rows1Number of Rows1Number of Rows1Number of RowsSolderTerminationSolderStoring TypeSolderContact Firish Thickness - MatingGoldContact Firish Thickness - MatingGoldContact Firish Thickness - MatingGoldContact Firish Thickness - Mating0.101° (2.54mm)Contact Firish Thickness - MatingSolderContact Firish Thickness - MatingGoldContact Firish Thickness - MatingGoldContact Length - Post0.132° (3.55mm)Contact Length - Post0.132° (3.55mm)Contact Length - PostMating - MatingContact Length - Post0.132° (3.55mm)Contact Length - Post0.132° (3.55mm)Contact Length - PostMating - MatingContact Length - PostMating - Mating -		
CategoryConnectors, InterconnectsRectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesKK? 4455Contact TypeReceptacleContact TypeNon-GenderedStyleSoral to Board or CableNumber of Positions7Number of Positions LoadedAllPitch - Mating0.100"(2.54mm)Number of Rows1Number of Rows0.100"(2.54mm)Number of Rows1Pitch JatingSolderYouring TypeSolderFerminationSolderContact Finish - MatingGoldContact Finish - MatingGoldContact Finish - MatingJatin (7.60mn)Insulation ColorMiteInsulation Finish - MatingSolar (3.55mn)	Manufacturer Part Number	0022182174
Rectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesKK? 4455Connector TypeReceptacleContact TypeNon-GenderedStyleBoard to Board or CableNumber of Positions17Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypeQuán (0.76µm)Contact Finish - MatingGoldContact Finish Thickness - MatingJuin (0.76µm)Insulation ColorWhiteInsulation Height0.311" (7.90mm)Contact Length - Post0.132" (3.35mm)	Manufacturer	Molex, LLC
Package-SeriesKK? 4455Connector TypeReceptacleContact TypeNon-GenderedStyleBoard to Board or CableNumber of Positions17Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypeGoldContact Finish - Mating30µin (0.76µm)Insulation ColorMiteInsulation Height0.311" (7.90mm)Contact Length - Post0.132" (3.35mm)	Category	Connectors, Interconnects
SeriesKK? 4455Connector TypeReceptacleContact TypeNon-GenderedStyleBoard to Board or CableNumber of Positions17Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleFastening TypeSolderContact Finish - MatingGoldContact Finish - MatingGoldInsulation ColorMineInsulation ColorMineInsulation Height0.311" (7.90mm)Contact Length - Post0.132" (3.35mm)		Rectangular Connectors - Headers, Receptacles, Female Sockets
Connector TypeReceptacleContact TypeNon-GenderedStyleBoard to Board or CableNumber of Positions17Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypeOut (0.54mm)Contact Finish - MatingGoldContact Finish - MatingOut (0.54mm)Insulation ColorSolderInsulation Finish Thickness - MatingSolderInsulation Height0.311" (7.90mm)Contact Length - Post0.132" (3.35mm)	Package	-
Contact TypeNon-GenderedStyleBoard to Board or CableNumber of Positions17Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeSolderFareninationSolderFastening TypePush-PullContact Finish - MatingGoldInsulation ColorMineInsulation Height0.311" (7.90mm)Contact Length - Post0.132" (3.55mm)	Series	KK? 4455
StyleBoard to Board or CableNumber of Positions17Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - Mating30µin (0.76µm)Insulation ColorWhiteInsulation Height0.311" (7.90mm)Contact Length - Post0.132" (3.35mm)	Connector Type	Receptacle
Yumber of Positions17Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldInsulation ColorWhiteInsulation Height0.311" (7.90mm)Contact Length - Post0.132" (3.35mm)	Contact Type	Non-Gendered
Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Insulation ColorWhiteInsulation Height0.311" (7.90mm)Contact Length - Post0.132" (3.35mm)	Style	Board to Board or Cable
Pitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting Type-TerminationSolderFastening TypePush-PullContact Finish - MatingSoljin (0.76µm)Insulation ColorWhiteInsulation Height0.311" (7.90mm)Contact Length - Post0.132" (3.35mm)	Number of Positions	17
Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingJujin (0.76µm)Insulation Color0.311" (7.90mm)Contact Length - Post0.132" (3.35mm)	Number of Positions Loaded	All
Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Insulation ColorWhiteInsulation Height0.311" (7.90mm)Contact Length - Post0.132" (3.35mm)	Pitch - Mating	0.100" (2.54mm)
Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Insulation ColorWhiteInsulation Height0.311" (7.90mm)Contact Length - Post0.132" (3.35mm)	Number of Rows	1
TerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Insulation ColorWhiteInsulation Height0.311" (7.90mm)Contact Length - Post0.132" (3.35mm)	Row Spacing - Mating	-
Fastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Insulation ColorWhiteInsulation Height0.311" (7.90mm)Contact Length - Post0.132" (3.35mm)	Mounting Type	Through Hole
Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Insulation ColorWhiteInsulation Height0.311" (7.90mm)Contact Length - Post0.132" (3.35mm)	Termination	Solder
Contact Finish Thickness - Mating30µin (0.76µm)Insulation ColorWhiteInsulation Height0.311" (7.90mm)Contact Length - Post0.132" (3.35mm)	Fastening Type	Push-Pull
Insulation ColorWhiteInsulation Height0.311" (7.90mm)Contact Length - Post0.132" (3.35mm)	Contact Finish - Mating	Gold
Insulation Height0.311" (7.90mm)Contact Length - Post0.132" (3.35mm)	Contact Finish Thickness - Mating	30µin (0.76µm)
Contact Length - Post 0.132" (3.35mm)	Insulation Color	White
• • • • • • • • • • • • • • • • • • •	Insulation Height	0.311" (7.90mm)
Operating Temperature 40° C 105° C	Contact Length - Post	0.132" (3.35mm)
-40 C ~ 105 C	Operating Temperature	-40°C ~ 105°C
Material Flammability Rating UL94 V-0	Material Flammability Rating	UL94 V-0

Features	Board Hooks
Ingress Protection	-
Mated Stacking Heights	-
Contact Finish - Post	Tin



If you have any question about 0022182174, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com