

## **0089000425 Information**

Heisener.com

**Part Number** 0089000425 **Manufacturer** Molex, LLC

Category Connectors, Interconnects

Terminals - PC Pin, Single Post Connectors

**Description** CONN PC PIN SQUARE 0.025 GOLD

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# 0089000425 Specifications

Manufacturer Part Number         0089000425           Manufacturer         Molex, LLC           Category         Connectors, Interconnects           Package         -           Series         KK? 2766           Terminal Type         Single Post           Terminal Style         Smooth           Pin Size - Above Flange         0.025" (0.64mm) Square           Pin Size - Below Flange         0.025" (0.64mm) Square           Length - Above Flange         -           Length - Below Flange         -           Length - Overall         0.650" (16.51mm)           Flange Diameter         -           Mounting Hole Diameter         0.029" ~ 0.031" (0.74mm ~ 0.79mm)           Mounting Type         Through Hole           Termination         Press-Fit           Insulation         Non-Insulated           Board Thickness         0.062" (1.57mm)           Contact Material         Brass           Contact Finish Thickness         20µin (0.51µm)	•	
Category         Connectors, Interconnects           Package         -           Series         KK? 2766           Terminal Type         Single Post           Terminal Style         Smooth           Pin Size - Above Flange         0.025" (0.64mm) Square           Pin Size - Below Flange         0.025" (0.64mm) Square           Length - Above Flange         -           Length - Below Flange         -           Length - Overall         0.650" (16.51mm)           Flange Diameter         -           Mounting Hole Diameter         0.029" ~ 0.031" (0.74mm ~ 0.79mm)           Mounting Type         Through Hole           Termination         Press-Fit           Insulation         Non-Insulated           Board Thickness         0.062" (1.57mm)           Contact Material         Brass           Contact Finish         Gold           Contact Finish Thickness         20µin (0.51µm)	Manufacturer Part Number	0089000425
Package-SeriesKK? 2766Terminal TypeSingle PostTerminal StyleSmoothPin Size - Above Flange0.025" (0.64mm) SquarePin Size - Below Flange0.025" (0.64mm) SquareLength - Above Flange-Length - Below Flange-Length - Overall0.650" (16.51mm)Flange Diameter-Mounting Hole Diameter0.029" ~ 0.031" (0.74mm ~ 0.79mm)Mounting TypeThrough HoleTerminationPress-FitInsulationNon-InsulatedBoard Thickness0.062" (1.57mm)Contact MaterialBrassContact FinishGoldContact Finish Thickness20μin (0.51μm)	Manufacturer	Molex, LLC
Package         -           Series         KK? 2766           Terminal Type         Single Post           Terminal Style         Smooth           Pin Size - Above Flange         0.025" (0.64mm) Square           Pin Size - Below Flange         -           Length - Above Flange         -           Length - Below Flange         -           Length - Overall         0.650" (16.51mm)           Flange Diameter         -           Mounting Hole Diameter         0.029" ~ 0.031" (0.74mm ~ 0.79mm)           Mounting Type         Through Hole           Termination         Press-Fit           Insulation         Non-Insulated           Board Thickness         0.062" (1.57mm)           Contact Material         Brass           Contact Finish         Gold           Contact Finish Thickness         20μin (0.51μm)	Category	Connectors, Interconnects
Series         KK? 2766           Terminal Type         Single Post           Terminal Style         Smooth           Pin Size - Above Flange         0.025" (0.64mm) Square           Pin Size - Below Flange         0.025" (0.64mm) Square           Length - Above Flange         -           Length - Below Flange         -           Length - Overall         0.650" (16.51mm)           Flange Diameter         -           Mounting Hole Diameter         0.029" ~ 0.031" (0.74mm ~ 0.79mm)           Mounting Type         Through Hole           Termination         Press-Fit           Insulation         Non-Insulated           Board Thickness         0.062" (1.57mm)           Contact Material         Brass           Contact Finish         Gold           Contact Finish Thickness         20μin (0.51μm)		Terminals - PC Pin, Single Post Connectors
Terminal TypeSingle PostTerminal StyleSmoothPin Size - Above Flange0.025" (0.64mm) SquarePin Size - Below Flange0.025" (0.64mm) SquareLength - Above Flange-Length - Below Flange-Length - Overall0.650" (16.51mm)Flange Diameter-Mounting Hole Diameter0.029" ~ 0.031" (0.74mm ~ 0.79mm)Mounting TypeThrough HoleTerminationPress-FitInsulationNon-InsulatedBoard Thickness0.062" (1.57mm)Contact MaterialBrassContact FinishGoldContact Finish Thickness20μin (0.51μm)	Package	-
Terminal StyleSmoothPin Size - Above Flange0.025" (0.64mm) SquarePin Size - Below Flange0.025" (0.64mm) SquareLength - Above Flange-Length - Below Flange-Length - Overall0.650" (16.51mm)Flange Diameter-Mounting Hole Diameter0.029" ~ 0.031" (0.74mm ~ 0.79mm)Mounting TypeThrough HoleTerminationPress-FitInsulationNon-InsulatedBoard Thickness0.062" (1.57mm)Contact MaterialBrassContact FinishGoldContact Finish Thickness20μin (0.51μm)	Series	KK? 2766
Pin Size - Above Flange0.025" (0.64mm) SquarePin Size - Below Flange0.025" (0.64mm) SquareLength - Above Flange-Length - Below Flange-Length - Overall0.650" (16.51mm)Flange Diameter-Mounting Hole Diameter0.029" ~ 0.031" (0.74mm ~ 0.79mm)Mounting TypeThrough HoleTerminationPress-FitInsulationNon-InsulatedBoard Thickness0.062" (1.57mm)Contact MaterialBrassContact FinishGoldContact Finish Thickness20µin (0.51µm)	Terminal Type	Single Post
Pin Size - Below Flange0.025" (0.64mm) SquareLength - Above Flange-Length - Below Flange-Length - Overall0.650" (16.51mm)Flange Diameter-Mounting Hole Diameter0.029" ~ 0.031" (0.74mm ~ 0.79mm)Mounting TypeThrough HoleTerminationPress-FitInsulationNon-InsulatedBoard Thickness0.062" (1.57mm)Contact MaterialBrassContact FinishGoldContact Finish Thickness20μin (0.51μm)	Terminal Style	Smooth
Length - Above Flange-Length - Below Flange-Length - Overall0.650" (16.51mm)Flange Diameter-Mounting Hole Diameter0.029" ~ 0.031" (0.74mm ~ 0.79mm)Mounting TypeThrough HoleTerminationPress-FitInsulationNon-InsulatedBoard Thickness0.062" (1.57mm)Contact MaterialBrassContact FinishGoldContact Finish Thickness20μin (0.51μm)	Pin Size - Above Flange	0.025" (0.64mm) Square
Length - Below Flange-Length - Overall0.650" (16.51mm)Flange Diameter-Mounting Hole Diameter0.029" ~ 0.031" (0.74mm ~ 0.79mm)Mounting TypeThrough HoleTerminationPress-FitInsulationNon-InsulatedBoard Thickness0.062" (1.57mm)Contact MaterialBrassContact FinishGoldContact Finish Thickness20μin (0.51μm)	Pin Size - Below Flange	0.025" (0.64mm) Square
Length - Overall $0.650"$ ( $16.51mm$ )Flange Diameter-Mounting Hole Diameter $0.029" \sim 0.031"$ ( $0.74mm \sim 0.79mm$ )Mounting TypeThrough HoleTerminationPress-FitInsulationNon-InsulatedBoard Thickness $0.062"$ ( $1.57mm$ )Contact MaterialBrassContact FinishGoldContact Finish Thickness $20μin$ ( $0.51μm$ )	Length - Above Flange	-
Flange Diameter  Mounting Hole Diameter  0.029" ~ 0.031" (0.74mm ~ 0.79mm)  Mounting Type  Through Hole  Termination  Press-Fit  Insulation  Non-Insulated  Board Thickness  0.062" (1.57mm)  Contact Material  Brass  Contact Finish  Gold  Contact Finish Thickness  20µin (0.51µm)	Length - Below Flange	-
Mounting Hole Diameter $0.029" \sim 0.031" (0.74 mm \sim 0.79 mm)$ Mounting TypeThrough HoleTerminationPress-FitInsulationNon-InsulatedBoard Thickness $0.062" (1.57 mm)$ Contact MaterialBrassContact FinishGoldContact Finish Thickness $20μin (0.51μm)$	Length - Overall	0.650" (16.51mm)
Mounting TypeThrough HoleTerminationPress-FitInsulationNon-InsulatedBoard Thickness0.062" (1.57mm)Contact MaterialBrassContact FinishGoldContact Finish Thickness20μin (0.51μm)	Flange Diameter	-
TerminationPress-FitInsulationNon-InsulatedBoard Thickness0.062" (1.57mm)Contact MaterialBrassContact FinishGoldContact Finish Thickness20μin (0.51μm)	Mounting Hole Diameter	0.029" ~ 0.031" (0.74mm ~ 0.79mm)
InsulationNon-InsulatedBoard Thickness0.062" (1.57mm)Contact MaterialBrassContact FinishGoldContact Finish Thickness20μin (0.51μm)	Mounting Type	Through Hole
Board Thickness0.062" (1.57mm)Contact MaterialBrassContact FinishGoldContact Finish Thickness20μin (0.51μm)	Termination	Press-Fit
Contact MaterialBrassContact FinishGoldContact Finish Thickness20μin (0.51μm)	Insulation	Non-Insulated
Contact FinishGoldContact Finish Thickness20μin (0.51μm)	Board Thickness	0.062" (1.57mm)
Contact Finish Thickness 20μin (0.51μm)	Contact Material	Brass
	Contact Finish	Gold
Report errors?	Contact Finish Thickness	20μin (0.51μm)
		Report errors?

### **0089000425 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### 0089000425 Payment Methods



















## 0089000425 Shipping Methods













If you have any question about 0089000425, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com